F.No.21-18/2016-IA-III Government of India Ministry of Environment, Forest and Climate Change (IA.III Section)

Indira Paryavaran Bhawan, Jor Bagh Road, New Delhi - 3

Date: 8th June, 2017

To,

M/s Viva Patil Real Estate & M/s Dreams Realtors,

Viva Homes, 2nd Floor, Thakur Arcade, Raja Shivaji Road, Virar West - 401303 Maharashtra

Email: mithun@vivagroup.in

Subject:

Residential Development with Shop Line at Gut No. 50, Plot No.2 of Village Kambalgaon, Taluka Palghar, District Palghar, Maharashtra by M/s Viva Patil Real Estate & M/s Dreams Realtors - Environmental Clearance - reg.

Sir,

This has reference to your online proposal No. IA/MH/MIS/60053/2016 dated 28th October, 2016, submitting the above proposal to this Ministry for grant of Environmental Clearance (EC) in term of the provisions of the Environment Impact Assessment (EIA) Notification, 2006 under the Environment (Protection) Act, 1986.

- 2. The proposal for grant of environmental clearance to the project 'Residential Development with Shop Line' at Gut No. 50, Plot No.2 of Village Kambalgaon, Taluka Palghar, District Palghar, Maharashtra promoted by M/s Viva Patil Real Estate & M/s Dreams Realtors, was considered by the Expert Appraisal Committee (Infra-2) in its meetings held on 24^{th-}25th November, 2016 and 13th-15th February, 2017. The details of the project, as per the documents submitted by the project proponent, and also as informed during the above meeting, are under:-
- (i) The project involves construction of residential development with shop line at Gut No. 50, Plot No.2 of Village Kambalgaon, Taluka Palghar, District Palghar, Maharashtra promoted by M/s Viva Patil Real Estate & M/s Dreams Realtors. The project is located at 19°46'15.20"N Latitude and 72°46'25.46" E Longitude.
- (ii) The total plot area is 68,456.58 m². FSI area is 75,149.88 m² and total construction built up area is 92,584.40 m². The project comprises 105 residential buildings having 2234 tenements and 942.65 m² of commercial area. Maximum height of the building is 14.85 m. Configuration of building is as given below.

S. No.	Building Type	No of buildings	Building Configuration	No. of Flats
1	A	46	G(P)+STILT(P)+4	828
2	A1	3	G(P)+STILT(P)+4	48
3	В	20	G(P)+STILT(P)+4	380
4	С	29	G(P)+STILT(P)+4	812
5	C1	5	G(P)+STILT(P)+4	130
6	D	2	Gr+4	36
Total		105		2234

- (iii) It is noted that no eco-sensitive area is located within 15 km distance of project site. Water bodies namely Surya River (8 km) and Arbian sea (9 km) are located within 10 km distance.
- (iv) Water requirement during construction phase, is around 90 KLD which will be met by tanker water. During the construction phase, soak pits and septic tanks will be provided for disposal of waste water. During operational phase, total water demand of the project is expected to be 1516 KLD and same will be met by fresh water from Maharashtra Jeevan Pradhikaran and recycled water.
- (v) Wastewater generated (1416 KLD) will be treated in STP of 1500 KLD capacity. 508 KLD of treated wastewater will be recycled for flushing. About 861 KLD will be discharged in Municipal sewer lines.
- (vi) About 5,623 kg/d solid waste will be generated in the project. The STP based on PHYTORID based technology will be installed. The biodegradable waste (3,374 kg/d) will be processed in mechanical composting (Eco-biocompack) and the non-biodegradable waste generated (2,249 kg/d) will be handed over to authorized local vendor. Space earmarked for solid waste management is 170 m².
- (vii) The total power requirement during construction phase is 250 kVA and will be met from MSEDCL and Total power requirement during operation phase is 6 MW (Demand Load) and will be met from MSEDCL. DG set capacity is 340 KVA. It is proposed that at least 2 solar powered lights and one fan will be provided to each flat.
- (viii) Rooftop rainwater of building will be collected in 9 nos. rain water harvesting tanks of total capacity 740 KL and the overflow from the RWH tank will be channeled to the ground water recharge pit.
- (ix) Parking facility for 9 four wheelers, 2820 two wheelers and 2820 cycles are proposed to be provided against the requirement of 9 four wheelers, 2820 two wheelers and 2820 cycles (as per local norms).
- (x) It is proposed to provide 8" AAC blocks in the wall assembly to conform the U value of wall envelop.
- (xi) Cost of project is Rs. 110.00 Crore, out of which, Rs. 795.00 Lakh and Rs. 75.00 Lakh/year are earmarked towards capital cost and recurring cost per annum for implementation of EMP.
- (xii) Proposed energy saving measures would save about 19.55% of power.
- (xiii) There is no court case pending against the project.
- (xiv) Employment potential: 100 Nos.
- (xv) Benefits of the project: The proposed project comprises housing units which will provide quality accommodations to the working population seeking reasonable housing close to major cities such as Mumbai, Thane, Vasai, Virar etc. as well as the Industrial areas at Boisar, Tarapur etc. The project will also create temporary as well as permanent employment opportunities during construction Phase as well as operational phase. It will create long term employment in activities such as maintenance of the buildings and related services.
- 4. The EAC, in its meeting held on 13th-15th February, 2017, after detailed deliberations on the proposal, has recommended for grant of Environmental Clearance to the project. As per recommendations of the EAC, the Ministry of Environment,

Forest and Climate Change hereby accords Environmental Clearance to the project 'Residential Development with Shop Line' at Gut No. 50, Plot No.2 of Village Kambalgaon, Taluka Palghar, District Palghar, Maharashtra promoted by M/s Viva Patil Real Estate & M/s Dreams Realtors, under the provisions of the EIA Notification, 2006 and amendments/circulars issued thereon, and subject to the specific and general conditions as under:-

PART A - SPECIFIC CONDITIONS:

I. Construction Phase

- (i) The project proponent shall obtain all necessary clearance/ permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.
- (ii) The natural drain system should be maintained for ensuring unrestricted flow of water. No construction shall be allowed to obstruct the natural drainage through the site, on wetland and water bodies. Check dams, bio-swales, landscape, and other sustainable urban drainage systems (SUDS) are allowed for maintaining the drainage pattern and to harvest rain water. Buildings shall be designed to follow the natural topography as much as possible. Minimum cutting and filling should be done.
- (iii) Construction site shall be adequately barricaded before the construction begins. Dust, smoke & other air pollution prevention measures shall be provided for the building as well as the site. These measures shall include screens for the building under construction, continuous dust/ wind breaking walls all around the site (at least 3 meter height). Plastic/tarpaulin sheet covers shall be provided for vehicles bringing in sand, cement, murram and other construction materials prone to causing dust pollution at the site as well as taking out debris from the site. Sand, murram, loose soil, cement, stored on site shall be covered adequately so as to prevent dust pollution. Wet jet shall be provided for grinding and stone cutting. Unpaved surfaces and loose soil shall be adequately sprinkled with water to suppress dust.
- (iv) All construction and demolition debris shall be stored at the site (and not dumped on the roads or open spaces outside) before they are properly disposed. All demolition and construction waste shall be managed as per the provisions of the Construction and Demolition Waste Rules, 2016. All workers working at the construction site and involved in loading, unloading, carriage of construction material and construction debris or working in any area with dust pollution shall be provided with dust mask.
- (v) At least 20% of the open spaces as required by the local building bye-laws shall be pervious. Use of Grass pavers, paver blocks with at least 50% opening, landscape etc. would be considered as pervious surface.
- (vi) Compliance with the Energy Conservation Building Code (ECBC) of Bureau of Energy Efficiency shall be ensured. Buildings in the States which have notified their own ECBC, shall comply with the State ECBC. Outdoor and common area lighting shall be LED. Concept of passive solar design that minimize energy consumption in buildings by using design elements, such as building orientation, landscaping, efficient building envelope, appropriate fenestration, increased day

Proposal No. IA/MH/MIS/60053/2016

- lighting design and thermal mass etc. shall be incorporated in the building design. Wall, window, and roof u-values shall be as per ECBC specifications.
- (vii) Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
- (viii) Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
- (ix) Separation of grey and black water should be done by the use of dual plumbing system. In case of single stack system separate recirculation lines for flushing by giving dual plumbing system be done.
- (x) Sewage shall be treated in the STP based on PHYTORID based technology (with tertiary treatment preferably Ultra filtration). The treated effluent from STP shall be recycled/re-used for flushing, horticulture & DG cooling. Excess treated water shall be discharged as per CPCB norms.
- (xi) No sewage/treated effluent from the project site shall be discharged into nearby lake/pond.
- (xii) The local bye-law provisions on rain water harvesting should be followed. If local bye-law provision is not available, adequate provision for storage and recharge should be followed as per the Ministry of Urban Development Model Building Byelaws, 2016. As proposed, 9 nos. of rain water harvesting tanks of total capacity of 740 KL shall be provided.
- (xiii) Separate wet and dry bins must be provided in each unit and at the ground level for facilitating segregation of waste. Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 170 m² of space shall be provided for solid waste management within the premises which will include area for segregation, composting. The inert waste from group housing project will be sent to dumping site.
- (xiv) Solar based electric power shall be provided to each unit for at least two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.
- (xv) A First Aid Room shall be provided in the project both during construction and operations of the project.
- (xvi) Topsoil should be stripped to a depth of 20 cm from the areas proposed for buildings, roads, paved areas, and external services. It should be stockpiled appropriately in designated areas and reapplied during plantation of the proposed vegetation on site.
- (xvii) Disposal of muck during construction phase shall not create any adverse effect on the neighboring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- (xviii) The diesel generator sets to be used during construction phase shall be low sulphur diesel type and shall conform to Environmental (Protection) prescribed for air and noise emission standards.
- (xix) Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.

Waligh

- (xx) As proposed, no ground water shall be used during construction/ operation phase of the project.
- (xxi) Approval of the CGWA require before any dewatering for basements.
- (xxii) The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of firefighting equipment etc as per National Building Code including protection measures from lightening etc.
- (xxiii) Any hazardous waste generated during construction phase, shall be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
- (xxiv) Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.
- (xxv) Ambient noise levels shall conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality shall be closely monitored during construction phase. Adequate measures shall be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
- (xxvi) Use of environment friendly materials in bricks, blocks and other construction materials, shall be required for at least 20% of the construction material quantity. These include Fly Ash bricks, hollow bricks, AACs, Fly Ash Lime Gypsum blocks, Compressed earth blocks, and other environment friendly materials. Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27th August, 2003 and 25th January, 2016. Ready mixed concrete must be used in building construction.
- (xxvii) A comprehensive mobility plan, as per MoUD best practices guidelines (URDPFI), shall be prepared to include motorized, non-motorized, public, and private networks. Road should be designed with due consideration for environment, and safety of users. The road system can be designed with these basic criteria.
 - Hierarchy of roads with proper segregation of vehicular and pedestrian traffic.
 - Traffic calming measures
 - Proper design of entry and exit points.
 - Parking norms as per local regulation

II. Operational Phase

- (i) The gaseous emissions from DG set shall be dispersed through adequate stack height as per CPCB standards. Acoustic enclosure shall be provided to the DG sets to mitigate the noise pollution. Low sulphur diesel shall be used. The location of the DG set and exhaust pipe height shall be as per the provisions of the Central Pollution Control Board (CPCB) norms.
- (ii) For indoor air quality the ventilation provisions as per National Building Code of India.

- (iv) The quantity of fresh water usage, water recycling and rainwater harvesting shall be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports. Fresh water requirement will be 1008 m³/day. Remaining water requirement (541 m³/day) will be recycled/reused for flushing and gardening. Excess treated sewage (861 m³/day) will be discharged to MIDC and agriculture.
- (v) The installation of the Sewage Treatment Plant (STP) shall be certified by an independent expert and a report in this regard shall be submitted to the Ministry before the project is commissioned for operation. Periodical monitoring of water quality of treated sewage shall be conducted. Necessary measures should be made to mitigate the odour problem from STP.
- (vi) The project proponent should take proper safeguards to prevent mosquitoes and other insect pests from breeding and proliferating in the phytorid beds and also for the control of odour from the proposed treatment plant.
- (vii) No sewage or untreated effluent water would be discharged through storm water drains.
- (viii) Sludge from the onsite sewage treatment, including septic tanks, shall be collected, conveyed and disposed as per the Ministry of Urban Development, Central Public Health and Environmental Engineering Organization (CPHEEO) Manual on Sewerage and Sewage Treatment Systems, 2013.
- (ix) The provisions of the Solid Waste (Management) Rules, 2016, e-Waste (Management) Rules, 2016, and the Plastics Waste (Management) Rules, 2016 shall be followed.
- (x) Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power. Solar water heaters shall be used to meet hot water demand, as far as possible.
- (xi) Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED shall be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.
- (xii) A minimum of 1 tree for every 80 sq.mt. of land should be planted and maintained. The existing trees will be counted for this purpose. Preference should be given to planting native species. Where the trees need to be cut, compensatory plantation in the ratio of 1:3 (i.e. planting of 3 trees for every 1 tree that is cut) shall be done and maintained. Area earmarked for green belt is 1024 m².
- (xiii) An environmental management plan (EMP) shall be prepared and implemented to ensure compliance with the environmental conditions specified above. A dedicated Environment Monitoring Cell with defined functions and responsibility shall be put in place to implement the EMP. The environmental cell shall ensure that the environment infrastructure like Sewage Treatment Plant, Landscaping, Rain Water Harvesting, Energy efficiency and conservation, water efficiency and conservation, solid waste management, renewable energy etc. are kept operational and meet the required standards. The environmental cell shall also keep the record of environment monitoring and those related to the environment infrastructure.

PART B - GENERAL CONDITIONS

- (i) A copy of the environmental clearance letter shall also be displayed on the website of the concerned State Pollution Control Board. The EC letter shall also be displayed at the Regional Office, District Industries centre and Collector's Office/ Tehsildar's office for 30 days.
- (ii) The funds earmarked for environmental protection measures shall be kept in separate account and shall not be diverted for other purpose. Year-wise expenditure shall be reported to this Ministry and its concerned Regional Office.
- (iii) Officials from the Regional Office of MoEF&CC, Nagpur who would be monitoring the implementation of environmental safeguards should be given full cooperation, facilities and documents/data by the project proponents during their inspection. A complete set of all the documents submitted to MoEF&CC shall be forwarded to the APCCF, Regional Office of MoEF&CC, Nagpur.
- (iv) In the case of any change(s) in the scope of the project, the project would require a fresh appraisal by this Ministry.
- (v) The Ministry reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.
- (vi) All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, the Forest Conservation Act, 1980 and the Wildlife (Protection) Act, 1972 etc. shall be obtained, as applicable by project proponents from the respective competent authorities.
- (vii) These stipulations would be enforced among others under the provisions of the Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and Control of Pollution) Act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and the EIA Notification, 2006.
- (viii) The project proponent shall advertise in at least two local Newspapers widely circulated in the region, one of which shall be in the vernacular language informing that the project has been accorded Environmental Clearance and copies of clearance letters are available with the State Pollution Control Board and may also be seen on the website of the Ministry of Environment, Forest and Climate Change at http://www.envfor.nic.in. The advertisement shall be made within Seven days from the date of receipt of the Clearance letter and a copy of the same shall be forwarded to the Regional Office of this Ministry at Nagpur.
- (ix) Any appeal against this clearance shall lie with the National Green Tribunal, if preferred, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.
- (x) A copy of the clearance letter shall be sent by the proponent to concerned Panchayat, Zilla Parisad/Municipal Corporation, Urban Local Body and the Local NGO, if any, from whom suggestions/ representations, if any, were received while processing the proposal. The clearance letter shall also be put on the website of the company by the proponent.
- (xi) The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of

Nowigh

- MoEF&CC, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM, SO₂, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.
- (xii) The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the respective Regional Offices of MoEF&CC by e-mail.
- (xiii) This issues with the approval of the Competent Authority.

(Dr. Vinod K. Singh) Scientist D

Copy to:

- 1) The Principal Secretary, Environment Department, Government of Maharashtra, 15th Floor, New Administrative Building, Mantralaya, Mumbai 400 032.
- 2) The APCCF (C), MoEF&CC, Regional Office (WCZ), Ground Floor, East Wing, New Secretariat Building, Civil Lines, Nagpur 440001.
- 3) The Chairman, Central Pollution Control Board Parivesh Bhavan, CBD-cum-Office Complex, East Arjun Nagar, New Delhi 110 032.
- 4) The Chairman, Maharashtra Pollution Control Board, Kalpataru Point, 3rd and 4th floor, Opp. Cine Planet, Sion Circle, Mumbai 400 022.
- 5) Monitoring Cell, MoEF&CC, Indira Paryavaran Bhavan, New Delhi.

6) Guard File/ Record File/ Notice Board.

(Dr. Vinod K. Singh) Scientist D