Minutes of the 13th meeting of Expert Appraisal Committee (Infra-2) for Projects related to All ship breaking yard including ship breaking unit, Airport, Common Hazardous Waste Treatment, Storage and Disposal Facilities, Ports and Harbours, Aerial Ropeways, CETPs, Common Municipal Solid Waste Management Facility, Building/Construction Project, Townships and Area Development projects held on 23-25 January, 2017.

Monday, 23rd January, 2017

13.1. Confirmation of Minutes of 12thEAC Meeting for Infra-2 held on 26-28 December, 2016.

Minutes of 12thEAC Meeting for Infra-2 held on 26-28 December, 2016 were confirmed

13.2. Consideration of Proposals

13.2.1.Deepening the Harbour Basin and Approach Channel to handle 14.5m draught
vessels and Modification of Port Entrance at V.O. Chidambaranar Port Tuticorin,
Tamilnadu by M/s V.O. Chidambaranar Port - TOR -
[IA/TN/MIS/60857/2016][F.No.10-89/2016-IA-III]

The project authorities gave a detailed presentation on the salient features of the project and proposed environmental protection measures to be undertaken along with the draft Term of References for the preparation of EIA-EMP report. All the projects related to Ports and Harbour and dredging are listed at 7(e) of schedule of EIA Notification, 2006 covered under category 'A' and appraised at central level.

M/s V.O. Chidambaranar Port has proposed for deepening the Harbour Basin and Approach Channel to handle 14.5 m draught vessels and Modification of Port Entrance at V.O. Chidambaranar Port Tuticorin, Tamilnadu. The project is located at Latitude: 8° 47' 30" N and Longitude: 78° 12' 15" E.The proposed site is located within the existing Harbour basin. Sufficient area within the existing harbour basin surrounded by breakwaters is available for these proposed developments.Presently, V.O.Chidambaranar Port is having capacity to handle vessels upto (-)12.80 m draught. The (-) 12.80 m draught is available in front of Coal Jetty I & II, Oil Jetty, Berth 8, Berth 9, North Cargo Berths (NCB) I & II. In view of improving the Port capacity, Port decided to increase the vessel draught from existing 12.80m to 14.50m to handle fully loaded Panamax vessels for inner harbour. The Port is also planning to modify (increase its width) the Port entrance to cater safe entry for the larger vessels. The proposed dredging covering the inner harbour basin and approach channel for a length of 10.80 km from Port Entrance to cater the fully loaded Panamax vessels having draught up to (-)14.5m.

Total volume to be dredged is works out to 14.5 Million cu.m.(approx). The reclamation area for this dredging is proposed to be on the south of the existing south breakwater thus making an approach for providing road connectivity, rail connectivity and other utilities to the outer harbour in future. The approximate area to be reclaimed is 131 hectare. The proposed project site is one km away from the sea shore inside the existing harbour basin surrounded by breakwaters. Hence, no land area required for the proposed project. Cost of the project is Rs.3,178.00 Crores. It is reported that eco- sensitive area i.e. Gulf of Mannar Marine National park is located at a distance a distance of 8 km. There is a fishing harbour about 6 kms away from the project site.

PP informed that MoEF&CC vide letter dated 1.10.2014 has issued TOR to them for

		opment of outer harbor a y of TOR extended upto 0		Tuticorin, Tamil Nadu and the
	existir recom to am	ng proposal to evalua nmendations alongwith pu	te the cumulative impact. blic hearing will remain same. er dated 1.10.2014 issued to PF	club the new proposal with the The existing ToR, SCZMA The Committee recommended P. The following additional TOR
		Submit a copy of layou authorized agency on 1:40		LTL map demarcated by an
	ii.	Recommendation of the S	CZMA for both proposals.	
		Copy of application subm km distance of Gulf of Mar		w.r.t. project located within 10
	iv.	Study the impact of dredgi	ng on the shore line.	
	v	A detailed impact analysis	of rock dredging.	
	vi.	•	edging and dumping on main the NIO or any other institute spectrum of the spec	rine ecology and draw up a pecializing in marine ecology.
	vii. A detailed analysis of the physico-chemical and biotic components in the highly turbid waters round the project site (as exhibited in the Google map shown during the presentation), compare it with the physico- chemical and biotic components in the adjacent clearer (blue) waters both in terms of baseline and impact assessment and draw up a management plan.			
13.2.2.	Construction of North Cargo Berth-III, North Cargo Berth-IV and dredging in front of North Cargo Berth-II, North Cargo Berth-III and North Cargo Berth-IV and filling up of dredged material into reclaiming the land inside V.O. Chidambaranar Port Complex, Tamil Nadu - Amendment in Environmental Clearance - [IA/TN/MIS/60458/2015] [F.No.11- 139/2010-IA.III]			
	dated Dredg handl Coal 2010 respe recom Cargo propo appro North	2 nd January, 2015 for co ging. As per the environi- ing Thermal Coal & Rock & Copper Concentrate. No and 2016, Port has cond ct to trade / traffic demand mended that the North Ca b Berth-IV for handling Co ct as recommended by the sed from earlier Environm	Instruction of North Cargo Berth mental clearance received, the Phosphate and North Cargo B ow, due to change in scenario o ducted fresh feasibility study fo d, project cost etc. Based on Tra argo Berth-III shall be developed ntainers and Clean cargoes. Po e consultant. As such there are nental Clearance issued on 02. ance and the present proposal	vide letter No.11-139/2010-IA-III h-III, North Cargo Berth-IV and e North Cargo Berth-III is for eerth-IV is for handling Thermal f cargo traffic between the year or restructuring the project with affic demand the consultant has d for handling of Coal and North ort has proposed to take up the some changes in cargo profile 01.2015. The details on earlier I for North Cargo Berth-III and
		Description	As per Environmental	Present requirement
			Clearance 02.01.2015	
		Berth Size	306m X 22.90m	306m X 22.90m
		Project Cost	Rs.420 Crores	Rss.586.89 Crores
		Cargo to be handled	Thermal Coal & Rock	Coal (Dry bulk cargo)

	Phosphate (Dry bulk cargo)	
Capacity of the Berth	9.15 Million Tonnes	10.22 Million Tonnes
Cargo handling	Grab unloader, Conveyor,	Grab unloader,
equipment	Stacker, Reclaimer, Front	Conveyor, Stacker,
	End Loader	Reclaimer, Front End
		Loader

(B) North Cargo Berth-IV

Description	As per Environmental Clearance 02.01.2015	Present requirement
Berth Size	306m X 22.90m	400m X 25m
Project Cost	Project Cost Rs.355 Crores	
Cargo to be handled	Thermal Coal &Copper	Containers and clean
	Concentrate (Dry bulk cargo)	cargoes
Capacity of Berth	9.15 Million Tonnes	8.62 Million Tonnes
Cargo handling	Grab unloader, Conveyor,	RMQCs, RTGCs,
equipment	Stacker, Reclaimer, Front	Trailers/Prime moves,
	End Loader	Reach stackers,
		Harbour Mobile crane

It is also informed that as for as North Cargo Berth-III is concern, only the project cost & capacity of berth is enhanced. Regarding, North Cargo Berth-IV due to change in cargo profile, from dry bulk cargo to container, the Berth size, Project Cost, Capacity of Berth and Cargo handling equipment evacuation system etc, are changed. However, due to change in cargo from dry bulk to container, the impact on environment will be less. Further, it is informed that there is no change in scope of dredging.

The Committee noted that there is increase in cargo capacity from 9.15 Million Tonnes to 10.22 Million Tonnes. Therefore, it is a case of change in the scope of the project.

The Committee exempted the proposal from public hearing as per Section 7 (ii) of EIA Notification 2006 as public hearing was held for the existing project on 27.12.2013.

After detailed deliberations on the proposal, the Committee recommended project specific TOR for preparation of EIA report:

- (i) Submission of certified compliance report issued by the Regional Office on the environmental conditions stipulated in the earlier EC issued by the MoEF and CC.
- (ii) SCZMA recommendations for the proposed change.
- (iii) Facilities to be provided in the proposed coal cargo.
- (iv) Identify the source of air pollution at proposed cargo berth.
- (v) Details of air pollution control system to be provided at cargo berth.
- (vi) Details of water consumption and its source. Wastewater management scheme.
- (vii) Layout plan of Greenbelt to be created around coal stack yard.
- (viii) Layout plan for drainage system to be included.
- (ix) Solid waste management scheme.
- (x) A Biodiversity Management Plan, from the NIO or any marine Ecology related

	 institute of repute, for conservation of marine ecology as a result of impacts from dredging and dumping. (xi) Details of Environmental Monitoring Plan. (xii) Disaster Management Plan. TOR will be issued after submission of fresh Form1. 				
13.2.3.	Construction of Shimla Passenger Ropeway from Parking Area Near Tourist Information Centre to Mall Road at Tehsil Shimla Urban, Shimla, Himanchal Pradesh by M/s Usha Breco Shimla Ropeway Private Limited- TOR - [IA/HP/MIS/61348/2016][F.No.10-90/2016-IA-III]				
	The project authorities gave a detailed presentation on the salient features of the project and proposed environmental protection measures to be undertaken along with the draft Term of References for the preparation of EIA-EMP report. All the projects related to Aerial Ropeway (Elevation greater than 1000 m) are listed at 7(g) of schedule of EIA Notification, 2006 covered under category 'A' and appraised at central level.				
M/s Usha Breco Shimla Ropeway Private Limited has proposed for Construct Passenger Ropeway from Parking Area Near Tourist Information Centre to Mall F Shimla Urban, Shimla, Himanchal Pradesh. The project is Category A project as an elevation of 2226 m above MSL. Cost of the project is Rs.296 crores.Cost of approx. Rs. 94 Lacs with recurring cost of Rs. 10.1 Lacs/annum. Technology w Monocable Detachable system. The Project is a 3502-m long ropeway, coverin 59345.18 sq m (including four Terminal Stations & ropeway corridor). The propo- shall be developed in two Sections. Section-I consist of LTP - T1 (Parking area Information Center, 2006 m above MSL) to UTP-T-3 (Lift, 2137 m above MSL) via Station - T2 (Tutikandi ISBT, 1970 m above MSL) & Section-II consist of LTP - m above MSL) & UTP- T-4 (Mall Road, 2226 m above MSL). There will be ropeway line from T1 to T4. About 36756.10 sq m (3.68 ha) of area of fores diverted.					
	The alignment falls within a Forest land for development of terminal stations & line towers. About 36756.10 sq m (3.68 ha) of area of forest land will be diverted.				
	Ropeway will have carrying capacity of 1000 persons per hour. Operation of 12 hrs of ropeway is envisaged. Population of 12000 persons/day will use the ropeway. Staff for operation & maintenance to be deployed at project will be about 100 persons. Proper arrangement of water supply and sewage disposal will be made at site. Power Load Requirement will be 2420 KVA. DG sets of capacity 1 X 500 KVA at T1, 1 X 75 KVA at T2, 1 x 1500 KVA at T3 & 1 x 200 KVA at T4 are proposed for backup power supply. These D.G. Sets will be provided with proper stack height as per the CPCB norms.				
	The total water requirement for emergency & other misc. purpose has been estimated as 7 KLD and the source will be municipal supply Water which shall be used mainly for flushing & hand washing, drinking, Gardening & misc. purposes. The generation of total waste water will be 2.8 KLD, which shall be treated in Bio-Toilets provided at Terminal T1 & T4. The treated water of 2.5 KLD obtained from Bio-toilets shall be disposed off in Septic Tank via soak pit provided at Terminal T1 & T4. The location for the water storage tank will be Terminal T-1 & T-4. For drinking water, water cooler/water Dispenser shall be provided at Terminal T-1, T-2, T-3 & T-4.615 Kg/day of municipal waste will be generated of which 430 kg/day of biodegradable waste will be treated in OWCs provided at each of the 4 terminals and converted to compost and 185 kg/day of recyclable waste will be segregated and given to approved recycler. Used				

oil will be given to authorized hazardous waste recycler. Plastic will be minimum used in the area.

There will be no displacement or immigration of the human population due to the proposed project. Risk assessment shall be done and proper safety and security measures shall be undertaken. Proper prevention and timely maintenance of ropes, machines etc will be scheduled to prevent any accident. Maintenance team will be trained to handle any type of contingency in time of emergency. All safety guidelines shall be adhered to and followed during construction and operation phases.

After detailed deliberations on the proposal, the Committee *recommended for grant of Terms of Reference as specified by the Ministry as Standard ToR in April, 2015 for the said project/activity* and the following TOR in addition to *Standard ToR* for preparation of EIA-EMP report:

- i. Importance and benefits of the project.
- ii. A toposheet of the study area of radius of 10km and site location on 1:50,000/1:25,000 scale on an A3/A2 sheet. (including all eco-sensitive areas and environmentally sensitive places)
- iii. Stage I forest clearance to be submitted.
- iv. Toposheet map of 10 km distance indicating eco-sensitive areas dully authenticated by the Wildlife warden.
- v. Route map of proposed ropeway project.
- vi. Layout maps of proposed project indicating location of upper station and lower station, building, food court, parking, greenbelt area, utilities etc.
- vii. Numbers of persons/projections of tourist.
- viii. Cost of project and time of completion.
- ix. A note on appropriate process and materials to be used to encourage reduction in carbon foot print. Optimize use of energy systems in buildings that should maintain a specified indoor environment conducive to the functional requirements of the building by following mandatory compliance measures (for all applicable buildings) as recommended in the Energy conservation building code (ECBC) 2007 of the Bureau of Energy Efficiency, Government of India. The energy system include air conditioning systems, indoor lighting systems, water heaters, air heaters and air circulation devices. Use
- x. Details of air emission, effluents, solid waste and hazardous waste generation and their management.
- xi. Requirement of water, power, with source of supply, status of approval, water balance diagram, man-power requirement (regular and contract)
- xii. The E.I.A. should specifically address to vehicular traffic management and parking facilities.
- xiii. An onsite disaster management plan shall be drawn up to account for risks and accidents. This onsite plan shall be dovetailed with the onsite management plan for the district.
- xiv. Public hearing to be conducted and issues raised and commitments made by the project proponent on the same should be included in EIA/EMP Report in the form of tabular chart with financial budget for complying with the commitments made.
- xv. Any litigation pending against the project and/or any direction/order passed by any Court of Law against the project, if so, details thereof shall also be included.

	Has the unit received any notice under the Section 5 of Environment (Protection) Act, 1986 or relevant Sections of Air and Water Acts? If so, details thereof and compliance/ATR to the notice(s) and present status of the case.
	xvi. A tabular chart with index for point wise compliance of above TORs.
	It was recommended that 'TOR' along with Public Hearing prescribed by the Expert Appraisal Committee (Infrastructure- 2) should be considered for preparation of EIA / EMP report for the above mentioned project in addition to all the relevant information as per the 'Generic Structure of EIA' given in Appendix III and IIIA in the EIA Notification, 2006. The draft EIA/EMP report shall be submitted to the State Pollution Control Board for public hearing. The issues emerged and response to the issues shall be incorporated in the EIA report.
13.2.4.	Setting up of Municipal Solid Waste Management Facility at Plot No. 110/1636 of Khata No. 208, Village Raidandia, Tehsil Udala, District Mayurbhanj, Odisha by M/s. Udala NAC - TOR - [IA/OR/MIS/61362/2016] [F.No.10-91/2016-IA-III]
	The project authorities gave a detailed presentation on the salient features of the project and proposed environmental protection measures to be undertaken along with the draft Term of References for the preparation of EIA-EMP report. All the projects related to common municipal solid waste management facility are listed at 7(i) of schedule of EIA Notification, 2006 covered under category 'B' and appraised at state level. However, applicability of general condition i.e. location of project at a distance of 5 Km from ESZ of Kuldiah Wildlife Sanctuary, proposal is treated as category 'A' project.
	M/s. Udala NAC has proposed for setting up of Municipal Solid Waste Management Facility at Plot No. 110/1636 of Khata No. 208, Village Raidandia, Tehsil Udala, District Mayurbhanj, Odisha. PP informed that one alterntive site was examined in Village Holdia. But this site was rejected as it is a forest land. The total area of the site would be 6 Acres and the capacity of processing plant facility will be 2.25 TPD in 2022, 2.74 in 2032, 3.26 in 2042. The site is being used for dumping of waste and no scientific disposal method is being followed. Land belongs to the UdalaNAC.Tehsildar of Udala has given the permissive possession vide letter No.436 dated 8 th February, 2010 to the Udala NAC.
	It is reported that protect areas namely, Phulajhari RF-5.00 km, North-West Arabandh RF-9.5 km, South-East Udala RF-1.5 km,North-West Khunta RF-14.3 km,North-East Nahara RF-13.5 km,North-East Tinsukia RF-13.4 km,South-East Nachhipur RF-12.6 km,South-West Asanbani RF-12.4 km,South-West Similipal National Park and Tiger Reserve-12.5 km, West Kuldiah Wildlife Sanctuary - 9.16 km, South ESZ of Kuldiah Wildlife Sanctuary - Within 5 km radius of Project site are located within 15 km distance. Water bodies namely Sunai Nadi-1.65 km, South Tangana Nadi-8 km, North-East Deo Nadi-3.5 Km are located within 15 km distance. Total cost of the project is Rs. 4.83 Crores.The proposed integrated MSW management project will include following components :
	a) Waste collection & transportation Facility, Intermediate Waste Storage Facility, Preprocessing facility, processing facility (Composting).b) Inert waste will be disposal at Baripada Landfill site.
	The water requirement during construction phase, 20 KLD of water will be required that will be met through water tanker. During the operational phase, 8 KLD of water will be required that will be abstracted through bore wells. Power consumption during the operational phase will be 60 KW and will be supplied by Central Electricity Supply Utility of Orissa (CESU). Area earmarked for greenbelt is 4,822 sqm
	After detailed deliberations on the proposal, the Committee recommended for grant of

	Station Township) At Munnar, Idduki District, Kerala by M/s Valley World Entertainments Private Ltd - TOR - [IA/KL/MIS/61394/2016] [F.No.10-92/2016-IA- III]
13.2.5.	Proposed Ropeway with Building Constructions (Amusement Park With Mini Hill
	It was recommended that 'TOR' along with Public Hearing prescribed by the Expert Appraisal Committee (Infrastructure- 2) should be considered for preparation of EIA / EMP report for the above mentioned project in addition to all the relevant information as per the 'Generic Structure of EIA' given in Appendix III and IIIA in the EIA Notification, 2006. The draft EIA/EMP report shall be submitted to the State Pollution Control Board for public hearing. The issues emerged and response to the issues shall be incorporated in the EIA report.
	 xiv. Action plan for measures to be taken for excessive leachate generation during monsoon period. xv. Detailed Environmental Monitoring Plan. xvi. Report on health and hygiene to be maintained by the sanitation worker at the work place. xvii. Public hearing to be conducted and issues raised and commitments made by the project proponent on the same should be included in EIA/EMP Report in the form of tabular chart with financial budget for complying with the commitments made. xviii. Any litigation pending against the project and/or any direction/order passed by any Court of Law against the project, if so, details thereof shall also be included. Has the unit received any notice under the Section 5 of Environment (Protection) Act, 1986 or relevant Sections of Air and Water Acts? If so, details thereof and compliance/ATR to the notice(s) and present status of the case. xix. A tabular chart with index for point wise compliance of above TORs.
	 i. Importance and benefits of the project. ii. A sensitivity analysis of the site shall be carried out as per the MoEF criteria and form part of the EIA report. iii. Details of various waste management units with capacities for the proposed project. Details of various waste management units with capacities for the proposed project. Details of various waste management units with capacities for the proposed project. Details of various waste management units with capacities for the proposed project. Details of various waste management units with capacities for the proposed project. Details of various should consult the Municipal solid waste Management manual of the Ministry of Urban Development, Government of India and draw up project plans accordingly. vi. Methodology for remediating the project site, which is presently being used for open dumping of garbage. vii. Layout maps of proposed solid waste management facilities indicating storage area, plant area, greenbelt area, utilities etc. viii. Details of air emission, effluents generation, solid waste generation and their management. ix. Requirement of water, power, with source of supply, status of approval, water balance diagram, man-power requirement (regular and contract) x. Process description along with major equipments and machineries, process flow sheet (quantative) from waste material to disposal to be provided xi. Hazard identification and details of proposed safety systems. xii. Details of Drainage of the project upto 5km radius of study area. If the site is within 1 km radius of any major river, peak and lean season river discharge as well as flood occurrence frequency based on peak rainfall data of the past 30 years. Details of Flood Level of the project site and maximum Flood Level of the river shall also be provided. xiii. Details of effluent treatment and recycling process. xiv. Action plan for measures to be taken for excessive leachate gene
	Terms of Reference as specified by the Ministry as Standard ToR in April, 2015 for the said project/activity and the following TOR in addition to Standard ToR for preparation of EIA-EMP report:

During the meeting, the project proponent made a presentation and provided the following information to the Committee:-

- (i) The project involves ropeway with building constructions (Amusement Park with Mini Hill Station Township) at Munnar, Idduki District, Kerala promoted by M/s Valley World Entertainments Private Ltd.
- (ii) For proposed ropeway, the elevation of LTP is 874.33 m & UTP is 920.15 m above MSL and the project lies in Konnathadi village which falls in Eco-sensitive area of the Western Ghats thus it is Category A project. The Built-up area of the project will be 149600.00 sqm. Details of the Terminals are as follows:

Station	Latitude	Longitude	
Terminal T1 (LTP)	77° 4'3.47"E	9°54'45.08"N	
Terminal T2 (UTP)	77° 2'56.99"E	9°56'27.08"N	

(iii) Land use of the site is as under:-

Particulars	Area in Sqm	Percentage
Ground Coverage	37424	10.97
Green Area	153972	45.12
Amusement park & Water		
show, Giant Wheel, Ropeway	95860	28.09
Surface Parking Area	18000	5.27
Internal Roads	36000	10.55
Total	341256	100.00

Area required (for Ropeway)	Total Area (In Sq. m.)	
Lower Terminal Station-A	1000 sqm	
Upper Terminal Station -B	600 sqm	
Ropeway Length-C	3602 mtrs	
Right of Way-D	10 m	
Corridor of the alignment - E	36020 sqm	
Total (A+B+E)	37620 sqm	

- (iv) The area required for the construction of the proposed Ropeway with Building Constructions (amusement park with mini hill station township) would be about 341256 sqm, out of which 37620 sqm shall be utilized for construction of Ropeway terminals and corridor. For proposed ropeway, the elevation of LTP is 874.33 m & UTP is 920.15 m above MSL.
- (v) Justification for selection of the site: The project is to set up a world class Tourism infrastructure at Munnar, Kerala, India. The project proponent will develop Ropeway with Building Constructions (amusement park with mini hill station township). Visitors can also enjoy a panoramic view of Kerala from the observation deck "The Skywalk", standing at about 3000 ft above sea level. From here, visitors can breathe in the cool fresh air enjoy the magnificent view. The project comprises of retractable roof at the lower station and elevated walkway. With a view to provide a sky-diving area for the tourists, this will be achieved by preserving the ecosystem, the natural surroundings, and the flora and fauna.With a view to provide a skydiving area for the tourist & residents that will visit the township and amusement park, the M/s Valley World Entertainments Private Ltd. has identified sites & thus required the ropeway facility for reaching at skydiving area. Three alternative routes were assessed. Out of the three

	alternative routes the Alternative-II was found appropriate. The three-alternative alignment has been discussed below:
	 Alignment 1: There will be cutting of trees at UTP area & along the corridor also. No parking space will be available
	 Alignment 2 (Selected Alignment): This alignment starts with its LTP near township area. The corridor traverses over a thin vegetation with very few trees upon land. The alignment finally ends its Upper Terminal Point at skydiving area. The alignment is clear of any urban habitat in its corridor Parking of township will carter the visitors of the ropeway, no extra parking land is required. Accessibility from township to lower LTP is good.
	 Alignment 3: Accessibility from township area is poor. Enough parking space is not available at LTP area. There will be major cutting of trees at UTP area
(v	i) The Built-up area of the project will be 149600.00 sqm. The project is to set up a world class Tourism infrastructure at Munnar, Kerala, India. The project proponent will develop Ropeway with Building Constructions (amusement park with mini hill station township). Visitors can also enjoy a panoramic view of Kerala from the observation deck "The Skywalk", standing at about 3000 ft above sea level. From here, visitors can breathe in the cool fresh air enjoy the magnificent view. The project comprises of retractable roof at the lower station and elevated walkway. With a view to provide a sky-diving area for the tourists, this will be achieved by preserving the ecosystem, the natural surroundings, and the flora and fauna.With a view to provide a skydiving area for the tourist that will visit the township and amusement park, the M/s Valley World Entertainments Private Ltd. has identified sites & thus required the ropeway facility for reaching at skydiving area.
(v	ii) For proposed ropeway, the elevation of LTP is 874.33 m & UTP is 920.15 m above MSL. The alignment will be 3602 metres in length with an elevation difference of 45.82 metres, covering an area of 37620 sq m (including Terminal Stations & ropeway corridor).
(v	iii) The proposed project will consist of three parts namely mini hill station Township area, Ropeway and Sky-Diving area. The ropeway will be built with its Upper Terminal Point at skydiving area and the Lower Terminal Point at mini hill station township. With a view to provide a sky-diving area for the tourists and the residents of Township, the ropeway facility will be provided for reaching at skydiving area. Thus, the ropeway facility shall inter-connect the mini hill station Township area and Sky-Diving area.
(i)	Activities in the proposed Township will be Amusement park & Water show, Giant Wheel, Residential Apartment, Studio Apt, Five Star Hotel, Villas, Convention Centre, Commercial Building, Clinic, Office and Restaurant. Area land use is as under:
(x) Investment/Cost: Estimated Cost of the project will be approximately Rs. 615 crores.
(x	i) Whether the project is in Critically Polluted Area: The project does not fall under Critically Polluted Area.
(x	•
(x	iii) Eco Sensitive Area : The project lies in Konnathadi village which falls in Eco-sensitive

	 area of the Western Ghats thus it is Category A project. Idukki Wildlife Sanctuary is located at distance of 12.65 km SW. (xiv) The project will have its own STP of 830 KLD for treatment of approx. 687 KLD wastewater. (xv) Used Oil of approx. 84 L/month from DG sets & machinery will be given to authorized hazardous waste vendor. Details of wastes is as under: 					
	Type of Waste	Colour of Bin	Category	Disposal Method	Total Waste (kg/day)	
	Organic Waste	Green	Bio- degradable	The waste will be treated in Organic Waste Convertor and converted into compost	2530	
	Recyclable Was	te Blue	Recyclable	Collected and given to approved recycler	1084	
	Total Waste				3614 kg/ day	
13.2.6.	 (xviii) Benefits of the project: It will increase Infrastructure of the area & will be a planned managed development in the area. It will set a precedent for others to develop planned Ropeway with Building Constructions project which will cumulatively help the area to b much more managed in future. It will provide a planned housing society with convenier shopping, Convention Centre, amusement park to fulfil basic needs of the residents a well as the people of nearby areas, community facility and club for the residents of th colony. Visitors can also enjoy a panoramic view of Kerala from the observation dec "The Skywalk", standing at about 3000 ft above sea level. With a view to provide skydiving area for the tourist & residents that will visit the township and amusemer park, the ropeway facility will be provided for reaching at skydiving area. Aeria Ropeway is fast emerging technology of providing not only tourist experience but a urban transportation means especially for hilly and tough terrains. It is totall environment friendly with least generation of any type of pollutants. The Committee noted that the project site is located in Konnathady Village which is i the list of ESA villages at S.N 1770 as notified by MoEF dated 17.04.2013, whic prohibits certain activities to carry out. In view of the above, it was decided to obtain the comments of ESZ Division of the Ministry before finalizing the TOR for the proposed project. 				anned to be enient nts as of the deck vide a ement Aerial but an totally h is in which	
13.2.0.	Proposed construction of Himani Chamunda Passenger Ropeway at Himani Chamunda Devi Temple, District Kangra, Himachal Pradesh by M/s Usha Breco Chamunda Devi Ropeway Private Limited- TOR - [IA/HP/MIS/61402/2016] [F.No.10-93/2016-IA-III]					
	The project authorities gave a detailed presentation on the salient features of the project and proposed environmental protection measures to be undertaken along with the draft Term of References for the preparation of EIA-EMP report. All the projects related to Aerial Ropeway Elevation greater than 1000 m) are listed at 7(g) of schedule of EIA Notification, 2006 covered			erm of way (

under category 'A' and appraised at central level.

M/s Usha BrecoChamunda Devi Ropeway Private Limited has proposed forconstruction of HimaniChamunda Passenger Ropeway at HimaniChamunda Devi Temple, District Kangra, Himachal Pradesh.The HimaniChamunda Temple is at an elevation of 2778 m above MSL.The proposed system to be installed at Chamunda Devi temple will be Continuous Detachable Monocable Gondola System. The Project is a 5520-m long ropeway, covering an area of 107768 sqm (including three Terminal Stations & ropeway corridor). Cost of the project will be approximately Rs.289 crores. The proposed ropeway shall be developed in two Sections., Section-I consist of LTP - T1 to MTP-T-2 & Section-II consist of MTP - T-2 to UTP (T-3). There will be a continuous ropeway line from T1 to T3.

Station	Latitude	Longitude
Terminal T1	76°25'5.77"E	32° 8'55.79"N
Terminal T2	76°26'32.46"E	32°10'51.82"N
Terminal T3	76°26'59.24"E	32°11'27.47"N

The alignment falls within a Forest land for development of terminal stations & line towers. About 85849 sq. m (8.5849 ha) of area of forest land will be diverted. This activity will be carried out as per the guidelines of the Forest (Conservation) Act, 1980. One of the many religious places of worship in Kangra, AadiHimaniChamunda temple in the lower reaches of the Dhauladhar ranges stands around 2920 m tall and is a heavenly place to visit. Presently, HimaniChamunda temple is accessible via two trek routes. The more frequented trek route connects Chamunda temple with HimaniChamunda via Jia village which is a few km from the Chamunda Devi Temple

The proposed ropeway shall be developed in two Sections. Section-I consist of LTP - T1 (Chamunda Devi Temple, 1057 m above MSL) to MTP-T-2 (Mid Station, 2127 m above MSL) & Section-II consist of MTP - T-2 (Mid Station, 2181 m above MSL) – UTP (HimaniChamunda Temple, 2771 m above MSL) (T-3).

The total water requirement for emergency & other misc. purpose has been estimated as 6 KLD and the source will be Gram Panchayat. Water shall be used mainly for flushing & hand washing, drinking, Gardening & misc. purposes. The generation of total waste water will be 2 KLD, which will be disposed off in bio toilets and after that treated water shall be discharged to septic tank followed by soak pit. The location for the water storage tank will be Terminal T-1, T-2 & T-3. For drinking water, water cooler/water Dispenser shall be provided at Terminal T-1, T-2, and T-3.

1090 Kg/day of waste will be generated of which 763 kg/day of biodegradable waste will be treated in OWCs proposed at Terminal-1 & Terminal-3 and converted into compost and 327 kg/day of recyclable waste will be segregated and given to approved recycler. Used oil will be given to authorized hazardous waste recycler. Total power load of the project is 2000 kVA. DG sets of 1 x 250 KVA at T1, 1 x 1010 KVA and 1 x 500 KVA at T2& 1x 80 KVA at T3 will be provided at terminals respectively.

After detailed deliberations on the proposal, the Committee *recommended* for grant of *Terms of Reference as specified by the Ministry as Standard ToR in April, 2015 for the said project/activity* and the following TOR in addition to *Standard ToR* for preparation of EIA-EMP report:

i. Importance and benefits of the project.

ii. A toposheet of the study area of radius of 10km and site location on

		1:50,000/1:25,000 scale on an A3/A2 sheet. (including all eco-sensitive areas and environmentally sensitive places)
	iii.	Stage – I forest clearance to be submitted.
	iv.	Route map of proposed ropeway project.
	v.	Layout maps of proposed project indicating location of upper station and lower station, building, food court, parking, greenbelt area, utilities etc.
	vi.	Numbers of persons/projections of tourist.
	vii.	Cost of project and time of completion.
	viii.	A note on appropriate process and materials to be used to encourage reduction in carbon foot print. Optimize use of energy systems in buildings that should maintain a specified indoor environment conducive to the functional requirements of the building by following mandatory compliance measures (for all applicable buildings) as recommended in the Energy conservation building code (ECBC) 2007 of the Bureau of Energy Efficiency, Government of India. The energy system include air conditioning systems, indoor lighting systems, water heaters, air heaters and air circulation devices.
	ix.	Details of air emission, effluents, solid waste and hazardous waste generation and their management.
	х.	Requirement of water, power, with source of supply, status of approval, water balance diagram, man-power requirement (regular and contract)
	xi.	The E.I.A. should specifically address to vehicular traffic management.
	xii.	An onsite disaster management plan shall be drawn up to account for risks and accidents. This onsite plan shall be dovetailed with the onsite management plan for the district.
	xiii.	Public hearing to be conducted and issues raised and commitments made by the project proponent on the same should be included in EIA/EMP Report in the form of tabular chart with financial budget for complying with the commitments made.
	xiv.	Any litigation pending against the project and/or any direction/order passed by any Court of Law against the project, if so, details thereof shall also be included. Has the unit received any notice under the Section 5 of Environment (Protection) Act, 1986 or relevant Sections of Air and Water Acts? If so, details thereof and compliance/ATR to the notice(s) and present status of the case.
	XV.	A tabular chart with index for point wise compliance of above TORs.
	Appraisal Co report for the 'Generic Stru EIA/EMP repo	nmended that ' TOR' along with Public Hearing prescribed by the Expert mmittee (Infrastructure- 2) should be considered for preparation of EIA / EMP e above mentioned project in addition to all the relevant information as per the cture of EIA' given in Appendix III and IIIA in the EIA Notification, 2006. The draft ort shall be submitted to the State Pollution Control Board for public hearing. The ed and response to the issues shall be incorporated in the EIA report.
13.2.7.		on of New Domestic Terminal Building at Patna Airport, Patna, Bihar ort Authority of India - TOR - [IA/BR/MIS/61409/2016][F.No.10-94/2016-
	proposed env	uthorities gave a detailed presentation on the salient features of the project and vironmental protection measures to be undertaken along with the draft Term of or the preparation of EIA-EMP report. All the projects related to Airports are listed

at 7(a) of schedule of EIA Notification, 2006 covered under category 'A' and appraised at central level.

M/s Airport Authority of India has proposed for construction of New Domestic Terminal Building at Patna Airport, Patna, Bihar. The increased passenger load due to increase in no. of flights has posed a congestion in the old terminal building leading to necessity for a new higher capacity Terminal building. The airport is spread over an area of 247.16 acres. Cost of project is Rs. 722.05 Crore. Following facilities will be developed:

a) Construction of centrally new domestic terminal building with all modern facilities and amenities conforming to GRIHA 4 Star Rating

- b) Construction of ATC Tower-cum-Technical Block, Administrative Block
- c) Construction of Multi Level Car Park
- d) Construction of fire station, cargo terminal, MT Pool
- e) Residential colony for about 120 nos. of AAI staff.

After detailed deliberations on the proposal, the Committee *recommended for grant of Terms of Reference as specified by the Ministry as Standard ToR in April, 2015 for the said project/activity* and the following TOR in addition to *Standard ToR* for preparation of EIA-EMP report:

- i. Importance and benefits of the project.
- ii. Copy of consent to establish and consent to operate for the existing airport facilities.
- iii. A toposheet of the study area of radius of 10km and site location on 1:50,000/1:25,000 scale on an A3/A2 sheet. (including all eco-sensitive areas and environmentally sensitive places).
- iv. Layout maps of proposed project indicating runway, airport building, parking, greenbelt area, utilities etc.
- v. Cost of project and time of completion.
- vi. A note on appropriate process and materials to be used to encourage reduction in carbon foot print. Optimize use of energy systems in buildings that should maintain a specified indoor environment conducive to the functional requirements of the building by following mandatory compliance measures (for all applicable buildings) as recommended in the Energy conservation building code (ECBC) 2007 of the Bureau of Energy Efficiency, Government of India. The energy system include air conditioning systems, indoor lighting systems, water heaters, air heaters and air circulation devices. Use
- vii. Details of emission, effluents, solid waste and hazardous waste generation and their management. Air quality modelling and noise modelling shall be carried out for the emissions from various types of aircraft.
- viii. Classify all Cargo handled as perishable, explosive, solid, petroleum products, Hazardous Waste, Hazardous Chemical, Potential Air Pollutant, Potential Water Pollutant etc. and put up a handling and disposal management plan.
- ix. Noise monitoring shall be carried out in the funnel area of flight path.
- x. Requirement of water, power, with source of supply, status of approval, water balance diagram, man-power requirement (regular and contract)
- xi. The E.I.A. should specifically address to vehicular traffic management as well as estimation of vehicular parking area.

	 xii. Details of fuel tank farm and its risk assessment. xiii. Public hearing to be conducted and issues raised and commitments made by the project proponent on the same should be included in EIA/EMP Report in the form of tabular chart with financial budget for complying with the commitments made. xiv. Any litigation pending against the project and/or any direction/order passed by any Court of Law against the project, if so, details thereof shall also be included. Has the unit received any notice under the Section 5 of Environment (Protection) Act, 1986 or relevant Sections of Air and Water Acts? If so, details thereof and compliance/ATR to the notice(s) and present status of the case. xv. A tabular chart with index for point wise compliance of above TORs.
	It was recommended that 'TOR' along with Public Hearing prescribed by the Expert Appraisal Committee (Infrastructure- 2) should be considered for preparation of EIA / EMP report for the above mentioned project in addition to all the relevant information as per the 'Generic Structure of EIA' given in Appendix III and IIIA in the EIA Notification, 2006. The draft EIA/EMP report shall be submitted to the State Pollution Control Board for public hearing. The issues emerged and response to the issues shall be incorporated in the EIA report.
13.2.8.	Setting up of Mini Bulk Carriers Handling Facility in the Upstream of 3 rd Oil Jetty with the Help of Floating Crane/ Pontoon Fitted Crane at HDC, Kolkata Port Trust by M/s Kolkata Port Trust – Environmental Clearance [IA/WB/MIS/30603/2015][F.No.10-26/2015-IA-III]
	The project authorities and their consultant (M/s Wapcos Limited) gave a detailed presentation on the salient features of the project and proposed environmental protection measures to be undertaken as per Draft Terms of References (TORs) awarded during the 153 rd Meeting of the Expert Appraisal Committee (Infrastructure) held during 18 th - 20 th November, 2015 for preparation of EIA-EMP report. The ToR was granted to the project vide letter No. 10-26/2015-IA-III dated 8 th January, 2016. All the projects related to Ports, Harbour and dredging are listed at 7 (e) of schedule of EIA Notification, 2006 covered under category 'A' and appraised at central level.
	M/s Kolkata Port Trust has proposed for setting up of Mini Bulk Carriers Handling Facility in the Upstream of 3 rd Oil Jetty with the Help of Floating Crane/ Pontoon Fitted Crane at HDC, Kolkata Port Trust.
	The scheme further envisages construction of hardstand and road from the shore up totransit storage area of cargo at the extended area of G.C. Berth along with design, construction and setting up of the floating jetty facility with all ancillary cargo handling equipment in the upstream of 3rd oil jetty. The project envisages creation of a new cargo handling facility at HDC, KoPT. The total area envisaged to be utilized on the shore is 18000 m ² . Total area envisaged to be utilized in river is 2000 m ² . Haldia Dock Complex of Kolkata Port Trust proposes to construct a floating barge jetty with Crane facility at the upstream of 3 rd oil jetty at latitude 22 ° 01' 12.4" N and Longitude 88° 04'39.1" to handle Mini Bulk Carriers (MBC) of about 10,000-12,000 DWT carrying cargo like Coal etc. Cargo handling capacity will be 2.55 MMTPA. The total cost of the project is Rs. 73.70 cores. The project envisages unloading of cargo from MBC by means of a crane to be fitted over a floating pontoon and RCC Walkway platform to be transferred by means of Conveyor to shore hardstand. The cargo will be evacuated by 25 numbers of 10 wheeler dumper, 9 numbers of Pay loader, 2 numbers Excavators and one number of bull Dozers and storing the same at the L plots of G.C. Berths. The pontoon size is 70m x 25m with 3 m depth with draught of 1.8 m.The components of the project are as under:

 Commissioning of afloating Crane/Pontoon (70m x 25m X 3 m) fitted with Crane Payloader and Mooring Boat pontoon. Commissioning of Conveyorbelt & hopper; Pile support & deadman & bollards Width of conveyor belt with a width of 1.5 m and capacity to carry 540 m³ per hour a a belt speed of 2 m/sec. 7 m wide Approach Trestle having 1.5 m walk way on each side 2 nos of Berthing dolphins (of size 6mx6m, each deck comprising of 4 nos of 1300 mm dia piles)
 4 nos of 600 mm dia pile for installing 50 MT bollards Paver topped Hardstand : 100m x 40 m

It is reported that no eco-sensitive area is located within 10 km distance. PP confirmed that no dredging will be carried out. It is reported that during project operation phase, a large portion of cargo would be handled through road. The Committee insisted them to implement rapid rail loading for cargo evacuation. A total water requirement during operation phase has been estimated as 153.5 m3/day. Quantity of sewage likely to be generated during operation phase would be of the order of 2.8 m^3 /day. Hence it is proposed that the sewage generated form the jetty during operation phase shall be treated in the existing STP of Haldia Dock Complex comprising of waste stabilization pond. The measures will be taken for prevention and control of water pollution are i) Slope of the bulk cargo storage facility will be towards landward side to avoid storm water draining into the river; (ii)Runoff will be collected in a sump and allowed to settle. An oil separator will be installed prior to the sump to arrest oil and grease from entering into the sump. Clear water from the sump will be allowed to overflow to the existing storm water drain of HDC for ultimate disposal. In addition, to prevent or minimize storm water pollution appropriate storm water pollution prevention plan (SWPPP) will be developed. SWPPP will be specific, because every unit is unique with source, type and volume of contaminated storm water discharge; (iii) Bulk cargo area will be paved and made impermeable for any leachate to percolate to the subsurface water table; (iv) Ballast and bilge water will be, handed over to registered re-refiners or treated at ballast water treatment plant available in Haldia Dock Complex. (v) While pumping out bilge and ballast water from ship to shore, care will be taken to avoid spillage. PP informed that greenbelt will be developed in 9500 m². Out of which 8100 m2 area is earmarked along 1.35 km long road from temporary stack yard to common stack yard. 1400 m² is earmarked along the periphery of temporary stack yard.

Public hearing was conducted by WBSPCB on 21st September, 2016. Issues raised during public hearing were regarding greenbelt development in township, river bank and other areas of port; etc. The Committee noted that issues have satisfactorily been responded by the project proponent and incorporated in the final EIA-EMP report.

SCZMA Recommendations: The West Bengal Coastal Zone Management Authority (WBCZMA) has recommended the project vide their letter No.285/EN/T-II-4/011/2016 dated 26th December, 2016. The HTL/LTL demarcation for the project site was conducted by Institute of Environmental Studies and Wetland Management, Kolkata. The Project area falls in the Zone-I,II& IVB As per CRZ notification, 2011.

After detailed deliberations, the Committee recommended the project for environmental and CRZ clearance and stipulated the following specific conditions along with other environmental conditions while considering for accord of environmental clearance:

 Construction activity shall be carried out strictly according to the provisions of CRZ Notification, 2011. No construction work other than those permitted in Coastal Regulation Zone Notification shall be carried out in Coastal Regulation Zone area.

(ii)	All the recommendations and conditions specified West Bengal Coastal Zone Management Authority (WBCZMA) vide letter No.285/EN/T-II-4/011/2016 dated 26 th December, 2016 <i>shall be complied with.</i>
(iii)	The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained.
(iv)	Shoreline should not be disturbed due to dumping. Periodical study on shore line changes shall be conducted and mitigation carried out, if necessary. The details shall be submitted along with the six monthly monitoring report.
(v)	The ground water shall not be tapped within the CRZ areas by the PP to meet with the water requirement in any case.
(vi)	The commitments made during the Public Hearing and recorded in the Minutes shall be complied with letter and spirit. A hard copy of the action taken shall be submitted to the Ministry.
(i)	All the conditions stipulated in the earlier Clearance including the recommendations of Environment Management Plan, Disaster management Plan shall be strictly complied with.
(ii)	The coal shall be stored only in designated stock yard with dust control measures viz. wind screen of height at least 2 m above the coal stock, made of fabric/HDPE, water sprinkler arrangement, green belt of at least three layers of suitable trees and scrubs.
(iii)	The coal from the ships shall be conveyed through closed conveyor to the coal stock yard. The conveyor shall be seamless without joints/transfer points.
(iv)	The dust from the roads shall be periodically cleaned and dust suppression by water spray be carried out.
(v)	Cargo shall be unloaded directly into hopper from the ship and transported to the stack yards through closed conveyor system only. Inbuilt dust suppression systems shall be provided at hoppers and all the transfer points / storage yards. Cargo shall not be unloaded directly onto the berth. Water meters shall be provided at different locations to record the consumption of water used for dust suppression and daily log shall be maintained.
(vi)	The ground water shall not be tapped within the CRZ areas by the PP to meet with the water requirement in any case.
(vii)	Necessary arrangements for the treatment of the effluents and solid wastes must be made and it must be ensured that they conform to the standards laid down by the competent authorities including the Central or State Pollution Control Board and under the Environment (Protection) Act, 1986.
(viii)	Runoff from project site shall be passed through an oil separator followed by setting tank. Treated water from the sump shall be allowed to overflow to the existing storm water drain of HDC for ultimate disposal. All the operational areas shall be connected with the network of liquid waste collection corridor comprising of storm water, oily waste and sewage collection pipelines.
(ix)	Marine ecology shall be monitored regularly also in terms of sea weeds, sea grasses, mudflats, sand dunes, fisheries, echinoderms, shrimps, turtles, corals, coastal vegetation, mangroves and other marine biodiversity components as

		part of the management plan.
	(x)	Measures should be taken to contain, control and recover the accidental spills of fuel and cargo handle.
	(xi)	All the mitigation measures submitted in the EIA report shall be prepared in a matrix format and the compliance for each mitigation plan shall be submitted to the RO, MoEF&CC along with half yearly compliance report.
	(xii)	Ships/barges/vessels shall not be allowed to release any oily bilge waste or ballast water in the sea. Any effluents from the Jetty which have leachable characteristics shall be segregated and recycled/disposed as per SPCB guidelines. Ships/vessels calling at the jetty shall not dump waste/bilge water during the berthing period.
	(xiii)	Location of DG sets and other emission generating equipment shall be decided keeping in view the predominant wind direction so that emissions do not effect nearby residential areas. Installation and operation of DG sets shall comply with the guidelines of CPCB.
	(xiv)	The quality of treated effluents, solid wastes, emissions and noise levels and the like, from the project area must conform to the standards laid down by the competent authorities including the Central or State Pollution Control Board and under the Environment (Protection) Act, 1986.
13.2.9.	of Aircraft (Chhattisg	o of Runway at 24 Beginning, Expansion of Apron Suitable for C Type t and other associated works at Swami Vivekananda Airport at Raipur garh) by Airport Authority of India–Environmental Clearance – S/61599/2015][F.No.10-6/2015-IA.III]
	presentation measures t 148 th Meeti 2015 for pro No. 10-06/2 2016. All th	tt authorities and their consultant (M/s ABC Techno Labs) gave a detailed n on the salient features of the project and proposed environmental protection to be undertaken as per Draft Terms of References (TORs) awarded during the ng of the Expert Appraisal Committee (Infrastructure) held during 19 th - 21 st May, eparation of EIA-EMP report. Terms of Reference issued by MOEF&CC vide letter 2015-IA-III dated 18 th June, 2015 and TOR was amended vide letter dated 14 th July e projects related to Airports are listed at 7(a) of schedule of EIA Notification, 2006 der category 'A' and appraised at central level.
	Apron Suita Airport at F 49.15" Nort additional la Authority) a	hority of India has proposed for extension of Runway at 24 Beginning, expansion of able for C Type of Aircraft and other associated works at Swami Vivekananda Raipur, Chhattisgarh.The geographical coordinates of existing airport are 21° 10' h and 81° 44' 24.99" East. The total area of the existing airport is 287.648 ha and and is 128.662 ha which has been acquired by NRDA (Naya Raipur Development and handed over to AAI (Airport Authority of India) for proposed extension. Total ect is Rs 103.5 Crores.
	make the o	ovision of extension of runway by 965 m x 45 m towards runway 24 beginning to perational runway. Dimensions of runway after extension will be 3251m x 45 m with shoulders on either side of extended runway. Following activities will be carried out

:
 a). Removal of obstructions and structures in the area of extension of Runway, basic stripand approach funnel.
 b). Provision of runway shoulders 7.5m wide on either side of extended runway. c). Provision of turn pad foe Code letter 'Cat-4C' type of aircraft as per annex-14 and
DGCA CAR. d). Appropriate slope of runway, apron, RESA and levelling, grading, development of
runway strip shall be given and DGCA CAR to facilitate draining of rain water into drainage system.
e). Provision of RESA of 240 m × 90 m dimension at both the ends of runway as perplanning of rain water into drainage system.
 f). Declaration of PCN values of the runway and standard runway markings. g). Provision and extension of boundary wall to ensure that both new and old boundary walls constructions are commensurate with BCAS norms. Provision of perimeter road, along with lighting and CISF watch tower, inside the boundary as per the current norms.
 h). Construction of box culverts of strength to withstand Code-4C type of aircraftoperations in case such culverts are needed as per site requirement for drainagepurpose of cable
 crossing. i). Provision of cable crossing with RCC hume pipes of required size and class at suitable location at proposed extension of runway.
j). Expansion of apron.
Small drain is passing in alignment of proposed extension of runway, which remains dry. Culvert is proposed over this drain to maintain natural drainage. Local road passing through proposed alignment of extension of Runway will be diverted to maintain access for road users. The extension airport will require approx 7 Lakhs cum earth filling, which will be obtained approved borrow areas. No trees will need to be felled for proposed extension of runway and associated works. It is reported that there is no eco-sensitive area within 10 Km radius area from the Raipur airport. There is no forest land diversion involved in the project.
Total water requirement for the Swami Vivekananda Airport will be 430 m ³ /day, which includes 100 m ³ /day water for HVAC, 50 m ³ /day for CFT and 280 m ³ /day for domestic purposes. Water requirement is met through tube wells already available at the Swami Vivekananda Airport. Total estimated wastewater generation during the operation phase is 180 KLD (maximum), which is treated in Sewage Treatment Plant (STP) of 200 KLDcapacity. After treatment, treated wastewater is reused for landscaping and green belt purpose. No wastewater is discharged outside the airport premises. Aftertreatment, treated wastewater is reused for landscaping and green belt purpose. No wastewater is discharged outside the airport premises. Aftertreatment, treated outside the airport premises. Newastewater is discharged outside the airport premises. No wastewater is discharged outside the airport premises. No wastewater is discharged outside the airport premises. No wastewater is discharged outside the airport premises. Approx 150 kg per day solid waste is generated during operation at existing airport, which in collected, segregated and managed by external agency for disposal. Hence, the impact on the soil is insignificant as an organized solid waste collection and disposal practices exist at the Raipur airport. Used lubricating waste oil from maintenance of DG sets and batteries, electronic wastes are collected separately and are sold to authorized recyclers as per CPCB/ CECB guidelines. The existing airport has power requirement 1500 kVA, which is meeting through power Grid Power Supply. Forpower back up 4 DG sets of 750 kVA capacities each and 2 DG sets of 320 kVA capacity each are available. The passenger capacity of existing terminal building is 500 domestic passengers and 200 international passengers. The parking facilities have been provided for 28 VIP cars, general parking for 350 cars, 150 two wheelers and 10 buses.
Public hearing was conducted by Chhattisgarh Environment Conservation Board on 23.11.2016. Issues raised during public hearing were regarding local employment, labour wages, toilet construction, Air pollution control measures, etc. The Committee noted that issues have satisfactorily been responded by the project proponent and incorporated in the final EIA-EMP report.

	The Committee noted that MoEF&CC has granted environmental clearance to Airports Authority of India on 29 th July, 2008 for expansion of Raipur Airport.
	It was decided that PP should submit the certified compliance report issued by the Region Office, Bhubaneswar on the existing environmental conditions stipulated in the EC.
13.2.10.	Construction of Dedicated Berth and other Infrastructure Facilities for the Administration of the Union Territory of Lakshdweep at Beypore, Calicut, Kerala by M/s CPWD, Calicut Central Circle – Environmental and CRZ Clearance - [IA/KL/MIS/32325/2013] (F.No.10-64/2013-IA.III]
	The project authorities and their consultant (M/s Wapcos Limited) gave a detailed presentation on the salient features of the project and proposed environmental protection measures to be undertaken as per Draft Terms of References (TORs) awarded during the 129 th Meeting of the Expert Appraisal Committee (Infrastructure) held during 26 th - 28 th December, 2013 for preparation of EIA-EMP report. The ToR was granted to the project vide letter No.10-64/2013-IA-III dated 19 th February, 2014. All the projects related to Ports, Harbour and dredging are listed at 7 (e) of schedule of EIA Notification, 2006 covered under category 'A' and appraised at central level.
	M/s CPWD, Calicut Central Circle has proposed for Construction of Dedicated Berth and other Infrastructure Facilities for the Administration of the Union Territory of Lakshdweep at Beypore, Calicut, Keralato handle the passenger and Cargo traffic. To meet essential requirements of the people of these islands, Lakshadweep Administration has been operating ships/vessel between Kochi, Beypore and Mangalore Ports in mainland and islands. All the PDS items, Petroleum products and other items are being transported from Beypore and Mangalore ports to these islands. The Existing Beypore Port is located on the south western coast of India (latitude 11° 10' 0" N & longitude 75° 47' 59" E), which is midway between the two major ports of Cochin and New Mangalore. The coordinates of the proposed dedicated berth for Lakshadweep are 11°9'48.96"N and 75°48'27.74"E. Proposed jetty will be constructed as a northern extension to the existing Port, east of the project isRs.49.23 Crore.
	 The major components proposed as a part of the dedicated berth andassociated facilities for the referred project includes the following: a) Construction of dedicated berth structure of size 200 x 20 m. b) Passenger amenities hall in three storied (G+2) RCC frame structure ofsize 18 x 18 m. c) Two warehouses of size 70m x 20m and 67m x 20m. d) Allied facilities such as land development, retaining structures, approachroad, water and power supply, firefighting arrangements and vehicleparking facilities. e) Land surface area is only 3600 m², out of the total required area of10000 m2. Filling with earth will be required with retaining wall along theperimeter for the construction of structures in the water covered area. f) Dredging in navigation channel and the turning circle. The total dredgingquantity works out to beabout 56744 m³. g) Construction of bulk services and development works. h) Firefighting arrangements
	One terminal building is proposed for passengers to accommodate the passenger traffic flow. The proposed passenger hall will include the waiting halls, security checks, ticket verification counters, medical aid, rest rooms, water and power supply, fire safety equipments, etc. The proposed terminal is a 3 storied framed structure with a total builtup area of 986.15 m ² . The total height of the building is 17.31 m above the deck level (+3 level) with a 4 m floor height on

all three floors. A 2 m wide staircase, a 13 passenger capacity lift and another 10- passenger capacity lift are provided for easy vertical movement of passengers.

Dredging for 200 x 20 Metres in front of the wharf will be carried out. The total quantity of dredged material from capital dredging works out to be approximately $56744m^{3}$. The dredge material will be used in the land filling at low laying area.

It is reported that Kadalundi Bird Sanctuary is situated at an aerial distance of 4.2 km from the proposed project site. During construction phase, stockpiling of excavated material will be kept covered. Excessive soil on paved areas will be sprayed (wet) and/or swept and unpaved areas will be sprayed with water to control fugitive emissions. During operation phase, in order to control fugitive emissions from handling of bulk cargoes, the Committee suggested them that storage area shall be earmarked with covered shed and concrete floor. Efforts will be made to reduce the noise generated by the various construction equipments. Construction activities like dredging, etc will be carried out in the confined manner to reduce the impacts on marine environment. Construction waste including debris shall be disposed safely in the designated areas and in no case shall be disposed in the marine environment. Dredging shall not be undertaken during fish breeding season and other special weather situations.

Fresh water requirement will be 1.25 m³/day. Wastewater generation will be 1 m3/day and treated in STP. STP of 10 KLD is proposed for sewage treatment. The Moving Bed Biological Reactor (MBBR) technology will be used for wastewater treatment and treated water will be used for horticulture.

The project area falling in CRZ – II. The Kerala Coastal Zone Management Authority (KCZMA) has recommended the project vide their letter No. 1198/EC4/2016/SEIAA dated 25th July, 2016.

The Public Hearing was conducted by KSPCB on 26th February, 2015 at Krishnan Memorial Auditorium, Beypore, Calicut.District Collector has certified that public hearing was conducted by Shri Anil Kumar, Election Deputy Collector, and rank of Deputy Collector Election is not less than the rank of Deputy Collector General (ADM). Issues raised during public hearing were regarding land acquisition, location of the project, impact on temple, completion of project etc. The Committee noted that issues have satisfactorily been responded by the project proponent and incorporated in the final EIA-EMP report.

After detailed deliberations, the Committee recommended the project for environmental and CRZ clearance and stipulated the following specific conditions along with other environmental conditions while considering for accord of environmental clearance:

- Construction activity shall be carried out strictly according to the provisions of CRZ Notification, 2011. No construction work other than those permitted in Coastal Regulation Zone Notification shall be carried out in Coastal Regulation Zone area.
- (ii) The environmental clearance is subject to obtaining prior clearance for Wildlife from the Standing Committee of the National Board for Wildlife.
- (iii) All the recommendations and conditions specified Kerala Coastal Zone Management Authority (KCZMA) vide letter 1198/EC4/2016/SEIAA dated 25th July, 2016*shall be complied with.*
- (iv) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained.

(v)

Shoreline should not be disturbed due to dumping. Periodical study on shore line

		changes shall be conducted and mitigation carried out, if necessary. The details shall be submitted along with the six monthly monitoring report.
	(vi)	All the roads in the vicinity of the project site and the roads connecting the quarry sites to the construction site should be paved or black topped to minimize the fugitive emissions.
	(vii)	Construction especially on marine front and dredging shall not be carried out during the fish breeding season.
	(viii)	Spillage of fuel / engine oil and lubricants from the construction site are a source of organic pollution which impacts marine life, particularly benthos. This shall be prevented by suitable precautions and also by providing necessary mechanisms to trap the spillage.
	(ix)	Construction waste including debris shall be disposed safely in the designated areas and in no case shall be disposed in the marine environment.
	(x)	Ships shall be prohibited to discharge oil or oily water such as oily bilge water containing more than 15 ppm of oil.
	(xi)	As proposed, 15 m width of the greenbelt shall be provided around the periphery of the jetty.
13.2.11.	"CAPFIMS" Central Armed Police Forces Institute of Medical Sciences Along with its Referral & Research Hospital & Allied Institutes at MaidanGarhi, New Delhiby Central Armed Police Forces Institute of Medical Sciences – Environmental Clearance -[IA/DL/NCP/24671/2014][F.No.10-26/2014-IA.III]	
	The project authorities and their consultant (M/s Perfect Enviro Solution Pvt. Ltd.) gave a detailed presentation on the salient features of the project and proposed environmental protection measures to be undertaken as per Draft Terms of References (TORs) awarded during the 143 rd Meeting of the Expert Appraisal Committee (Infrastructure) held during 6 th -27 th January, 2015 for preparation of EIA-EMP report. Terms of Reference (ToR) was granted by MoEF&CCvide letter No.10-26/ 2014-IA-III dated 12 th February, 2015.Proposed project falls under item no. 8 (b) i.e. Township and area development projects of the schedule of the EIA Notification, 2006. As per amended notification dated 9.12.2016, covering an built up area more than 3,00,000 m ² , proposal is categorized as Category 'A' and appraised by EAC.	
	"CAPFIMS" & Research vide allotme	ned Police Forces Institute of Medical Sciences has proposed for development of Central Armed Police Forces Institute of Medical Sciences Along with its Referral Hospital & Allied Institutes at MaidanGarhi, New Delhi. The land is allotted by DDA ent letter no. F.22 (3)10/IL/1429 dated 27/7/12 & no. F.22 (3)2010/IL/1581 dated r development of Hospital & Academic zone and Residential zone.
	forces like C	developed with an objective to provide best medical care to troops and families of CRPF, BSF, CISF, ITBP, SSB, NSG and Assam Rifles as well as to Central Police ns which function under the Union Home Ministry.
	plot area is ridge/geo-	et will be located at Latitude 28°28'28.61" N and longitude 77°12'54.83" E. The total s 2,08,009.30sqm. Out of which, 17.75 acres of the project site falls under southern morphological ridge. It is proposed that no construction will be done on 17.75 st of the project is Rs. 1071 Cr. The project will comprise of Super Speciality R & R

Hospital (800 bedded), Academic zone, Residential zone (residential campus + Hostels for doctors, nurses, nursing & paramedical hostel), Auditorium, utility block and religious shrine. FAR area will be 333400 sqm and total construction/ built up area will be 372504.44 sqm. Maximum height of the building will be 51m. Building configuration of the project is as given below:

	• • • • • • • • • • • • • • • • • • • •	
No of stories & Level (Residential Zone)		
Block No.	No of Storey	Maximum Ht. Of Tower
Block-B1	G+14	47.08 Mt.
Block-B2	G+14	47.08 Mt.
Block – B3	G+14	47.08 Mt.
Block – B4	G+14	47.08 Mt.
Block – B5	G/S+14	47.08 Mt.
Block – B6	G/S+13	45.85 Mt.
Block – B7	G/S+14	47.08 Mt.
Block – B8	G+13	45.85 Mt.
Block – B9	G/S+14	51.00 Mt.
Block – B10	G/S+14	51.00 Mt.
Block – B11	G/S+13	47.80 Mt.
No. of Stories & Levels (H	ospital & Academic Zone)	
Block No.	No of Storey	Maximum Ht. Of Tower
Block-B12	G/S+14	51.00 Mt.
Block-B13	G+9	36.40 Mt.
Block –B14	G	20 Mt.
Block – B15	G+7	40.00 Mt.
Block-B16	G+10	50.50 Mt.
Block-B17	G+2	12.00 Mt.
Block-B18	G	9.00 Mt.
Block-B19	G	7.00 Mt.
Block-B20	G	7.00 Mt.
Block-B21	G	7.0 t.

Adequate parking provision shall be provided in the project will be 6684 ECS shall be provided in basement, stilt, surface and Multi-Level Stack Parking.It is reported that Asola Wildlife Sanctuary is at 0.2 km N, E, S (around the project).

During the construction of the proposed project, the services required like water supply and sewage facilities shall be arranged on a temporary basis from STP treated water supplied through authorized tankers and the same will be maintained without any adverse impact on the environment. During the construction phase, soak pits and septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided for labour force.

During operation phase, total water requirement for proposed complex shall be 2199 KLD. Out of which, fresh water requirement from Ground water source will be 1031 m3/day and remaining water requirement (1168 m3/day) will be met from recycled/treated effluent. Water shall be used mainly for domestic, flushing, Gardening, Cooling, Lab & OT, & miscellaneous purposes. Total quantity of wastewater generation shall be 1380 KLD (1236 from domestic uses & 144 KLD from Lab & OT). The 1236 KLD of generated sewage shall be treated in STP of 1800 KLD (2 modules of 900 KLD each) and 144 KLD from Lab & OT shall be treated in ETP of 175 KLD. The treated water generation from STP will be 1211 KLD out of which 1168 KLD shall be reused for flushing, Cooling, gardening and misc. purposes and excess 43 KLD shall be discharged to sewer. The treated water generation from ETP will be 130 KLD which will be discharged to the sewer line.

About 4455 Kg/ day solid waste will be generated in the project. The biodegradable waste (3118 Kg/ day) will be treated in Organic waste convertor and the recyclable waste generated

(1337 Kg/ day) will be handed over to authorized local vendor/recycler. Bio-medical waste 230 kg/day will be generated from the complex.

Power requirement: The total power requirement during construction phase will be met by obtaining temporary connection from BSES and for backup, DG set will be kept of 125 KVA and total power requirement during operation phase will be 14162.3 KW and will be met from BSES. D.G. sets of capacity of 4 x 1010 KVA, 6 x 750 KVA and 2 x 500 KVA for power back up is proposed.

RWH: Rainwater of buildings will be collected in 5 RWH pits of dia. 6.7 m & depth 7.0 m for recharging the ground water.

Energy saving measures will be provided such as insulated walls with cavity, solar PV generation of 1 MW, LED lighting, energy efficient glass and compliance of ECBC norms.

Employment potential:Labourers during construction phase and about 2700 personnel as staff during operation phase.

Benefits of the project: The benefits of the project are:

- This Institute comprising of 800 bedded (500 General Speciality & 300). Super speciality hospital will have State of the Art features and will provide world class health care facilities to Central Armed Police Forces of the nation. It has significant importance as it is the first of its kind to be established for Central Armed Police Forces who urgently need the treatment in case of casualties often happening with forces.
- OPD & emergency will be available for general public also.
- Hospital will cater around 50 lakh Central Armed Police Forces personnel & their families.
- Medical college, Nurses College & School of Paramedics will be for general public also.
- The Hospital will provide employment to labourers during construction phase and employment to personnel working in the hospital during operation phase.
- The Hospital will also enhance the infrastructure of the area.
- The Hospital will have its own modern residential campus & hostel for students, doctors and its health workforce.

After detailed deliberations, the Committee recommended the project for environmental clearance and stipulated the following specific conditions along with other environmental conditions while considering for accord of environmental clearance:

I. Construction Phase

- (i) The Projects Proponents shall obtain all necessary clearance / permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.
- (ii) As proposed, no construction shall be done on 17.75 acres land of southern ridge/geo- morphological ridge.
- (iii) Prior clearances from ridge management board, Government of Delhi shall be obtained for 17.75 acres land of southern ridge/geo- morphological ridge.
- (iv) Prior clearance from NBWL shall be obtained in respect of Ashola Wild life sanctuary.

(V)	Construction site should be adequately barricaded before the construction begins.
(vi	The building envelope for all air conditioned buildings / spaces shall be complied with the ECBC. Roofs and opaque walls should comply with the maximum assembly U factor or the minimum insulation R-value as well as lighting systems and equipment shall comply with the provisions of Energy conservation building Code.
(vi	Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
(vi	ii) Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
(ix) Bio-medical waste shall be managed as per the latest Bio-medical waste (management and handling) rules, 2016.
(x)	Radioactive waste shall be handled, stored and managed as per the guidelines of Atomic Energy Regulatory Board.
(xi	Sewage shall be treated in the STP based on MBBR technology (with tertiary treatment Ultra Filtration). The treated effluent from STP shall be recycled/re- used for flushing, horticulture & DG cooling. As proposed, wastewater from laboratory and operation theatre will be treated in the ETP of 175 KLD.
(xi	As proposed, 5 RWH pits of dia. 6.7 m & depth 7.0 m for artificial ground water recharge shall be installed as per CGWB guidelines.
(xi	Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 200 sqm. of area shall be provided for solid waste management within the premises which will include area for segregation, composting. The inert waste from project site will be sent to Municipal dumping site.
(xi	v) Solar based electric power shall be provided to each flat for atleast two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.
(x	 A First Aid Room will be provided in the project both during construction and operations of the project.
(x'	 All the top soil excavated during construction activities should be stored for use in horticulture/ landscape development within the project site.
(X'	vii) Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
(×	viii) The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environmental (Protection) prescribed for air and noise emission standards.
(xi	x) Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
(x)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
(x:	Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the State

Pollution Control Board.

- (xxii) Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.
- (xxiii) Ambient noise levels should conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
- (xxiv) Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27th August, 2003. Ready mixed concrete must be used in building construction.
- (xxv) As proposed, no ground water shall be used during construction / operation phase of the project.
- (xxvi) The approval of the Competent Authority shall be obtained for structural safety of building s due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.

II Operation Phase

- (i) The gaseous emissions from DG set shall be dispersed through adequate stack height as per CPCB standards. Acoustic enclosure shall be provided to the DG sets to mitigate the noise pollution. Low sulphur diesel shall be used. The location of the DG sets may be decided with in consultation with State Pollution Control Board.
- (ii) Fresh water requirement from ground water source shall not exceed 1031 m³/day. Prior permission shall be obtained CGWA/SGWA for ground water drawl.
- (iii) The quantity of fresh water usage, water recycling and rainwater harvesting shall be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports.
- (iv) The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the Ministry before the project is commissioned for operation. Periodical monitoring of water quality of treated sewage shall be conducted. Necessary measures should be made to mitigate the odour problem from STP.
- (v) No sewage or untreated effluent water would be discharged through storm water drains.
- (vi) Solid waste management shall be collected, treated disposed in accordance with the Municipal Solid Waste (Management & Handling) Rules, 2016.
- (vii) Rain water harvesting structure for roof run-off and surface run-off, as plan submitted should be implemented. Before recharging the surface run off, pretreatment must be done to remove suspended mater, oil and grease. The borewell for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
- (viii) Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power.
- (ix) Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED should be

		properly collected and disposed off/sent	for recycling as per the prevailing
		guidelines/rules of the regulatory authority to	
		The green belt of the adequate width and along the periphery of the plot shall be rais particulates and noise.	
13.2.12.	at Vishak	ation of existing facility and addition of hapatnam Port by M /s Vishakhapat ental Clearance – [IA/AP/MIS/60432/20	nam Port Trust- Amendment in
	•	meeting, the project proponent made a pr to the Committee:-	esentation and provided the following
	93/2	ier, the Environmental and CRZ Clearance 2012-IA III dated 25 th May, 2016. 2016 Modernization Projects at VPT are:	
	on I <u>PROJECT</u> ≻ Dev	gradation of Existing Facility and creation of i DBFOT basis (OHC & WQ-I) with a project co	ost of Rs.845.45 crores (Q-8) berth with mechanized handling
	PROJECT > Exte Visa		
	date (iv) The 25 th grac DBF (v) The	present proposal is for amendment in the s ed 25 th May, 2016. total cost of the projects reflected in the En May, 2016 is Rs. 845 crores which is the c lation of Existing Facility and creation of new FOT basis (OHC & WQ-I). refore in this regard PP has requested to inc e projects separately as below:	vironmental and CRZ Clearance dated ost of only a single project i.e. the Up- r facility at VPT for Iron ore handling on
	S.	N. Name of the project	Project Cost in Crores
	1	Up-gradation of Existing Facility and cro of new facility at VPT for Iron ore hand DBFOT basis	
	2	Development of West Quay North (WQ WQ-8) berth with mechanized handling facilities for handling bulk cargoes o DBFOT basis	
	3	Extension of Existing Container Termin the Outer Harbour of Visakhapatna	

	After detailed deliberation, the Committee recommended the proposal for aforesaid corrections.			
13.2.13.	Environmental and CRZ Clearance for the project(i) development of East quay- IA(EQ-1A)berth on south side of EQ-1(ii)development of East quay-1(EQ-1)by replacing the existing EQ-1 berth and part of EQ by M /s Vishakhapatnam Port Trust - Amendment in Environmental and CRZ Clearance [IA/AP/MIS/21758/1910][F.No.11-33/2010-IA.III]			
	During the meeting, the project proponent made a presentation and provided the following information to the Committee:-			
	 information to the Committee:- (i) The project was granted Environmental and CRZ Clearance vide letter No.11-33/2010- IA-III dated 6th June, 2011 for the project (i) development of East quay-IA(EQ-1A)berth on south side of EQ-1; (ii) development of East quay-1(EQ-1)by replacing the existing EQ-1 berth and part of EQ in Vishakhapatnam Port (Andhra Pradesh) in favour of M /s Vishakhapatnam Port Trust. (ii) The present proposal is for amendment in the above Environmental and CRZ Clearance. As per Special Condition No. 7(xii) in Environmental Clearance, it was indicated as "there shall be no transport of coal/ cargo through roads". The Concessionaire of the subject project M/s Adani Vizag coal Terminal Pvt. Ltd., has informed VPT that there are few customers in the vicinity of Port who do not have railway siding for delivery of the cargo for their use and as such requested VPT to recommend to MoEF for amendment to condition No. 7(xii) to permit / allow the cargo through road by truck movement for specific quantity to cater to the need of customers who do not have railway siding. (iii) The Andhra Pradesh Pollution Control Board vide their Renewal of Consent & Authorization Order has since renewed the CFO upto 30.11.2020. As per the above order vide item No.(14) (e) under General conditions which states as <i>'Ws. AVCTPL</i> <i>shall apply to MoEF for amendment of EC issued vide order dt.06.60.2011 with</i> <i>respect to transportation of coat/ cargo through road.</i> (iv) In view of the above, the project proponent requested to consider the above for the amendment of the Environmental and CRZ Clearance dated 6th June, 2011 for condition No (xii) of 7 as stated below: 			
	Env. Condition No.Environmental and CRZ Clearance condition as accordedProposed for amendment(xii) of 7There shall be noThere shall be transport of coal/			
	transport of coal/ cargo through terminal capacity i.e., 0.641 roads" MMTPA.			
	After detailed deliberation, the Committee recommended the proposal for amendment in the existing EC & CRZ clearance subject to satisfactory implementation of all air pollution control measures while transporting the cargo through road.			
13.2.14.	Development of Dholera Greenfield International Airport' in Village Navagam of District Ahmedabad (Gujarat) by Airport Authority of India – Amendment in Environmental Clearance – [IA/GJ/MIS/60554/2015][F.No.10-85/2011-IA.III]			

	During the meeting, the project proponent made a presentation and provided the following information to the Committee:-
	(i) The project was granted Environmental Clearance vide letter No.10-85/2011-IA.III dated 27 th November, 2015.
	 (ii) The present proposal is for amendment in the said EC. The following two amendments in Environmental Clearance for Dholera Greenfield International Airport are requested:
	 Survey number of same site as 101p (Instead of 100p) Name Taluka for same site as Dholera Taluka (instead of Tehsil Dhanduka).
	(iii) In the Environmental Clearance dated 27 th November, 2015, Survey number of site of Dholera Greenfield International Airport is mention 100 paiky in Navagam Village, Tehsil Dhanduka in Ahmadabad District, based on information provided in Form 1 and TOR.
	 (iv) Initially District Land Measurement Services, Govt of Gujarat, informed that Survey Number for land demarcated for Proposed Dholera Airport at Navagam Village is 100 paiky. Hence, in Form 1, Survey Number 100 paiky was mentioned.
	(v) Base on final site demarcation & measurement of land of proposed Dholera Airport site by office of District Inspector Land Records AhemdabadGoG, they certified Survey Number of the site is 101 p (instead of 100 p). Both Survey numbers 100 and 101 are
	 adjacent government land. (vi) As per the Government of Gujarat, Gazette Notification 09/09/2013, Schedule C, Dholera Taluka was created and Navagam Village is now comes under newly Dholera Taluka (instead of Tehsil Dhanduka).
	After detailed deliberation, the Committee recommended the proposal for amendment in the existing EC
13.2.15.	Construction of 13 th to 16 th Cargo beth at Kandlain Gujarat by M/s Kandla Port Trust (KPT) - Amendment in Environmental and CRZ Clearance[IA/GJ/MIS/61521/2008] [F.No.11-70/2006-IA-III]
	During the meeting, the project proponent made a presentation and provided the following information to the Committee:-
	 (i) The MoEF granted Environmental and CRZ Clearance to the Kandla Port Trust vide their letter No.11-70/2006-IA-III dated 1st October, 2008 for Construction of 13th to 16th Cargo berth at Kandla in Gujarat. Total 4berths (Each berth 300mx55m) and land requirement is 102.17 ha. MoEF&CC vide letter no 11/70/2006 IA III dated 7.02.2014 has already extended the validity of the environmental clearance letter till 30.09.2018. (ii) The present project is for amendment in the above Environmental and CRZ Clearance. The amendment in 16th berth by increasing in length by 50m, additional backup area 3.6
	 ha and proposed capacity 16th Berth will be 4.50MMTPA. (iii) Cost of the Project: Revised cost of cargo berth No.16 will be Rs.278.00 Crores.
	(iv) Whether the project is in critically polluted area: No.
	(v) SCZMA Recommendations: The Gujarat Coastal Zone Management Authority (GCZMA) has recommended the project vide their letter No.ENV-10-2006-138-P dated 14 th February, 2008 for 13 th to 16 th cargo berth.
	 has recommended the project vide their letter No.ENV-10-2006-138-P dated 14th February, 2008 for 13th to 16th cargo berth. (vi) Forest land : NA.
	 has recommended the project vide their letter No.ENV-10-2006-138-P dated 14th February, 2008 for 13th to 16th cargo berth. (vi) Forest land : NA. (vii) Eco-sensitive area: NA.
	 has recommended the project vide their letter No.ENV-10-2006-138-P dated 14th February, 2008 for 13th to 16th cargo berth. (vi) Forest land : NA.

Г	
	 development is undertaken at, roadside and near residential and office buildings at Kandla, Gandhidham town and surrounding villages. (x) Reclamation: Reclamation is required for additional backup area i.e. 3.6 ha.
	PP informed that KPT planned to modify the dimensions of 16 th cargo berth by increasing the length of cargo berth no 16 from 300m to 350 m with additional back up area 3.6 Ha and capacity 4.5 MMTPA. PP informed that handling capacity of cargo will remain same. Now, PP has requested for amendment in EC and CRZ clearance letter dated 07.01.2014.
	In view of the above, the Committee suggested them to submit SCZMA recommendation for the proposed modification in the berth dimension.
	The proposal was deferred till the desired information is submitted. The above information shall be provided with the uploading of minutes on the website.
13.2.16.	Construction of Shipping building facility at Pipalav Port - Amendment in Environmental Clearance [IA/GJ/MIS/20077/2009][F.No.11-60/2008-IA.III]
	The Committee deferred the project as the project proponent did not attend the meeting.
13.2.17.	Redevelopment of "SagarVaibhav Co-Op Housing Society Ltd." Plot bearing CTS no. 51 of Village Mandapeshwar, Dahisar (West), Opposite Mary Immaculate Girls School, LaxmanMhatre Road, Dahisar (West), Tehsil Borivali, District Mumbai Suburban, Mumbai by M/s Kolte-Patil Developers LtdReconsideration for Environmental Clearance - [F.No.21-31/2016-IA-III]
	Project was considered by the EAC in its 11 th meeting held on 24-26 November, 2016 wherein the Committee sought some additional information.
	Now, PP vide letter dated 3.1.2017 has submitted addl. Information. Copy of addl. Information is available on the website. During presentation, PP informed that space earmarked for solid waste management is 80 m^2 .
	After detailed deliberations, the Committee found additional information adequate and recommended the project for environmental clearance and stipulated the following specific conditions along with other environmental conditions while considering for accord of environmental clearance:
	I. Construction Phase
	 The Projects Proponents shall obtain all necessary clearance / permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.
	(ii) Construction site should be adequately barricaded before the construction begins.
	(iii) The building envelope for all air conditioned buildings / spaces shall be complied with the ECBC. Roofs and opaque walls should comply with the maximum assembly U factor or the minimum insulation R-value as well as lighting systems

/:.) I loo of water poving devices / fixtures /viz low flow flucting evotemes was of low
(iv) Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
(v	Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
(v) Sewage shall be treated in the STP based on MBBR (with tertiary treatment preferably Ultra filtration). The treated effluent from STP shall be recycled/re-used for flushing, horticulture & DG cooling.
(v	 As proposed, rooftop rainwater of buildings will be collected in 3 Nos. RWH tanks of total 40 KL capacity for harvesting after filtration.
(v	ii) Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 80sqm.of area shall be provided for solid waste management within the premises which will include area for segregation, composting. The inert waste from group housing project will be sent to dumping site at MCGM.
(i)) Solar based electric power shall be provided to each flat for atleast two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.
(x	A First Aid Room will be provided in the project both during construction and operations of the project.
(x) All the top soil excavated during construction activities should be stored for use in horticulture/ landscape development within the project site.
(x	i) Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
(x	ii) The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environmental (Protection) prescribed for air and noise emission standards.
(x	v) Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
(x	During construction phase, total water requirement is expected to be 12 KLD for workers and 10-20 KLD for construction activity which will be met by M.C.G.M. and tanker respectively. During construction phase the waste water will be disposed to existing municipal sewer line. Temporary sanitary toilets will be provided during peak labor force.
(x	<i>i</i>) As proposed, no ground water shall be used during construction / operation phase of the project.
(x	vii) The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
(x	<i>v</i> iii) Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
(x	x) Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.

		(xxi) (xxi) (xxii) (xxiii	provision of Fly Ash Notification of September, 1999 and amended as on 27 th August, 2003. Ready mixed concrete must be used in building construction. As proposed, no ground water shall be used during construction / operation phase of the project.
	П	Ор	eration Phase
		(i)	The gaseous emissions from DG set shall be dispersed through adequate stack height as per CPCB standards. Acoustic enclosure shall be provided to the DG sets to mitigate the noise pollution. Low sulphur diesel shall be used. The location of the DG sets may be decided with in consultation with State Pollution Control Board.
		(ii)	Fresh water requirement from MCGM water supply shall not exceed 95 m ³ /day.
		(iii)	The quantity of fresh water usage, water recycling and rainwater harvesting shall be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports.
		(iv)	The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the Ministry before the project is commissioned for operation. Periodical monitoring of water quality of treated sewage shall be conducted. Necessary measures should be made to mitigate the odour problem from STP.
		(v)	No sewage or untreated effluent water would be discharged through drains.
		(vi)	Solid waste management shall be collected, treated disposed in accordance with the Municipal Solid Waste (Management & Handling) Rules, 2016.
		(vii)	Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power.
		(viii)	Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.
		(ix)	The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise. Area earmarked for greenbelt is 1024 m ² .
13.2.18.			ial and commercial development at Delta-2 at Plot No2, Sector- 8,
	Lea	asing	avi Mumbai, District: Raigad, Maharashtra by M/s. Midtown Holding and Properties Pvt. Ltd -Reconsideration for Environmental Clearance - 41/2016-IA-III]
	As	the pr	oject is same as item No. 13.3.20, the project has been considered as item

	No. 13.3.20	Э.			
13.2.19.	Residential Development at Bhiwandi, Thane in Maharashtra by M/s. Tulip Land & Developers Pvt. Ltd - Reconsideration of Environmental Clearance - [F.No.21-38/2016-IA-III]				
		considered by the EAC in its 11 th meeting held on 24-26 November, 2016 wherein tee sought some additional information.			
		le letter dated 10.1.2017 has submitted addl. Information. Copy of addl. Information on the website			
	recommend conditions	detailed deliberations, the Committee found additional information adequate and ed the project for environmental clearance and stipulated the following specific along with other environmental conditions while considering for accord of tal clearance:			
	I. Con	struction Phase			
	(i)	The Projects Proponents shall obtain all necessary clearance / permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.			
	(ii)	Construction site should be adequately barricaded before the construction begins.			
	(iii)	The building envelope for all air conditioned buildings / spaces shall be complied with the ECBC. Roofs and opaque walls should comply with the maximum assembly U factor or the minimum insulation R-value as well as lighting systems and equipment shall comply with the provisions of Energy conservation building Code.			
	(iv)	Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.			
	(v)	Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.			
	(vi)	Sewage shall be treated in the STP based on MBBR (with tertiary treatment preferably Ultra filtration). The treated effluent from STP shall be recycled/re-used for flushing, horticulture & DG cooling.			
	(vii)	As proposed, rooftop rainwater of buildings will be collected in 11Nos. RWH tanks of total 205 KL capacity for harvesting after filtration.			
	(viii)	Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 220 sqm. of area shall be provided for solid waste management within the premises which will include area for segregation, composting. The inert waste from group housing project will be sent to dumping site at MCGM.			
	(ix)	Solar based electric power shall be provided to each flat for atleast two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.			
	(x)	A First Aid Room will be provided in the project both during construction and			

		operations of the project.
	(xi)	All the top soil excavated during construction activities should be stored for use in horticulture/ landscape development within the project site.
	(xii)	Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
	(xiii)	The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environmental (Protection) prescribed for air and noise emission standards.
	(xiv)	Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
	(xv)	During construction phase, total water requirement is expected to be 12 KLD for workers and 20-30 KLD for construction activity which will be met by M.C.G.M. and tanker respectively. During construction phase the waste water will be disposed to existing municipal sewer line. Temporary sanitary toilets will be provided during peak labor force.
	(xvi)	As proposed, no ground water shall be used during construction / operation phase of the project.
	(xvii)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
	(xviii)	Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
	(xix)	Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.
	(xx)	Ambient noise levels should conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
	(xxi)	Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27 th August, 2003. Ready mixed concrete must be used in building construction.
	(xxii)	As proposed, no ground water shall be used during construction / operation phase of the project.
	(xxiii)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
н	Opera	ation Phase
	he to	ne gaseous emissions from DG set shall be dispersed through adequate stack eight as per CPCB standards. Acoustic enclosure shall be provided to the DG sets mitigate the noise pollution. Low sulphur diesel shall be used. The location of e DG sets may be decided with in consultation with State Pollution Control Board.
	(ii) Fr	esh water requirement from BNCMC water supply shall not exceed 646 m ³ /day.

	(iii)	The quantity of fresh water usage, water recycling and rainwater harvesting shall be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports.
	(iv)	The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the Ministry before the project is commissioned for operation. Periodical monitoring of water quality of treated sewage shall be conducted. Necessary measures should be made to mitigate the odour problem from STP.
	(v)	No sewage or untreated effluent water would be discharged through drains.
	(vi)	Solid waste management shall be collected, treated disposed in accordance with the Municipal Solid Waste (Management & Handling) Rules, 2016.
	(vii)	Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power.
	(viii)	Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.
	(ix)	The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.
13.2.20.	Dhayari	ion of Residential & Commercial Project "DSK VISHWA" at, Kirkitwadi, , Pune, Maharashtra by M/s D. S. Kulkarni Developers Pvt. Ltd. –ToR- NCP/61211/2016] [F.No.21-11/2017-IA-III]
	proposed Referenc i.e. Town per amer	ect authorities gave a detailed presentation on the salient features of the project and d environmental protection measures to be undertaken along with the draft Term of tes for the preparation of EIA-EMP report.Proposed project falls under item no. 8 (b) aship and area development projects of the schedule of the EIA Notification, 2006. As inded notification dated 9.12.2016, covering an built up area more than 3,00,000 m ² , is categorized as Category 'A' and appraised by EAC.
	project "I 104,105 126/11/2, DhayariS Pune Ma developm obtained from 3,73	Kulkarni Developers Pvt. Ltd. has proposed for expansion of residential & commercial DSK VISHWA" at Gut No. 83/B/2, 85,86/1,87, 88,89,90,92/1,99,100, 101, 102, 103, &106 At Kirkitwadi& S.No.122/2, 126/1 (P), 126/2/1 (P), 126/3To10 (P), 126/11/1 (P), , 126/12To16, 126/2/3 & 4, 125/01 To 04, 08/58 (P), 125/6/1, 124/3, 14/4 of S.No. 124/2, 124/6, 124/7/1, 124/7/2,124/8,124/15,186, 187,188 Kirkitwadi, Dhayari, aharashtra. The project consists of Residential + Commercial + Club House nent. PP informed that environment clearance letter dated 20.10.2011 has been from SEIAA for the existing building construction project. Plot area will be increased 3,754.00m ² to 4,13,345.00 m ² and built –up area will be increased from 413820.9 m ²
	to 604188	8.3 m ² after expansion.

Solid Waste Generation	Total solid waste (Kg)	60% wet solid waste (Kg)	40% dry solid waste (Kg)
Residential	13283.5	9098.5	4185
Commercial	1031.27	618.8	412.5

Parking facilities: Parking as per DCR requirements will be provided. Adequate facility will be provided for the parking.

Parking	Existing	Proposed	Total
Car	2087	1285	3372
Scooter	5928	3238	9166
Cycles	8172	3238	11410

The power requirement will be 3.88 MW which will be sourced by MSEDC.Solar water system for Hot water and solar lighting for common areas of buildings and street light.

After detailed deliberations on the proposal, the Committee *recommended* for grant of *Terms of Reference as specified by the Ministry as Standard ToR in April, 2015 for the said project/activity* and the following TOR in addition to *Standard ToR* for preparation of EIA-EMP report:

- i. Importance and benefits of the project.
- ii. Present landuse of the proposed project site.
- iii. Copy of approved building sanction plan.
- iv. Status land acquisition.
- v. Details of no. of floor alongwithbuiltup area to be constructed in each block to be furnished.
- vi. Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.
- vii. Layout of parking plan indicating entry and exit points of vehicular movement as well as traffic management plan. Highlight the fire tender pathway.
- viii. Details of source of water supply alongwith permission to be submitted.
- ix. Treatment scheme for sewage and its recycling mode.
- x. Excess treated sewage disposal plan/scheme to be submitted.
- xi. Prediction of ground level concentration of pollutants due to DG sets.
- xii. Efforts shall be made to reduce capacity of DG set and remaining standby power shall be met from solar energy.
- xiii. Details of rain water harvesting system to be furnished. Clarity on recharge pits, storage systems for rain water and use of appropriate filtration system for collected rain water to be detailed.
- xiv. Calculation on sizing of solar water heating systems to be furnished.
- xv. A backup arrangement of at least 50% solar powered systems connected to the grid and at least two solar powered lights and one solar powered fan in each flat
- xvi. A management plan for excavation and dewatering to ensure compliance to the CGWA guidelines and regulation.
- xvii. Solid waste management plan alongwith area earmarked for solid waste management scheme.
- xviii. Management of excavated soil. Pollution control measures to be taken to control fugitive emission during construction phase including marble /stone cutting.
- xix. Details energy conservation measures to be taken. taken (all points mentioned in the proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported through drawings and details in the proposal.
 - xx. Layout plan indicating Greenbelt alongwith area earmarked to be provided.

It was recommended that 'TORs' prescribed by the Expert Appraisal Committee (Infrastru 2) should be considered for preparation of EIA / EMP report for the above mentioned proj addition to all the relevant information as per the 'Generic Structure of EIA' given in App III and IIIA in the EIA Notification, 2006.					entioned project in			
	Tuesday, 24 th January, 2017							
13.3.1.	& 6 at vill	ommercial constructio age -Achole, Dist. I tal Clearance-[IA/MH/N	Palgarh, Mahara	shtra by M/s.	Nitin Patil -			
	88/A,91/2A,9 located at La proposal is po total built-up flats are Sch (Shops: 82 no	atil has proposed for 1/2B &92/5 & 6 atVillage atitude 19°24'57.29"N an ending with SEIAA, Maha area is 31013.70 sqm. 4 ool- 6051.41 sqm, Buildi o's, Offices: 264 no's) and om 264 to 100 nos. The c	Achole, District Para d Longitude 72°49 arashtra. The total Nos of building will ng No 1: 23 nos. CFC 585.90 sqm. F	algarh,Maharashti)'02.70"E.PP infoi plot area is 1694(Il be developed. 7 of shops, Buildin PP informed that c	ra. The project is rmed that project 0.00 sqm and the The description c g no 2- 346 no office buildings wi			
		School	G+7 floors	Height 29.40 m				
		Bldg 1commercial	G+2 floors	Height 11.40m				
		Bldg 2 (offices& shops)	B+G+7 floors	Height 30.10 m				
		CFC (community Hall)	G+2 (pt) floors	Height 11.55 m				
	National Park SE) is located Cost of the construction p septic tanks w toilet blocks a operation phas Out of which f be 41 m ³ /day, from outside t 113m ³ /day and effluent will Biodegradable waste will be 2 waste manage RG area/ gree 1109.08 m ² . R	that Tungareshwar Wildl (i.e. 8.8 Km) is located w within 10 km distance of p project is Rs.71.00 Cro hase is 10 KLD which w ill be provided for dispos is temporary sanitary toil se,the total water requirer resh water requirement fr from recycled water of th puilding i.e. VIVA Resider d treated in the STP. Cool be discharged outside waste will be 113 Kg/Day 255 Kg/Day which will be ement is 33 m ² for the bu en belt will be 2441.83squ G area is provided as per During construction ph	vithin 10 km distant project. wres. The total ex- vill be sourced thro al of waste water of ets will be provide ment will be 241 m from VVCMC will be proposed building nor vill be 69 m ³ /c ling tower make up building premise y which will be proo handed over to re ilding 1 & 2, CFC a m. (20.8 %) of whic Development Con	ce. Bhayandarcre spected water re ough Tanker Wate during construction ad during peak la ³ /day during non is 53 m ³ /day, from g will be m ³ /day a day. Wastewater g requirement will b es. Solid Wast cessed in OWC. N cyclers. Space ea and 28 m ² for sche ch area earmarke trol Regulations by	eek(-95 km du quirement during er. Soak pits and h phase. 2 No. c bor force. Durin monsoon seasor tanker supply wi nd recycled wate generation will b be 134 m ³ /day. N e Management on-biodegradabl armarked for soli- ool building. Tota d for greenbelt i y VVCMC. Powe			

well as common area lighting. **Rain Water Harvesting:** Quantity of Rain Water is 53 cum/day and capacity of RWH Tanks proposed to be for harvesting after filtration will be 106 cum. **Parking Details:** For4 wheelers (according to local norms) requirement is 210 Nos. and for 2 wheelers (according to local norms) requirement is 391 Nos. Accordingly, same 225 Nos. for 4 wheelers and 391 Nos. for 2 wheelers are proposed to be provided. **Energy saving measures:** 22% power saving.

After detailed deliberations, the Committee recommended the project for environmental clearance and stipulated the following specific conditions along with other environmental conditions while considering for accord of environmental clearance:

I. Construction Phase

- (i) The Projects Proponents shall obtain all necessary clearance / permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.
- (ii) Construction site should be adequately barricaded before the construction begins.
- (iii) The building envelope for all air conditioned buildings / spaces shall be complied with the ECBC. Roofs and opaque walls should comply with the maximum assembly U factor or the minimum insulation R-value as well as lighting systems and equipment shall comply with the provisions of Energy conservation building Code.
- (iv) Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
- (v) Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
- (vi) Sewage shall be treated in the STP based on MBBR technology (with tertiary treatment i.e. Ultra Filtration). The treated effluent from STP shall be recycled/re-used for flushing, cooling tower make up, horticulture & DG cooling.
- (vii) As proposed, 106 cum of RWH Tanks will be installed for harvesting after filtration as per CGWB guidelines.
- (viii) Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 33 m² of area for the building 1 & 2, CFC and 28 m² for school building shall be provided for solid waste management within the premises which will include area for segregation, composting. The inert waste from project will be sent to dumping site of Municipality.
- (ix) Solar based electric power shall be provided to each unit for atleast two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.
- (x) A First Aid Room will be provided in the project both during construction and operations of the project.
- (xi) All the top soil excavated during construction activities should be stored for use in horticulture/ landscape development within the project site.
- (xii) Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved

		sites with the approval of competent authority.
	(xiii)	The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environmental (Protection) prescribed for air and noise emission standards.
	(xiv)	Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
	(xv)	As proposed, no ground water shall be used during construction / operation phase of the project.
	(xvi)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
	(xvii)	Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
	(xviii) Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.
	(xix)	Ambient noise levels should conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
	(xx)	Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27 th August, 2003. Ready mixed concrete must be used in building construction.
	(xxi)	As proposed, no ground water shall be used during construction / operation phase of the project.
	(xxii)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
II	Ор	eration Phase
	(i)	The gaseous emissions from DG set shall be dispersed through adequate stack height as per CPCB standards. Acoustic enclosure shall be provided to the DG sets to mitigate the noise pollution. Low sulphur diesel shall be used. The location of the DG sets may be decided with in consultation with State Pollution Control Board.
	(ii)	Fresh water requirement from VVCMC shall not exceed 53 m 3 /day and from tanker supply shall not exceed 41 m 3 /day.
	(iii)	The quantity of fresh water usage, water recycling and rainwater harvesting shall be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports.
	(iv)	The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the Ministry before the project is commissioned for operation. Periodical monitoring of water quality of treated sewage shall be conducted. Necessary measures should be made to mitigate the odour problem from STP.
		•

	(vi)	Solid waste management shall be collected, treated disposed in accordance with the Municipal Solid Waste (Management & Handling) Rules, 2016.	
	(vii) Rain water harvesting structure for roof run-off and surface run-off, as pla submitted should be implemented. Before recharging the surface run off, pr treatment must be done to remove suspended mater, oil and grease. The borewe for rainwater recharging should be kept at least 5 mts. above the highest groun water table.		
	(viii)	Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power.	
	(ix)	Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.	
	(x)	The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.	
13.3.2.	Expansion of building (from 104810 Sq.m. to 131355.699 Sq.m) at Survey No. 4/2 (p), 14/4B (P), 16, 17(P), Village Vadgon, Budruk District Puna, Maharashtra by M/s Paranjape Scheme Construction Ltd- Environmental Clearance – [IA/MH/NCP/60602/2016][F.No.21-84/2016-IA-III]		
	M/s Paranjape Scheme Construction Ltd has proposed for expansion of building (from 104810 Sq.m. to 131355.699 Sq.m) at Survey No. 4/2 (p), 14/4B (P), 16, 17(P), Village Vadgon, Budruk District Puna, Maharashtra. SEIAA vide letter no SEAC-2011/CR.623/TC.2 dated 3 rd November, 2011 has granted environmental clearance to M/s Paranjape Schemes (Construction) Ltd. for expansion residential project. Constructed area till date is 99,096.54 m ² . The total plot area is 54,362 m ² . FSI area is 58,092.16 m ² and total construction area is 1,31,771.85 m ² . The project comprise of 12 Residential Buildings with 6 row house. Total 961 no. of tenements shall be developed. Maximum height of the building is 36.00 m. Cost of the project is Rs. 234 Cr.		
	met by ta for dispose During op 658 m ³ /d Corporati treated w CMD cap kg/day so be treated will be ha phase is recharged 2,039 two	onstruction phase, total water requirement is expected to be 100 CMD which will be nker water. During the construction phase, soak pits and septic tanks will be provided sal of waste water. Temporary sanitary toilets will be provided during peak labor force. Derational phase, total water demand of the project will be reduced from 676 m ³ /day to lay after expansion. Out of which, fresh water requirement from Pune Municipal on will be 434 m ³ /day and remaining water requirement (219 m ³ /day) will be met from astewater. Wastewater generation will be 566 m ³ /day and treated in STP of 2 x 300 bacity. About 320 m3/day will be discharged in Municipal sewer lines. About 2419 blid waste will be generated in the project. The biodegradable waste (1451 kg/day) will d by mechanical composting and the non-biodegradable waste generated (967 kg/d) inded over to authorized contractors. The total power requirement during construction 300kVA and will be met from MSEDCL and Total power requirement during operation 4.42 MW and will be met from MSEDCL. Rooftop rainwater of buildings will be d in ground through 30 nos of recharge pits. Parking facility for 657 four wheelers, by wheelers and 1,719 cycles are proposed to be provided against the requirement of wheelers, 2,039 two wheelers and 1,719 cycles respectively (as per local norms).	
	After deta	ailed deliberation, the Committee sought following additional information:	
	(i)	Certified compliance report issued by the Regional Office, Nagpur on the existing	

		anvironmentel og	nditions stipulated in anvironm	ntal algorange		
	(ii)		nditions stipulated in environme e past history of the project rela rashtra		of application at	
	(iii)	Respond to the comments made by the SEAC/SEIAA during the presentations at Maharashtra, based on minutes of SEAC/SEIAA meetings.				
	(iv)					
	(v)	Copy of approve Committee of Ma	d Sanction plan. Approval of th harashtra.	ne project from Hig	gh Rise Building	
	(vi)	• •	cating road, greenbelt, draina rain water harvesting structur	•		
	(vii)	Layout of parking	g plan indicating entry and exi nagement plan. Highlight the fi			
	(viii)		of water supply alongwith perm			
	(ix)		ewage disposal plan/scheme to			
	(x) (xi)		und level concentration of emiss nade to reduce capacity of DG			
		shall be met from	, ,			
	(xii)	Calculation on size	zing of solar water heating syste			
	(xiii)	At least 2 solar powered lights and one fan shall be provided in each flat. Solar				
	(•	be connected to the grid.		an a Rabara ta	
	(xiv)	Solid waste management plan alongwith area earmarked for solid waste				
	(xv)	management scheme. Management of excavated soil. Pollution control measures to be taken to control fugitive emission during construction phase including marble /stone cutting.				
	(xvi)	Details energy conservation measures to be taken, taken (all points mentioned in the proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported through drawings and details in the proposal				
	(xvii)	Layout plan indicating Greenbelt alongwith area earmarked to be provided.				
			till the desired information is loading of minutes on the webs		oove information	
13.3.3.			osed Residential & Comm		-	
			No. 10 of Village Achole,		_	
	Maharashtra by M/s Deepak H Thakur- Environmental Clearance – [IA/MH/NCP/60984/2016][F.No.21-85/2016-IA-III]					
	M/s Deepa	ik H Thakur has r	proposed for development of R	esidential & Comn	nercial project at	
	M/s Deepak H Thakur has proposed for development of Residential & Commercial project at plot bearing S.No.86 B, H.No 9 &H.No. 10 of Village Achole, Taluka, Vasai, Dist- Palghar,					
	Maharashtra. PP informed that the project was appraised by SEAC-II, Maharashtra in their 49 th					
	SEAC-II meeting dated 25-08-2016 as an Item No58 & is recommended for grant of EC to SEIAA.					
			.10 sqm and the total built up		•	
			e total nos. of flats proposed to			
		•	be provided. The maximum h project is as under:-	eight of the buildir	192 mili ne 03.35	
			-		,	
		Buildings	Cround floor opponing u 15	Height		
		A to C	Ground floor shopping + 1 ^s	^t 69.95 m		

upper habitable Floors		podium+ 2 nd podium + 3 rd Level (R.G)Podium + 4 th to 22 nd upper habitable Floors	
------------------------	--	--	--

It is reported that Tungareshwar Wildlife Sanctuary (8.89 Km) and ESZ of Sanjay Gandhi National Park (i.e. 8.8 Km) is located within 10 km distance. Bhayandarcreek(-9..5 km due SE) is located within 10 km distance of project.

The total expected water requirement during construction phase will be 15 KLD which will be Outsourced through Tanker. Septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided during peak labor force. The total water demand during operation phase will be 177 KLD. Out of which, fresh water requirement from VVMC water supply will be 108 m³/day and remaining water requirement 69m³/daywill be met from recycled water/treated water. Wastewater generation will be 153 m³/day and treated in the STP. Treated water will be used for (59 KLD For flushing and 84 KLD for cooling tower of Viva Mall near project site).

Biodegradable waste generation will be 316Kg/Day, which will be processed and treated in OWC to convert into organic manure. Non-biodegradable waste will be 258 Kg/Day which will be handed over to authorized local vendor. Space earmarked for solid waste management is 136 m². Quantity of Rain Water is 46 cum and Capacity of RWH Tanks for harvesting after filtration will be 92 cum. Area earmarked for greenbelt is 1159 m² and area earmarked for RG is 1505.11 m². Parking Details: For 4 wheelers 242 Nos and for 2 wheelers 216 Nos. will be provided. Power Requirement: During construction phase 100 kVA which will be outsourced through MSEDCL. DG set (200 KVA) will be installed.

After detailed deliberations, the Committee recommended the project for environmental clearance and stipulated the following specific conditions along with other environmental conditions while considering for accord of environmental clearance:

I. Construction Phase

- (i) The Projects Proponents shall obtain all necessary clearance / permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.
- (ii) Construction site should be adequately barricaded before the construction begins.
- (iii) The building envelope for all air conditioned buildings / spaces shall be complied with the ECBC. Roofs and opaque walls should comply with the maximum assembly U factor or the minimum insulation R-value as well as lighting systems and equipment shall comply with the provisions of Energy conservation building Code.
- (iv) Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
- (v) Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
- (vi) Sewage shall be treated in the STP based on MBBR technology (with tertiary treatment i.e. Ultra Filtration). The treated effluent from STP shall be recycled/re-used for flushing, cooling tower make up, horticulture & DG cooling.

(∨ii)	As proposed, 92 cum of RWH Tanks will be installed for harvesting after filtration as per CGWB guidelines.
(viii)	Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 136 m ² of area for the proposed building shall be provided for solid waste management within the premises which will include area for segregation, composting.The inert waste from project will be sent to dumping site of Municipality.
(ix)	Solar based electric power shall be provided to each unit for atleast two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.
(x)	A First Aid Room will be provided in the project both during construction and operations of the project.
(xi)	All the top soil excavated during construction activities should be stored for use in horticulture/ landscape development within the project site.
(xii)	Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
(xiii)	The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environmental (Protection) prescribed for air and noise emission standards.
(xiv)	Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
(xv)	As proposed, no ground water shall be used during construction / operation phase of the project.
(xvi)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
(xvii)	Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
(xviii)	Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.
(xix)	Ambient noise levels should conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
(xx)	Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27 th August, 2003. Ready mixed concrete must be used in building construction.
(xxi)	As proposed, no ground water shall be used during construction / operation phase of the project.
(xxii)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
	National Daharng Codo molading protocion modoaroo nom ignoring oto.

	II Operation Phase			
	(i)	The gaseous emissions from DG set shall be dispersed through adequate stack height as per CPCB standards. Acoustic enclosure shall be provided to the DG sets to mitigate the noise pollution. Low sulphur diesel shall be used. The location of the DG sets may be decided with in consultation with State Pollution Control Board.		
	(ii)	Fresh water requirement from VVCMC shall not exceed 108m ³ /day.		
	(iii)	The quantity of fresh water usage, water recycling and rainwater harvesting shall be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports.		
	(iv)	The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the Ministry before the project is commissioned for operation. Periodical monitoring of water quality of treated sewage shall be conducted. Necessary measures should be made to mitigate the odour problem from STP.		
	(v)	No sewage or untreated effluent water should be discharged into storm water drain.		
	(vi)	Solid waste management shall be collected, treated disposed in accordance with the Municipal Solid Waste (Management & Handling) Rules, 2016.		
	(vii)	Rain water harvesting structure for roof run-off and surface run-off, as plan submitted should be implemented. Before recharging the surface run off, pre- treatment must be done to remove suspended mater, oil and grease. The borewell for rainwater recharging should be kept at least 5 mts. above the highest ground water table.		
	(viii)	Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power.		
	(ix)	Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.		
	(x)	The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.		
13.3.4.	Proposed Reconstruction redevelopment of J K Project at CTS No. 1552, Girgau8m division Gamdevi, HarishchandraGoregaonkar Road, Mumbai by M/s Floreat Investments Private Limited - [IA/MH/NCP/60409/2016][F.No.21-86/2016- IA-III]			
		mittee deferred the project as the project proponent did not attend the meeting.		
13.3.5.	Expansion of redevelopment Project at Plot No. 18 to 21 & 23 to 26 CTS No. 195 (pt) D. N. Nagar, MHADA layout, Andheri (West) Mumbai, Maharashtra by M/s. Axayraj Build Well Pvt. Ltd Environmental Clearance -[F.No.21-87/2016-IA-III][IA/MH/NCP/60145/2016]			
	sqm to 65 (pt) D. N	yraj Build Well Pvt. Ltd. has proposed for expansion (built up area from 56,041.69 5,745.64 sqm) of redevelopment Project at Plot No. 18 to 21 & 23 to 26 CTS No. 195 I. Nagar, MHADA layout, Andheri (West) Mumbai, Maharashtra. The project was anted Environmental Clearance vide letter No. 21-260/2008-IA-III received dated 6 th		

May, 2011 for construction area 56,041.69 sqm. However, 41755.82 sqm has been constructed on site as per Environmental Clearance obtained dated 6th May, 2011.

The total plot area is10,278.39 sqm andtotal built up area is 65,745.64 sqm after expansion. The total flats proposed to be developed are Residential -355 Nos, Shops - 224 nos, Offices - 542 Nos. & Restaurant - 3 Nos. The maximum height of the buildings will be 53.15 m. the building configuration is as follows:

Build	ling configuration	on	Height
Ground + 1st to 3 rd Commercial	A,B,C,D,E,F & H	5 th to 14 th floor up	53.15 m
floor + 4 th to 5 th (pt) Podia - plus (residential above)	G1, G2, I1, I2	4 th to 15 th floor up	

It is reported that Eco Sensitive Zone of Sanjay Gandhi national park (3.1 Km away) is located within 10 km distance. **Cost of the project is** Rs.89.97 Crores. Total water requirement will be increased from 360 m³/day to 413 m³/day after expansion. Total wastewater generation will be increased from 265 to 367 m3/day after expansion. The capacity of STP will be 380 KLD. 150 KLD excess treated water will be drained to municipal drain. 813 Kg/Day Biodegradable waste will be processed and treated in OWC to convert into organic manure. 1010 Kg/Day Non-biodegradable waste which will be handed over to authorized local vendor. **The quantity of rainwater is** 36.7 cum and the RWH tanks having capacity of 80 cum for harvesting after filtration will be provided. Minimum Parking capacity for 4 wheeler required as per Local Norm is 439 nos and same will be provided.

After detailed deliberation, the Committee sought following additional information:

- (i) Certified compliance report issued by the Regional Office, Nagpur on the existing environmental conditions stipulated in environmental clearance.
- (ii) Give a conformity status to conditions stipulated in Annexure XIV of the amended EIA notification of 09-12-2016.
- (iii) Copy of approved Sanction plan. Approval of the project from High Rise Building Committee of Maharashtra.
- (iv) Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.
- (v) Layout of parking plan indicating entry and exit points of vehicular movement as well as traffic management plan. Highlight the fire tender pathway.
- (vi) Water balance to be rechecked and submitted.
- (vii) Excess treated sewage disposal plan/scheme to be submitted.
- (viii) Prediction of ground level concentration of emissions from stack due to DG sets.
- (ix) At least 2 solar powered lights and one fan shall be provided in each flat. Solar generation shall be connected to the grid.
- (x) Solid waste management plan alongwith area earmarked for solid waste management scheme.
- (xi) Action plan for disposal of construction and demolition waste to be submitted.
- (xii) Management of excavated soil. Pollution control measures to be taken to control fugitive emission during construction phase including marble /stone cutting.

(xiii) Details energy conservation measures to be taken. taken (all points mentioned in the proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported through drawings and details in the proposal

	(xiv) Increase the greenbelt area. Layout plan indicating Greenbelt alongwith area earmarked to be provided.
	The proposal was deferred till the desired information is submitted. The above information shall be provided with the uploading of minutes on the website.
13.3.6.	Proposed Slum Rehabilitation Project at CTS No. 4958 D, 4958 D/1 to 124 of village Kolekalyan, Santacruz (E), Mumbai, Maharashtra by M/s. Amrapali S.R.A. C.H.S. Ltd - Environmental Clearance [IA/MH/NCP/60992/2016][F.No.21-88/2016-IA-III]
	M/s. Amrapali S.R.A. C.H.S. Ltd has proposed for development of Slum Rehabilitation Project at CTS No. 4958 D, 4958 D/1 to 124 of village Kolekalyan, Santacruz (E), Mumbai, Maharashtra. Slum Rehabilitation Authority vide letter no SRA/ENG/2547/HE/PVT/LOI dated 15 th September, 2014 has issued LOI for proposed SR Scheme. The project will be located at Latitude 19° 4'20.157"N, and longitude72°51'45.240"E.The total plot area is 3881.60 sqmand total built up area is23120.923 sqm. Total 278 Flats and 2 shops shall be developed. The maximum height of the building is 44.4 m. Cost of the project is Rs 85.81 crore
	It is located within 10 km of Sanjay Gandhi National Park Eco Sensitive areas
	During construction phase, total water requirement is expected to be 10 - 20 KLD which will be met by tanker water. During the construction phase, soak pits and septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided during peak labour force. During operational phase, total water demand of the project is expected to be 202 KLD. Out of which fresh water requirement is 129 KLD (Composite Building: 91 KLD and Sale Building: 38 KLD) which will be met by the Municipal Corporation of Greater Mumbai. Wastewater generated 171 KLD (Composite Building:122 KLD and Sale Building: 49 KLD) will be treated in 2 STPs of total capacity 190 KLD (Composite Building:135 KLD and Sale Building: 55 KLD) of treated wastewater will be recycled (68 KLD for flushing, 5 for gardening). About 81 KLD will be disposed in to municipaldrain.
	About 761kg/day solid waste will be generated in the project. The biodegradable waste (453 kg/day) will be processed in OWC and the non- biodegradablewaste generated (308 kg/day) will be handed over to local vendor. The total power requirement during construction phase is 142 kW and will be met from TATA power. The total connected load requirement during construction phase is 2227.4 KW (Composite Building: 1012.2 KW and Sale Building: 1215.2 KW) and will be met from Reliance/TATA/Local Electricity provider.1 D.G. set of 320 KVA and 1 D. G. set of 380 KVA will be providedfor power backup. Rooftop rainwater of buildings will be collected in 4 RWH pits.
	Parking facility : Parking facility for 136 no. of four wheelers and is proposed to be provided against the requirement of 140 no. (According to local norms). Proposed energy saving measures would save about 20% of power.
	After detailed deliberation, the Committee sought following additional information:
	 (i) Give a conformity status to conditions stipulated in Annexure XIV of the amended EIA notification of 09-12-2016. (ii) Efforts shall be made to provide car parking to each flat. (iii) Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.

	(iv)	Details of RG area earmarked for the project.	
	(v)	Layout of parking plan indicating entry and exit points of vehicular movement as well	
		as traffic management plan. Highlight the fire tender pathway.	
	(vi)	Water balance to be rechecked and submitted.	
	(vii)	Excess treated sewage disposal plan/scheme to be submitted.	
	(viii)	Prediction of ground level concentration of emissions from stack due to DG sets.	
	(ix)	At least 2 solar powered lights and one fan shall be provided in each flat. Solar	
		generation shall be connected to the grid.	
	(x)	Solid waste management plan alongwith area earmarked for solid waste	
	,	management scheme shall restimated.	
	(xi)	Action plan for disposal of construction and demolition waste to be submitted.	
	(xii)	Management of excavated soil. Pollution control measures to be taken to control	
		fugitive emission during construction phase including marble /stone cutting.	
	(xiii)		
		the proposal such as orientation to support reduced heat gain, use of ASHRAE	
		90.1, use of ECBC compliant envelope measures to be supported through drawings	
		and details in the proposal	
	(xiv)	Increase the greenbelt area. Layout plan indicating Greenbelt alongwith area	
		earmarked to be provided.	
		posal was deferred till the desired information is submitted. The above information provided with the uploading of minutes on the website.	
13.3.7.	& 6 S. Village Environ	ed Residential cum commercial project at Plot bearing S. No. 131 H.No. 5 No. 133 H. No. 2,3 S. No. 139 H.No. 5, 15, 17/1 S.No. 140, H. No. 2/5 at Virar Taluka Vasai District Thane, Maharashtra by M/s Viva Shelter - mental Clearance –[F.No.21-89/2016-IA-III][IA/MH/NCP/60397/2016]	
	M/s Viva Shelter has proposed for development of Residential cum commercial project at Plot bearing S. No. 131 H.No. 5 & 6 S. No. 133 H. No. 2,3 S. No. 139 H.No. 5, 15, 17/1 S. No. 140, H. No. 2/5 at Village Virar Taluka Vasai District Thane, Maharashtra. It is reported that Vaitarna creek (4.6 Km), Ranal Talav (0.7 km) and Manvel Pad Lake (0.5 km) are located within 10 km distance. Project site is located adjacent to forest area. The project is located at 19°26'55.99"N Latitude and 72°49'32.37"E Longitude. The project site is located at 6 km from the boundary of Tungareshwar Wildlife Sanctuary protected area.		
	1,04,031 Flats, 11	I plot area is 58,510 m ² . FSI area is 57,749.76 m ² and total construction area is .86 m ² . The project comprises of 9 Residential Buildings, 1 MHADA Building, 1,532 I Bungalows and 7 Row houses, 42 shops and 2 C.F.C.s shall be developed. n height of the building is 65.10 m. configuration of the building is as given below:	

BLDG NOS/TYPE	WINGS	BLDG CONFIGURATION	NO. OF FLATS/SHOPS	POPULATION (NOS)
RESIDENTIAL Z	RESIDENTIAL ZONE			
1	A, B & C	G+16	250	1250
2	A & B	ST+21	162	810
3	A ,B,C,D & E	G+16	342	1710
4	A ,B & C	G+16	218	1090
5		ST+16	62	310
6	A, B & C	ST+16	218	1090
7	B1(BUNGALOW)	G+1	1	5
8	B2(BUNGALOW)	G+1	1	5
9		G+7	14	70
C.F.C. 1	-	ST+2		119
SHOPS			42	126
GREEN ZONE				
1		ST+1	8	40
2	A,B,C & D	ST+4	112	560
BUNGALOW	1 to 11	G+1	11	55
ROW HOUSES	1 to 7	G+1	7	35
C.F.C. 2		ST+2		119
MHADA BUILDINGS	A,B,C,D,E,F & G	ST+4	144	720
Total				8114

- (i) During construction phase, total water requirement is expected to be 100 KLD which will be met by tanker water. During the construction phase, soak pits and septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided during peak labor force.
- (ii) During operational phase, total water demand of the project is expected to be 732 KLD and same will be met by fresh water from VVCMC (Municipal Water Supply) and recycled water. Wastewater generated (627 KLD) uses will be treated in STP of 700 KLD capacity. 170 KLD of treated wastewater will be recycled for flushing. About 450 KLD will be discharged in Municipal sewer lines.
- (iii) About 3948 kg/d solid waste will be generated in the project. The biodegradable waste (2368 kg/d) will be processed in mechanical composting (Eco-biocompack) and the non-biodegradable waste generated (1580 kg/d) will be handed over to authorized local vendor.
- (iv) The total power requirement during construction phase is 200 kVA and will be met from MSEDCL and Total power requirement during operation phase is 4 MW and will be met from MSEDCL.
- (v) Rooftop rainwater of building will be collected in 6 RWH tank of total 400 m³ capacity for harvesting after filtration.
- (vi) Parking facility for 888 Nos. four wheelers are proposed to be provided against the requirement of 888 four wheelers (as per local norms) and 1598 two wheelers are proposed to be provided.
- (vii) Proposed energy saving measures would save about 21.15 % of power.

After detailed deliberation, the Committee sought following additional information:

	(i) Londuce of the project site
	(i) Landuse of the project site.
	(ii) Status project proposal in the SEIAA, Maharashtra.
	(iii) Distance of project site from the reserve forest to be submitted.
	(iv) Give a conformity status to conditions stipulated in Annexure XIV of the amended
	EIA notification of 09-12-2016.
	(v) Copy of approved Sanction plan.
	 (vi) Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished. (vii) Details of RG area earmarked for the project. (viii) Layout of parking plan indicating entry and exit points of vehicular movement as well as traffic management plan. Highlight the fire tender pathway. (ix) Water balance to be rechecked and submitted. (x) Excess treated sewage disposal plan/scheme to be submitted. (xi) Action plan to prevent the nearby water bodies from water pollution due to the proposed project. (xii) Prediction of ground level concentration of emissions from stack due to DG sets. (xiii) At least 2 solar powered lights and one fan shall be provided in each flat. Solar generation shall be connected to the grid. (xiv) Solid waste management plan alongwith area earmarked for solid waste management scheme shall restimated. (xv) Management of excavated soil. Pollution control measures to be taken to control fugitive emission during construction phase including marble /stone cutting. (xvi) Details energy conservation measures to be taken. taken (all points mentioned in the proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported through drawings and details in the proposal (xvii) Increase the greenbelt area. Layout plan indicating Greenbelt alongwith area
	earmarked to be provided. The proposal was deferred till the desired information is submitted. The above information shall be provided with the uploading of minutes on the website.
13.3.8.	Amendment in development of commercial building at Plot bearing S.No. 169/1, Sector - I & II (part), Aundh, Pune (Maharashtra) by M/s Chitrali Properties Pvt Ltd - Environmental Clearance -[F.No.21-90/2016-IA-III][IA/MH/NCP/60444/2016]
	M/s Chitrali Properties Pvt Ltd has proposed for modification in the configuration of commercial building at Plot bearing S. No. 169/1, Sector - I & II (part), Aundh, Pune (Maharashtra).
	The project was granted Environmental Clearance vide letter No. 21-366/2007-IA-III dated 07.12.2007 and the EC was revalidated up to 07.12.2017 by SEIAA on 24.09.2015. The Environment Clearance received in 2007 was for a total Built up Area (BUA) of 91,000 sqm. and proposed to have one building each in sector I and II Part i.e. Building A (Sector I) comprising of Mall, Multiplex and Hotel having total 18 Floors and Building B (Sector II) comprising of IT office and retail.
	Now, PP has proposed modifications in the project configuration of the building A (Part). So that built-up area has decreased from 91000 m2 to 76416 m ² due to reduction in number of floors as per modified PMC approval. The change applies only to building A. The total plot area is 29,500 sqm, total FSI is 45,634 sqm, total Premium Paid Non-FSI is 30,782 sqm and total built up area will be 76,416 sqm. The project comprising of Sector I & II (part). Sector I has one

building named as Building A which comprises of Mall, Multiplex and proposed IT /offices. Sector II (part) has one building named as Building B comprising of IT office and retail. The maximum height of the **building A** considering total proposal upto 9th floor is 65.925 m. (Top of mumty level). The height of the **building A** as per the present PMC approved plan upto 4th floor is 33.925 m (Terrace level). The height upto mumty level for the same is 38.925m.
 Details of proposed Building configuration vis – a- vis EC granted in 2007 is as given below:

As per EC granted in 2007	As per amendment sought	Remarks
Sector 1 Building A : 2 basements + Ground North + Ground South + 13 floors	T2 basements + Ground North + Ground South + HGF + 1 st Floor +2 nd Floor + Third Floor (Part) + Service Floor + Fourth Floor (Two Floors for IT/Office use) Part Ground Floor South, Part Higher Ground Floor, Part First Floor & Part Second Floor at South Side of the building as proposed amendment in EC	Change in Building A Configuration
Sector 2 (P): Building B (IT Building) 3 Basements + Ground + 7 Floors	Sector 2 (P) : Building B (IT Building) 3 Basement + Ground + 7 floors	No change
Height of building A = 66.32 m Building B = 32.10 m	Height of building A = 33.925 m Building B = 32.10 m	Decrease
Total water requirement 722 m3/day	462 m3/day	Decrease
Sewage generation 575 m3/day	300 m3/day	Decrease
STP capacity 480 m3/day	300 m3/day for building A and 80 m3/day for building B	Decrease
Solid Waste 200 kg/day	1320 Kg/ day	Increased
Greenbelt	6011 m ²	
Parking 850	1438	Increased
DG set 850 KVA	1438 KVA	Increased
Energy Requirement	15 MW	15 MW

Area already constructed area is 33152 m2 for Building A and 32394 m2 for Building B. Area pending for construction in Building A as per sanctioned plan is 10870 m².

P informed that 2 court cases are pending in the NGT against the project.

After detailed deliberation, the Committee sought following additional information:

- (i) Certified compliance report issued by the Regional Office, Nagpur on the existing environmental conditions stipulated in environmental clearance.
- (ii) Present status of NGT cases against the project. Submit the copy of latest NGT Orders.

	(iii) Give a conformity status to conditions st notification of 09-12-2016.	tipulated in Annexure λ	(IV of the amended EIA	
	(iv) Copy of approved Sanction plan. App Committee of Maharashtra.	roval of the project fr	om High Rise Building	
	(v) Status project proposal in the SEIAA, Ma	harashtra.		
	(vi) Copy of approved Sanction plan.			
	()			
	 (vii) Layout plan indicating road, greenb handling area, rain water harvesting st (viii) Layout of parking plan indicating entry as traffic management plan. Highlight (ix) Water balance to be submitted. (x) Excess treated sewage disposal plan/s (xi) Prediction of ground level concentration 	ructure, etc. in different and exit points of vehi the fire tender pathway scheme to be submitted	t colour to be furnished. icular movement as well /. d.	
	(xii) Efforts shall be made to reduce the ca			
	(xiii) At least 2 solar powered lights and generation shall be connected to the g	one fan shall be prov	ided in each flat. Solar	
	(xiv) Details energy conservation measures proposal such as orientation to suppor of ECBC compliant envelope measures details in the proposal	t reduced heat gain, us	se of ASHRAE 90.1, use	
	details in the proposal (xν) Increase the greenbelt area. Layout plan indicating Greenbelt alongwith are			
	earmarked to be provided. The proposal was deferred till the desired info shall be provided with the uploading of minutes of		The above information	
13.3.9.	Residential Project (Proposed Slum Re C.T.C No. 123(Pt), 1835 (Pt), 116 (Pt), S Mumbai by Grace Urban Development [F.No.21-91/2016-IA-III] [IA/MH/NCP/61095 The Committee deferred the project as t meeting.	No. 14,14A of villa Corporation-Enviro /2016]	ige Chembur, Kurla, nmental Clearance -	
13.3.10.	Proposed residential cum commercial bu 431/196,F. P. No. 37/B1 + B2 at Shukarva M/s. Olympia – Environmenta III][IA/MH/NCP/61233/2016]	rPeth,Tilak Road, P		
	M/s. Olympia has proposed for development of residential cum commercial building "Avaant at C.T.S. No. 431/195 & 431/196,F. P. No. 37/B1 + B2 at ShukarvarPeth, Tilak Road, Pune Maharashtra. PP informed that case in not pending with SEIAA, Maharashtra. The project located at Latitude 18°30'16.59"N and Longitude 73°51'14.35"E.The total plot area is 6,626.7 m ² . Out of which area earmarked for RG is 1258.11 m ² . The project will comprise of 0 Buildings with 48 Nos. of tenements, 8 shops and 13 offices. Total built-up area of 31876.05m ² . PP has proposed to increase the built-up area from 17123.4 m2 to 31876 m The maximum height of the building is 87.57m. Building configuration is as given below :			
	Building Configuration	Height	Component	
		82.57 m		
	1 Commercial + Residential (B +	02.37 111	Tenements 45;	

	3 rd Parking + Podium + 1-17 Residential Floors		
2	EWS Residential (Parking + 3 Floors)	16.5 m	Tenements 3

It is reported that Mutha River (1.5 km), Katraj lake (Zoo, 5.3 Km), Peshave Park Lake (0.35 Km), Jambhulwadi Lake (7.3 Km) and Khadakwasla Dam(11.24 km) are located within 15 km distance. **Cost** of the project is Rs. 173 crores.

During construction phase, total water requirement is expected to be 4KLD which will be met by water from Potable water tankers. During the construction phase, soak pits and septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided during peak labor force. During operational phase, total water requirement for the project will be 65 m³/day. Out of which fresh water requirement from Pune Municipal Corporation water supply will be 31 m3/day and remaining water requirement (34 m³/day) will be met from recycled Water/treated water. Wastewater generation will be 47m³/day and treated in STP of total 50m³/day capacity. 42m³/day of treated wastewater will be recycled (22 for flushing, 12 for gardening). About 8m³/day will be disposed-off suitably.

About 220kg/day solid waste will be generated in the project. The biodegradable waste (113kg/day) will be processed in OWC and the non-biodegradable waste generated (107kg/day) will be handed over to PMC. Area earmarked for solid waste management is 50 m². The Committee suggested them that atleast 80 m² space shall be provided for soldi waste management. The total power requirement during construction phase is 25 KVA and will be met from MSEDCL and total power requirement during operation phase is 846kW and will be met from MSEDCL. Rooftop rainwater of buildings will be collected in RWH tanks of total. 75.85m³ capacity for harvesting after filtration. 05 nos of recharge pits of size 2.5m x 2.5m x 2m (1m filter media) will be proposed. PP also confirmed that proposed site shall not used for car servicing. DG sets (315 KVA (2 Nos.) + 200 (KVA x 1) will be installed.

Parking facility for 250 Four wheelers and 395 two wheelers is proposed to be provided against the requirement of 250 and 395 respectively (according to local norms). The description of the parking is as under:

Building	Configuration	Required	Proposed
1	Commercial + Residential	250 Cars 395 Scooters 195 Cycles	250 Cars 395 Scooters 195 Cycles
2	EWS Residential	2 Cars 8 Scooters 8 Cycles	2 Cars 8 Scooters 8 Cycles

Floor wise Parking Nos. are as follows;

Sr. No.	FLOORS	Available Car park	Available Scooters	Available Cycle
1	Basement floor	46	13	0
2	Ground floor	102	0	195
3	Second floor	51	64	0
4	Third floor	51	84	0
5	Podium floor	0	234	0
Total Pr MOEF	oposed Parking for	250	395	195
Total Re	quired Parking as per	250	395	195

		Norms
	arance	r detailed deliberations, the Committee recommended the project for environmental and stipulated the following specific conditions along with other environmental while considering for accord of environmental clearance:
н.	Co	nstruction Phase
	(i)	The Projects Proponents shall obtain all necessary clearance / permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.
	(ii)	Construction site should be adequately barricaded before the construction begins.
	(iii)	The building envelope for all air conditioned buildings / spaces shall be complied with the ECBC. Roofs and opaque walls should comply with the maximum assembly U factor or the minimum insulation R-value as well as lighting systems and equipment shall comply with the provisions of Energy conservation building Code.
	(iv)	Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
	(v)	Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
	(vi)	Sewage shall be treated in the STP (with tertiary treatment i.e. Ultra Filtration). The treated effluent from STP shall be recycled/re-used for flushing, horticulture & DG cooling.
	(vii)	As proposed, rooftop rainwater of buildings will be collected in RWH tanks of total. $75.85m^3$ capacity for harvesting after filtration. 05 nos of recharge pits of size 2.5m x 2.5m x 2m (1m filter media) shall be provided as per CGWB guidelines.
	(∨iii)	Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 80 m ² of area for the proposed building shall be provided for solid waste management within the premises which will include area for segregation, composting.The inert waste from project will be sent to dumping site of Municipality.
	(ix)	Solar based electric power shall be provided to each unit for atleast two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.
	(x)	A First Aid Room will be provided in the project both during construction and operations of the project.
	(xi)	All the top soil excavated during construction activities should be stored for use in horticulture/ landscape development within the project site.
	(xii)	Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
	(xiii)	The diesel generator sets to be used during construction phase should be low

sulphur diesel type and should conform to Environmental (Protection)
prescribed for air and noise emission standards.
Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
As proposed, no ground water shall be used during construction / operation phase of the project.
The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.
Ambient noise levels should conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27 th August, 2003. Ready mixed concrete must be used in building construction.
As proposed, no ground water shall be used during construction / operation phase of the project.
The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
tion Phase
e gaseous emissions from DG set shall be dispersed through adequate stack ight as per CPCB standards. Acoustic enclosure shall be provided to the DG sets mitigate the noise pollution. Low sulphur diesel shall be used. The location of e DG sets may be decided with in consultation with State Pollution Control Board.
esh water requirement from Pune Municipal Corporation Water Supplyshall not ceed 31 m ³ /day.
e quantity of fresh water usage, water recycling and rainwater harvesting shall be easured and recorded to monitor the water balance as projected by the project oponent. The record shall be submitted to the Regional Office, MoEF&CC along th six monthly Monitoring reports.
the installation of the Sewage Treatment Plant (STP) should be certified by an dependent expert and a report in this regard should be submitted to the Ministry fore the project is commissioned for operation. Periodical monitoring of water ality of treated sewage shall be conducted. Necessary measures should be made mitigate the odour problem from STP.
sewage or untreated effluent water should be discharged into storm water drain.
lid waste management shall be collected, treated disposed in accordance with e Municipal Solid Waste (Management & Handling) Rules, 2016.

		submitted should b treatment must be c	ting structure for roof run-off and s e implemented. Before recharging the lone to remove suspended mater, oil a ging should be kept at least 5 mts. al	he surface run off, pre- ind grease. The borewell			
	```	•	e used for lighting in the apartment to re- ric meter shall be installed for solar pow	•			
		Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.					
		The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.					
13.3.11.	District N	sed SRA Project at plot bearing C.T.S No. 720, 723,728 Village Kandivali, t Mumbai, Maharashtra by M/s Triax Developers LLP – Environmental nce – [F.No.21-93/2016-IA-III] [IA/MH/NCP/61384/2016]					
	No. 720, reserved fo total plot a is24554.29 proposed t	Developers LLP has proposed for development of SRA Project at plot bearing C.T.S 723,728 Village Kandivali, District Mumbai, Maharashtra. The land is entirely for rehabilitation & resettlement and is partly reserved for garden reservation. The area is 10296.80 sqm, FSI area (including fungible is36990.21 sqm, Non FSI Area 9 sqm and the total construction area will be 61544.5 sqm. Total nos. of flats to be developed are 493 for Rehab, 328 for Sale and 12 nos for Sale shops. The height of the buildings will be 69.90 m. The Project components is as under:-					
		Wings	Configuration	Height			
		Rehab Wing A	Gr/Stilt (parking) + 23 floors	69.90 m			
		Rehab Wing B	Gr/Stilt + 7 floors	24.50 m			
		Rehab Wing C	Gr/Stilt + 23 floors	69.90 m			
		Sale	Basement + Stilt (pit parking) +1 Parking Podiums & Amenities + 21 Residential Floors	69.95			
	due south I	of the project is Rs.160 Crores.It is reported that Sanjay Gandhi national park ( 3.78 km buth East).The project falls outside the eco sensitive zone of Sanjay Gandhi national park lized on 05.12.2016 vide S.O. 3645 by MoEFCC.					
	Greater Mu STP having 194 KLD ( water will b water. Tem will be 124 will be use handed ov manageme sourced by	mbai (MCGM), wate g capacity of 500 Kl Flushing water requ e discharged to mur porary sanitary toile 8 Kg/Day which will ed for landscaping. ver to recyclers/ver nt is 120 m ² . Durin Reliance.Quantity of	8 KLD which will be sourced through er NOC awaited. The waste water quan LD in an area of 350 sqm is proposed irement: 190 KLD and R.G water req nicipal drains. Septic tanks will be provided ts will be provided during peak labor fo be treated in (organic waste converte Non-biodegradable waste will be 85 ndors. PP informed that area earn of construction phase 100 KVA will be of Rain Water will be 83 cum. and cap	tity will be 470 KLD. The I. Recycled water will be uired: 4 KLD). 229 KLD ded for disposal of waste rce.Biodegradable waste er)OWC and the manure 8 Kg/Day which will be narked for solid waste e required which will be bacity of RWH Tanks for			
	fixtures, so	lar energy and ener	e 166 cum.Energy will be conserved gy efficient equipment.Total RG area c availing DCR requirements. <b>Parking fa</b>	on ground is 792.07 sqm			

	Wheelers and 50 nos of 2 Wheelers will be provided. The Committee suggested them to explore the feasibility for providing 4 wheelers parking to each flat.
	After detailed deliberation, the Committee sought following additional information:
	<ul> <li>(i) Landuse of the propose project site.</li> <li>(ii) Copy of the approval of proposed project from the concerned Government Agency/Authority. Copy of approved Sanction plan. Approval of the project from High Rise Building Committee of Maharashtra.</li> <li>(iii) Give a conformity status to conditions stipulated in Annexure XIV of the amended EIA notification of 09-12-2016.</li> <li>(iv) Status project proposal in the SEIAA, Maharashtra.</li> <li>(v) Explore the feasibility for providing 4 wheelers parking to each flat owner.</li> <li>(vi) Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.</li> <li>(vii) Layout of parking plan indicating entry and exit points of vehicular movement as well as traffic management plan. Highlight the fire tender pathway.</li> <li>(viii) Revised water balance to be submitted.</li> <li>(x) Excess treated sewage disposal plan/scheme to be submitted.</li> <li>(x) Prediction of ground level concentration of emissions from stack due to DG sets.</li> <li>(xii) At least 2 solar powered lights and one fan shall be provided in each flat. Solar generation shall be connected to the grid.</li> <li>(xiii) Action plan for management of Construction and Demolition Waste to be generated from demolition of the existing building structures as per the latest rules/guidelines.</li> <li>(xiv) Details energy conservation measures to be taken. taken (all points mentioned in the proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported through drawings and</li> </ul>
	<ul> <li>(xv) Increase the greenbelt area. Layout plan indicating Greenbelt alongwith area earmarked to be provided.</li> </ul>
	The proposal was deferred till the desired information is submitted. The above information shall be provided with the uploading of minutes on the website.
13.3.12.	Expansion of Residential, Retail, IT & Commercial project on plot bearing CTS. Nos. 117A, 117A/1, 117B &117 C Village Tungwa, Saki Vihar Road, Powai, Mumbai by M/s. Larsen & Toubro Realty Ltd. – Environmental Clearance reg. [IA/MH/NCP/61506/2017] [F.No.21-104/2016-IA-III]
	<ul> <li>(i) The project involves expansion of Residential, Retail, IT&amp; Commercial project on plot bearing CTS. Nos. 117A, 117A/1, 117B &amp;117 C Village Tungwa, Saki Vihar Road, Powai, Mumbai (Maharashtra) promoted by M/s. Larsen &amp; Toubro Realty Ltd admeasuring 1,44,403.10 sqm as per Earlier Environmental Clearance dated 6th</li> </ul>
	<ul> <li>September, 2014.</li> <li>(ii) The project have Environmental Clearance for a construction area of 3,52,747.77sqm to construct 8 nos of Residential buildings and 2 nos of IT building. In accordance with Environmental Clearance received, the work of 4 nos of buildings is completed and OC has been granted for TC-III and building-T1, T2, T3.The work of remaining 6 buildings is in progress.</li> </ul>
	<ul> <li>is in progress.</li> <li>(iii) On receipt of I to R dated 19th May, 2016 for the plot area of 46,060 sqm and inclusion of land portion of 2,276.40 sqm on the adjoining plot, the plot area has increased to 1.40 G70 50 sqm matching into increase in the constraint increased to</li> </ul>
	<ul> <li>1,46,679.50 sqm resulting into increase in the construction potential.</li> <li>(iv) It is now proposed to have the expansion i.e.; vertical expansion in the existing buildings and construction of additional 8 Residential building and one Health and</li> </ul>

Welfare center in the added R zone. All the internal roads are minimum 9 m wide for easy fire engine movement. The maximum height of the buildings is within the permissible height granted by the Aviation Authority.

- (v) The project received its Terms of Reference (ToR) during the 47th SEAC-2 meeting held on 3rd June 2016 at Mumbai, Maharashtra.
- (vi) Construction is done and environmental settings are already provided as per earlier EC. The natural drainage pattern is utilized for aligning the drainage services. The overall infrastructure shall be further enhanced because 45.75 m wide Jogeshwari-Vikroli link Road is on the East side of the plot and 27 m wide Saki Vihar Road is on the West side which is abutting the site. Infrastructural facility and connectivity is well established around the plot area, Central Railway Station (Kanjurmarg) 4.8 Km ChatrapatiShivaji International Airport 6.0 km (Aerial Distance), Saki naka metro station-1.5 kms. The project site is abutting Saki Vihar road and JVLR.
- (vii) The project is located at Latitude 72°53'36.10" E and Longitude 19°07'23.66"N.
- (viii) The total plot area is 1,46,679.50sqm. The project includes 16 Nos. of Residential Buildings, 2 Nos. of IT buildings and Health and Welfare Centre. The total Nos. of flats will be 1863. The FSI area is 2,91,090.21sqm, and the total construction area will be 5,85,921.16 sqm. The Maximum height of the buildings will be 96 m.
- (ix) Water requirement: Total expected water requirement will be 30 KLD which will be sourced through Tanker Water. Septic tank is provided during ongoing construction and same shall be continued for expansion. Total expected water demand is 1508 KLD, Recycled water is 535 KLD, Waste water generated is 1330 KLD, Capacity of STP is 1392 KLD and Zero treated water to municipal drain.
- (x) **Solid Waste Management:** Biodegradable waste will be 2743 kg/day Kg/day whichwill be treated in OWC and the manure will be used for landscaping at site and as replacement for saw dust in OWC. Non-biodegradable waste will be 2105 Kg/Day which will be handed over to authorized recyclers.
- (xi) **Power Requirement:** 300 KVA, total Connected Load: 45552 KW, total Demand Load: 22686 KW.
- (xii) **Rain Water Harvesting:** The quantity of RWH will be 1089 cum. Capacity of RWH Tanks proposed to be provided, will be 454 cum.
- (xiii) **Parking Facility:** According to local norms 3847 Nos for 4 wheelers required and parking proposed to be provided for 4019 Nos.
- (xiv) Energy saving measures: 18% of power saving.
- (xv) If located/ not located within 10 km eco sensitive area: No.
- (xvi) Investment/Cost of the project: Rs. 750.00 Crores.
- (xvii) **Employment Potential:** Total labor required: 695 nos and during construction phase: 100 nos.

The Committee noted that EIA report was submitted to SEIAA/SEAC, Maharashtra and SEAC appraised the EIA report. Further, SEAC deferred the proposal for want of addl. Information. It is reported that "proposed incentive FSI of 3 for IT Industry is not approved by MCGM yet. Plans submitted are only for FSI1. Further plans should be in consonance with permission given by Industry Department". However, PP has not submitted the EIA report on the MoEFCC's website.

In view of the above, the Committee recommended that :

- 1. Submit copy of the EIA report on the web portal of environmental clearance.
- 2. Point wise reply to the queries raised by SEAC, Maharashtra.
- 3. Copy of certified compliance report issued by the Regional Office of MoEF&CC on the environmental conditions stipulated in the existing environmental clearance.

The proposal was deferred till the desired information is submitted. The above information shall be provided with the uploading of minutes on the website.

13.3.13. Proposed Expansion of Residential and Commercial Project "Oxford City" at village

#### Lavale, Tehsil- Mulshi, District Pune, Maharashtra by M/s Knowledge City Education Pvt. Ltd. and M/s. Oxford Golf & Resorts Pvt. Ltd - TOR Regarding -[IA/MH/NCP/61545/2017][F.No.21-105/2016-IA-III]

M/s Knowledge City Education Pvt. Ltd. and M/s. Oxford Golf & Resorts Pvt. Ltd has proposed forexpansion of Residential and Commercial Project "Oxford City" at Gut No. at village Lavale: 1167, 1168, 1169, 1170, 1171, 1172, 1176, 1176, 1178, 1181/1, 1181, 1183, 1183/1, 1184, 1185, 1191, 1194, 1196, 1198/3, 1200, 1201, 1202, 1203, 1204, 1206, 1207, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1218, 1219, 1220, 1221, 1222, 1223, 1224, 1225, 1226, 1227, 1228, 1229, 1230, 1231, 1232, 1241, 1243, 1245, 1246, 1247, 1253, 1259, 1261, 1263, 1264, 1265, 1266/2, 1269/2, 1283, 1284, 1289, 1656, 1657, 1658, 1659, 1660 & Gut No. at village Bavdhan: 23, 34/1, 34/2/1, 34/4b/1, 129/1, 131, 132, 135, 137/1, 137/2, 137/3, 159, 163, 168, 199, 200/3 in Tehsil- Mulshi of District Pune, Maharashtra.

Sr.	Latitude	Longitude	Sr.	Latitude	Longitude
No.		-	No.		_
А	18°31'26.56"N	73°44'47.79"E	F	18°31'32.35"N	73°43'35.07"E
В	18°31'55.06"N	73°44'27.93"E	G	18°30'25.34"N	73°43'21.19"E
С	18°31'49.04"N	73°44'24.23"E	Н	18°30'33.08"N	73°43'32.85"E
D	18°31'50.10"N	73°43'50.32"E		18°30'52.10"N	73°43'58.99"E
Е	18°31'43.40"N	73°43'29.00"E	J	18°31'13.54"N	73°44'19.66"E

## (i) Location on Google map/ survey map:

PP informed that as per the Environmental Clearance dated 27-02-2007, 10 nos. of villas, 18 nos. of building (for 186 tenements) and 32 nos. of IT buildings are existed. As per the Environmental Clearance dated 17-10-2006, 446 residential villas, hotel commercial building, university area are existed.

The present expansion will consists of 290 buildings consisting residential, commercial, amenity, educational institutes and hospital, utility. It will includes Residential 108445, Commercial 131629, Hospital 200 (bed), Educational Institute: 9960 Floating Population: 25000. Total 275434 Nos. will be provided. Cost of the project is Rs.14,840 Crores (approx.).

The proposed project site is earmarked for Residential& Commercial use as per the local development plans and the proposed project is planned and designed as per the regulations and procedures laid down by the Local Authority (Pune Metropolitan Development Corporation). The total plot area is 38,57,154.00 Sq. m and the total Built up area will be 54,24,423.30 Sq. m.

Total water requirement will be 17265 KLD which will be sourced through Irrigation Department Pune & Treated waste water.Waste water generation will be 12817 KLD. Adequate capacity of STP's are proposed in various location and phases. 12176 KLD of treated waste water will be available for reuse. For flushing, 5268 KLD and for horticulture, 2561 KLD. Excess treated sewage will be disposed to proposed sewer line of NIT.Segregation of non-biodegradable and biodegradable garbage on site. Bio degradable garbage will be treated in OWC (Organic Waste Convertor). Non-biodegradable garbage will be segregated into recyclable and non-recyclable waste and shall be handed over to PMC. STP Sludge (Dry sludge) will be used as manure.Power requirement will be 57 MVA which will be sourced through MSEDCL/MSETCL.RWH Scheme will be provided.**Parking facility** for 27572 Nos. of 4 wheelers will be provided.

After detailed deliberations on the proposal, the Committee recommended for grant of Terms of Reference as specified by the Ministry as Standard ToR in April, 2015 for the said

	<i>project/activity</i> report:	and the following TOR in addition to Standard ToR for preparation of EIA-EMP
		Certified compliance report issued by the Regional Office, Nagpur for environmental conditions stipulated in the existing EC.
	ii.	Importance and benefits of the project.
	iii.	Present landuse of the proposed project site.
	iv.	Copy of building sanction plan as well as approval of high rise building committee of Maharashtra.
		Details of no. of floor alongwith builtup area to be constructed in each block to be furnished.
		Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.
		Layout of parking plan indicating entry and exit points of vehicular movement as well as traffic management plan. Highlight the fire tender pathway.
		Details energy conservation measures to be taken. taken (all points mentioned in the proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported through drawings and details in the proposal.
		Details of source of water supply alongwith permission to be submitted.
		Treatment scheme for sewage and its recycling mode. Excess treated sewage disposal plan/scheme to be submitted.
		Prediction of ground level concentration from the stack of DG sets
		Efforts shall be made to reduce capacity of DG set and remaining standby power shall be met from solar energy.
	xiii.	Action plan to comply with the noise pollution norms with respect to various zones.
	xiv.	A management plan for excavation and dewatering to ensure compliance to the CGWA guidelines and regulation.
		Action plan to manage hospital wastes (liquid as well as solid) as per Bio- medical Waste Management Rules.
		Municipal solid waste management plan alongwith area earmarked for solid waste management scheme.
	xviii.	Layout plan indicating Greenbelt alongwith area earmarked to be provided. Give a conformity status to conditions stipulated in Annexure XIV of the amended EIA notification of 09-12-2016. Copy of Form1A also to be submitted.
	2) should be c addition to all	nended that 'TORs' prescribed by the Expert Appraisal Committee (Infrastrucure- onsidered for preparation of EIA / EMP report for the above mentioned project in the relevant information as per the 'Generic Structure of EIA' given in Appendix the EIA Notification, 2006.
13.3.14.	No. 88, 90, 9 122, 123, 1	Ind Amendment in Residential and Commercial Development at Gat 1, 92, 93, 94, 95, 96, 97, 113/2, 124, 125, 126, 127, 128/1, 128/2, 128/3, 26(P) Village- MhalungeKhed Dist. Pune, Maharashtraby M/s Housing Development Pvt. Ltd - TOR – [F.No.21-79/2016-IA-III] 60326/2016]
	Residential an 124, 125, 126 Maharashtra. 2009/CR.15/T0	e Housing Development Pvt. Ltd has proposed for expansion and amendment in d Commercial Development at Gat No. 88, 90, 91, 92, 93, 94, 95, 96, 97, 113/2, 127, 128/1, 128/2, 128/3, 122, 123, 126(P) Village- MhalungeKhed Dist. Pune, Environmental Clearance was issued to the project vide letter No.SEAC-C.2 dated 19 th May, 2010 for construction area of 2,60,372.47 m ² . The total rea completed as per earlier EC dated 19 th May, 2010 is 1,18,088.22 m ² . The under:

CO	mpleted & Under Constr	ruction as per earlier	r EC
Sectors	No. of Bldgs.	Bldg. configuration	No. of Flats
Sector 2A			
	37	P+6, P+12	1200
	Club House 1		
Sector 3A	65	P+8,G+1	189
	Club House 1		
Sector 1A	13	P+4,G+3	496
Sector 1B	5	P+8	384
	Club House 1		
	School-1		
TOTAL	120		2269
Prop	osed Construction: for	expansion & Amend	lment
Sectors	No. of Bldgs.	Bldg. configuration	No. of Flats
Sector 1C	6	P + 12	852
Phase 1	20 shops		
	1 Club House		
Sector 1C	6	P + 12, P+11	810
Phase 2	36 shops		
Sector 3	6	P + 12	564
Phase 1	30 shops		
	1 Club House		
Sector 3	7	P + 12	672
Phase 2	Hotel	P+7	
	Comm. & retails	P+2	
	Shopping Mall, shops	P+7	
	School	G + 6	
	Sports Complex	G + 1	
	Hospital	G + 5	
	Hostel	G + 4	
	1100(01	_	

The total plot area is  $2,47,700m^2$ . The project will comprise of total 145 buildings. FSI area is  $2,94,811.12m^2$  and total construction area of  $5,28,121.58m^2$ . Total No. of flats 5167 nos., Hotel, Commercial & Retail, Shopping Mall, School, Sports Complex, Hospital and Hostel shall be developed. Maximum height of the building is will be 37.5m. **Cost** of the project is Rs.715.15 Cr

During construction phase, total water requirement is expected to be 10-20 KLD which will be met by tanker. During the construction phase, soak pits and septic tanks will be provided for disposal of wastewater. Temporary sanitary toilets will be provided during peak labour force.During operational phase, total water demand of the residential project is expected to be 4025 KLD and for Hospital 37 KLD is required o ut of the total 2526 will be met through Maharashtra Jeevan Pradhikaran (MJP) Waste water generated from residential project (3841 KLD) will be treated in 9 Nos. of STPs of total 3450 KLD capacity. (Existing 3 Nos.- 1800 m³/day, 255 m³/day, 225 m³/day.- MBBR Technology and for proposed 6 nos. of STP - 450 m³/day, 430 m³/day, 60 m³/day, 70 m³/day, 40 m³/day, 120 m³/day - Phytorid Technology) 3380 KLD of treated waste water will be recycled (1300 for flushing, 224 for gardening). About 1856 KLD will be stored in a pond of 10 days capacity further it will be discharged to the natural Nallamentioning BOD

level less than 30 as per CPCB guidelines.For Hospital waste water, ETP will be provided, treated waste water in ETP will be connected to STP for recycle. About12.9 TPD solid waste will be generated in the project. The biodegradable waste (7.7TPD) will be processed in OW C and the non-biodegradable waste generated (5.2 TPD) will be handed over to PCMC.The total power requirement during construction phase is about 100 KW and will be met from Maharashtra State Electricity Distribution Company Limited (MSEDCL) and total power requirement during operation phase is will be met by MSEDCL Supply. D.G. Sets will be used in case of Power Failure only for emergency services.

Details	Existing Buildings	Proposed buildings	Total Load	
Connected Load	6700	7358	14058 KW	
Maximum Demand	5025	5518.5	10544 KW	
D.G. Set		200 KVA - 3 nos.,160 KVA- 4 nos., 500 KVA - 2nos. 82.5 KVA- 1no., 62.5 KVA- 1no.	11 os.	

Roof top rain water of buildings will be recharged through 50 nos. of recharge pit having size 2mt. x 0.9mt x 2mt for harvesting after filtration. RWH tank not planned.Parking facility for (1408 Existing + 1471 Proposed) four wheelers and Existing 2329 + Proposed 4165 two wheelers, is proposed to be provided against the requirement of (259 Existing + 365 Proposed) cars and Existing 1843 + Proposed 3964 two wheelers two wheeler respectively (according to local norms).

Component	Parking Required as per DCR (Nos.)	Parking Spaces provision (Nos.)
4 Wheeler	624	2879
2 Wheeler	5807	6494

Proposed energy saving measures would save about 7% of power. It is reported that the project is not located within 10 km of any Eco-Sensitive areas.

- i. Certified compliance report issued by the Regional Office, Nagpur for environmental conditions stipulated in the existing EC.
- ii. Importance and benefits of the project.
- iii. Present landuse of the proposed project site.
- iv. Copy of building sanction plan as well as approval of high rise building committee of Maharashtra.
- v. Details of no. of floor alongwith builtup area to be constructed in each block to be furnished.
- vi. Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.
- vii. Layout of parking plan indicating entry and exit points of vehicular movement as well as traffic management plan. Highlight the fire tender pathway.

	<ul> <li>viii. Details energy conservation measures to be taken. taken (all points mentioned in the proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported through drawings and details in the proposal.</li> <li>ix. Details of source of water supply alongwith permission to be submitted.</li> <li>x. Treatment scheme for sewage and its recycling mode. Excess treated sewage disposal plan/scheme to be submitted.</li> <li>xi. Prediction of ground level concentration from the stack of DG sets</li> <li>xii. Efforts shall be made to reduce capacity of DG set and remaining standby power shall be met from solar energy.</li> <li>xiii. Action plan to comply with the noise pollution norms with respect to various zones.</li> <li>xv. A management plan for excavation and dewatering to ensure compliance to the CGWA guidelines and regulation.</li> <li>xv. Action plan to manage hospital wastes (liquid as well as solid) as per Biomedical Waste Management Rules.</li> <li>xvii. Layout plan indicating Greenbelt alongwith area earmarked for solid waste management scheme.</li> <li>xviii. Layout plan indicating Greenbelt alongwith area earmarked to be provided.</li> <li>xviii. Give a conformity status to conditions stipulated in Annexure XIV of the amended EIA notification of 09-12-2016. Copy of Form1A also to be submitted.</li> </ul>
13.3.15.	Expansion of Mixed Use Project at CTS no. 86, 87 of village Paspoli and CTS no. 112, 115 of village Tungwa Saki Vihar Road, Powai, Kurla, Mumbai, Maharashtra by M/s Larsen & Toubro Ltd - TOR - [IA/MH/NCP/60986/2016][F.No.21-80/2016-IA- III]
	M/s Larsen & Toubro Ltd has proposed for Expansion of Mixed Use Project at CTS no. 86, 87 of village Paspoli and CTS no. 112, 115 of village Tungwa Saki Vihar Road, Powai, Kurla, Mumbai, Maharashtra. The project was granted Environmental Clearance from SEIAA, Maharashtra vide their letter No. SEAC-2014/CR-151/C-I dated 28.01.2016 for total construction area of 1,49,618.70sqm. No construction is been started on site. Only site clearance work has been started as per previous EC dated 28.01.2016. The total plot area is2, 36,919.00 sqm. 1002 Nos. of flats will be constructed (For Expansion). Total Nos. of Buildings will be 11. Maximum height of the buildings will be 102.4 m. <b>Cost of the project is</b> Rs. 1700 Cr .The project includes:
	<ul> <li>Wing A – 3rd B + 2 levels of Part B/Part P + stilt/Gr+1 to 18th Floors – Considered in previous EC dated 28th January, 2016</li> <li>Wing B – 3rd B + 2 levels of Part B/Part P + stilt/Gr+1st to 2nd Floor - Considered in previous EC dated 28th January, 2016</li> <li>Wing C – 3rd B + 2 levels of Part B/Part P + stilt/Gr+1 to 18th Floors - Considered in previous EC dated 28th January,2016</li> </ul>
	In the present expansion, following is proposed:
	Commercial Towers: (a) IT Tower 1 with 3 basement + Ground + 18 floors, (b) IT Tower 2 with 3 basement + Ground + 6 floor +7 th Pt floor and (c) 1 Retail Building with 3 Basements + Ground + 4 floors

Residential Towers:

- (a) T1 to T6 2 Basement + Ground + 1 podium + Stilt + 30 floor
- (b) School G + 6 Floors

(i) FSI area is as follows:

FSI area for previous EC	93,381.64 Sqm.
FSI area for Expansion	3,54,964.79 Sqm.
Total FSI area	4,48,346.43 Sqm.

(ii) Total construction area is as follows:

Construction area for previous EC	1,49,618.70 Sqm.
Construction area for	4,87,735.65 Sqm.
Expansion	
Total Construction area	6,37,354.35 Sqm.

It is reported that Powai lake (0.5 km), Vihar lake (1,40 km) and Chandivali Lake (0.52 km) are situated from the project site. Sanjay Gandhi National Park is located within 15 km from the project site.

The total expected water requirement during construction phase will be 30 KLD which will be sourced through Tanker. Septic tank shall be provided during construction. The total expected water demand during operational phase will be 1190 KLD, Recycled water: 974 KLD, Waste water generated: 1082 KLD, Total 6 Nos of STP considered for expansion having total capacity of 1218 KLD. Zero KLD treated water to municipal drain.

**Solid Waste Management (For Expansion):** Biodegradable waste: 4572 Kg/day which will be treated in OWC and the manure will be used for landscaping at site and as replacement for saw dust in OWC. Non-biodegradable waste: 3094 Kg/Day which will be handed over to authorized recyclers.

**Power Requirement:** During construction phase approximately 300 KVA power will be required and During operation phase total connected load will be 35129 KW & total demand load will be 14633 KW.

**Parking Details: Parking facility for** 997 cars in IT and Retail & 1804 Nos. cars for Residential and 361 Nos for two wheelers will be provided.

- i. Certified compliance report issued by the Regional Office, Nagpur for environmental conditions stipulated in the existing EC.
- ii. Importance and benefits of the project.
- iii. Present landuse of the proposed project site.
- iv. Copy of building sanction plan as well as approval of high rise building committee of Maharashtra.
- v. Details of no. of floor alongwith builtup area to be constructed in each block to be furnished.
- vi. Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste

		•	a, rain water harv	esting structure, e	tc. in different c	olour to be			
	vii.			g entry and exit poin		ovement as			
	viii.		•	. Highlight the fire t asures to be taken	• •	mentioned			
	viii.	in the propo	sal such as orier	ntation to support	reduced heat g	ain, use of			
			ings and details in	compliant envelope	e measures to be	e supported			
	ix.	•	•	/ alongwith permiss	ion to be submitte	ed.			
	Х.	Treatment sc		and its recycling m					
	xi.			aterbodies from wa	ater pollution of th	e proposed			
	xii.	• •	around level conce	ntration from the st	ack of DG sets				
	xiii.		-	ce capacity of DG		ng standby			
	xiv.	•	e met from solar ei	nergy. noise pollution no	orms with respect	to various			
		zones.	o comply with the						
	XV.		nt plan for excavat lines and regulation	ion and dewatering n.	to ensure compl	iance to the			
	xvi.	Municipal so	•	ment plan alongwi	th area earmarke	ed for solid			
	xvii.	•		alongwith area ear	marked to be prov	vided.			
	xviii.	Give a conf	ormity status to o	conditions stipulate	ed in Annexure	XIV of the			
		amended EIA	notification of 09-	12-2016. Copy of F	orm1A also to be	submitted.			
	It was recor	mmended that 'T	ORs' prescribed by	/ the Expert Apprai	sal Committee (In	frastrucure-			
				/ EMP report for th					
		ddition to all the relevant information as per the 'Generic Structure of EIA' given in Appendix							
	III and IIIA i	A in the EIA Notification, 2006.							
13.3.16.	Fynansion	and amend	ment of mixed	used developm	ent at Tal Mu	lshi Dist			
10.0.10.	Pune, Ma	harashtra by	M/s. Goel Ga	nga Developers		- TOR -			
	[IA/MH/NC	P/61008/2016]	[F.No.21-81/201	6-IA-III]					
	M/s. Goel	Ganga Develor	oers (I) Pvt Itd.	has proposed for	expansion and	change of			
				Village Bavdhan, T					
				been granted by S					
			29 [™] September, 2	2014 for the exis	ting project. Sta	atus of the			
	construction	n is as follows:							
		BUILDING NAME	REVISED	STATUS OF	TOTAL AREA				
		AS PER EC	NOMENCLATURE	CONSTRUCTION	CONSTRUCTED				
			10						
		A3	A3	1st slab RCC work in progress	31,449.57				
		A4	A4	Finishing work upto					
				11th floor					
		B1	B1	Finishing work up to					
				11h floor					
		B2	B2	2nd slab work in					
				progress					

B3	B3	1st slab work in progress	
B4	B4	Foundation work in progress	
B5	B8	Foundation work in progress	
B6	B9	Foundation work in progress	
C1	B5	Work to be started	
C2	DELETED	-	
D1	B6	Work to be started	
D2	B7	Work to be started	
D3	CLUB HOUSE 2	Work to be started	

(i) The details of the project is as under:

S. No.	Buildings as per Existing EC	No. of Floors as per Existing EC	Height of building (Mt) as per Existing EC	Tenements as per Existing EC	Proposed buildings	Proposed No. of Floors	Proposed Height of building (Mt)	Proposed Tenements
1	-	-	-		A1	B+B+P+23	69	134
2	-	-	-		A2	B+B+P+23	69	176
3	A3	2B+S+11	35.90	74	A3	B+B+P+23	69	176
4	A4	2B+S+11	35.90	74	A4	B+B+P+23	69	176
5	B1	2B+S+11	35.90	74	B1	B+B+P+23	69	182
6	B2	2B+S+11	35.90	74	B2	B+B+P+23	69	180
7	B3	2B+S+11	35.90	74	B3	B+B+P+23	69	180
8	B4	2B+S+11	35.90	74	B4	B+B+P+23	69	180
9	B5	2B+S+11	35.90	74	B8	B+B+P+23	69	184
10	B6	2B+S+11	35.90	74	B9	B+B+P+23	69	184
11	C1	2B+S+11	35.90	74	B5	B+B+P+23	69	180
12	C2	2B+S+11	35.90	74				

			Total	954				2476
17					B10	B+B+P+23	69	184
-	CLUB HOUSE	G+1	-	-	CLUB HOUSE	G+1	-	-
15 I	D3	2B+S+11	35.90	74	CLUB HOUSE 2	2B+G+2	-	-
14 I	D2	2B+S+11	35.90	74	B7	B+B+P+23	69	180
13 I	D1	2B+S+11	35.90	74	B6	B+B+P+23	69	180

The total plot area is 1,12,179.0  $m^2$ . proposed 14 Residential buildings having B+B+P+23 floors and 2476 nos of flats and two no. of club house having 2B+G+2 and G+1 floors respectively. **Cost** of the project is Rs.620 Crore.

It is reported that water bodies namely Ram River (Within 500 mt of project site), Indrayani river(16 Km), Mula river (4.52 Km), Mula- Mutha (8.87 Km), Pashan lake (Approx.-1.0 Km), Manas lake-Approx.-5.0 Km Katraj lake-Approx.-11.55 Km Vishrantwadi lake-Approx.-12.30 Km Model colony lake-Approx.-7.0 Km Jambhulwadi lake-Approx.-11.45 Km Lohegaon lake-Approx.14.75 Km Khadakwasla dam-Approx.-9.0 Km Upper Lake-Approx.-11.70 Km Peshva Lake-Approx.-8.25 Km Bhugaon lake-Approx.-3.50 Km Bird Valley Lake-Approx.-14.80 Km Urwade lake-Approx.-12.60 Km are located within 15 km distance.

During construction phase, total water requirement is expected to be 53 KLD which will be met by tanker. During the construction phase Temporary sanitary toilets will be provided with septic tank and soak pits during peak labour force.During operational phase, total water demand of the project is expected to be 2039 KLD and out of the total 1154 KLD for Domestic purpose will be met by GrampanchayatBavdhan, 19 KLD for Swimming Pool will be met by potable guality water tankers and the rest 867 KLD will be met by recycled water. Waste water generated (1560 KLD) uses will be treated in one STP of total 1720 KLD capacity. 867 KLD of treated waste water will be recycled (557 for flushing. 310 for gardening).About 537KLD will be disposed into Grampanchayat drain. About 5.5 TPD solid waste will be generated in the project. The biodegradable waste (3.34 TPD) will be processed in OWC and the non-biodegradable waste generated (2.22TPD) will be handed over to PMC. The total power requirement during construction phase is about 100KW and will be met from Maharashtra State Electricity Distribution Company Limited (MSEDCL)and total power requirement during operation phase is 6016.00KW will be met by MSEDCL Supply.RWH: Roof top rain water of buildings will be recharged through 16no. of recharge pit having size 1mt. x 1mt x 1.5mt for harvesting after filtration. RWH tank not planned. Parking facility for (1155 Proposed) four wheelers and 2875 two wheelers is proposed to be provided against the requirement of (974 nos.) cars and 2488 nos. two wheelers two wheeler respectively (according to local norms). Proposed energy saving measures would save about 39.97 % of power.

	i.	Certified compliance report issued by the Regional Office, Nagpur for environmental conditions stipulated in the existing EC.
	ii.	Importance and benefits of the project.
	iii.	Present landuse of the proposed project site.
	iv.	Copy of building sanction plan as well as approval of high rise building committee of Maharashtra.
	V.	Details of no. of floor alongwith builtup area to be constructed in each block to be furnished.
	vi.	Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.
	vii.	Layout of parking plan indicating entry and exit points of vehicular movement as well as traffic management plan. Highlight the fire tender pathway.
	viii.	Details energy conservation measures to be taken. taken (all points mentioned in the proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported
	ix.	through drawings and details in the proposal. Details of source of water supply alongwith permission to be submitted.
	X.	Treatment scheme for sewage and its recycling mode. Excess treated sewage
		disposal plan/scheme to be submitted.
	xi.	Action plan to prevent nearby waterbodies from water pollution apprehended due to the proposed project.
	xii.	Prediction of ground level concentration from the stack of DG sets
	xiii.	Efforts shall be made to reduce capacity of DG set and remaining standby power shall be met from solar energy.
	xiv.	Action plan to comply with the noise pollution norms with respect to various zones.
	XV.	A management plan for excavation and dewatering to ensure compliance to the CGWA guidelines and regulation.
	xvi.	Municipal solid waste management plan alongwith area earmarked for solid waste management scheme.
	xvii.	Layout plan indicating greenbelt alongwith area earmarked to be provided.
	xviii.	Give a conformity status to conditions stipulated in Annexure XIV of the amended EIA notification of 09-12-2016. Copy of Form1A also to be submitted.
	2) should be addition to al	mended that 'TORs' prescribed by the Expert Appraisal Committee (Infrastrucure- considered for preparation of EIA / EMP report for the above mentioned project in I the relevant information as per the 'Generic Structure of EIA' given in Appendix the EIA Notification, 2006.
13.3.17.		nt of Residential Apartment project "Prestige Jindal City" at Sy. Nos.
		2, 31/1, 31/2, 32/1, 32/2, 36/1, Chikkabidarakallu Village,
		aHobli, Nelamangala Taluk (Presently Bengaluru North Taluk),
		Karnataka by M/s. Prestige South City Holdings – TOR /61241/2016][F.No.21-82/2016-IA-III]
	project "Pres Chikkabidara Taluk), Beng 77"29'18.86" Buildings. FS 3,498 Nos. fla	South City Holdings has proposed for development of Residential Apartment stige Jindal City" at Sy. Nos. 28/4, 29/2, 31/1, 31/2, 32/1, 32/2, 36/1, kallu Village, DasanapuraHobli, Nelamangala Taluk (Presently Bengaluru North galuru, Karnataka. The project is located at 13"03'12.74" N Latitude and E Longitude. The total plot area is 1,35,063.82sqm. The project will comprise of 5 at area is 3, 96,953.30 sqm and total construction area of 5, 81,436.56 sqm. Total ats shall be developed. Maximum height of the building is 95.0 m. The cost of the 590.03 Crores.
	77"29'18.86" Buildings. FS 3,498 Nos. fla	E Longitude. The total plot area is 1,35,063.82sqm. The project will comprise of I area is 3, 96,953.30 sqm and total construction area of 5, 81,436.56 sqm. Tot ats shall be developed. Maximum height of the building is 95.0 m. The cost of th

It is reported that water bodies namely Anchepalya Lake (600 m) and Doddabidarakallu Lake (900 m) are located from the project site. With reference to theproject site, there is an existing natural tertiary drain passing through the site from south of south west to east of south east direction where for the same a 25m buffer has been provided from the edge of the drain as per the NGT order No. OA 222/2014 dated 04.05.2016 and the same will be retained without doing any diversion. And also there is a kharab land which is termed as Nalakharab in the site hence a buffer of 25m has been provided from the edge of the kharab land as per the NGT order No. OA 222/2016. It is not located within 10 km of any Eco Sensitive areas.

During construction phase, total water requirement is expected to be 176.5 KLD which will be met by External tanker water supplier. During the construction phase, soak pits and septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided during peak labor force. During operational phase, total water demand of the project is expected to be 2,907 KLD and the same will be met by the Bengaluru Water Supply and Sewerage Board (BWS&SB). Wastewater generation will be 2,326 KLD and treated in 810 KLD, 490 KLD, 905 KLD & 130 KLD STPs of total 2,335 KLD capacity. 1,237 KLD of treated wastewater will be recycled (982 KLD for flushing, 255 KLD for gardening). About 856 KLD will be disposed in to municipal drain. About 9.6 TPD solid wastes will be generated in the project. The biodegradable waste (5.4 TPD) will be processed in OWC and the non-biodegradable waste generated (4.2 TPD) will be handed over to authorized local vendor. Power requirement: The total power requirement during construction phase is 250 kVA and will be met from Bengaluru Electricity Supply Company Ltd. (BESCOM) and total power requirement during operation phase is 24,265 kVA and will be met from Bengaluru Electricity supply company Ltd. (BESCOM). RWH: Rooftop rainwater of buildings will be collected in 115 Cum, 60 Cum. 100 Cum & 50 Cum RWH tanks of total 325 KLD capacity for harvesting after filtration. Parking Facility: Parking facility for 3,780 Nos. four wheelers and Zero two wheelers is proposed to be provided against the requirement of 3,777 Nos. and Zero respectively (according to local norms). Proposed energy saving measures would save about 28.5% of power. There will be 350 nos. of tree cutting in the project site. The Committee also suggested them to relocate the entry and exit gate of the proposed project site in order to avoid traffic congestion on the main road.

- i. Compliance of NGT order dated 04.05.2016 in the matter of OA 222/2014 regarding existing natural tertiary drain passing through the project site.
- ii. Importance and benefits of the project.
- iii. Present landuse of the proposed project site.
- iv. Copy of building sanction plan as well as approval of high rise building committee of Maharashtra.
- v. Details of no. of floor alongwith builtup area to be constructed in each block to be furnished.
- vi. Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.
- vii. Layout of parking plan indicating entry and exit points of vehicular movement as well as traffic management plan. Highlight the fire tender pathway. Relocate the entry and exit gate of the proposed project site in order to avoid traffic congestion on the main road.
- viii. Details energy conservation measures to be taken. taken (all points mentioned in the proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported through drawings and details in the proposal.

	<ul> <li>ix. Details of source of water supply alongwith permission to be submitted.</li> <li>x. Treatment scheme for sewage and its recycling mode. Excess treated sewage</li> </ul>
	<ul><li>disposal plan/scheme to be submitted.</li><li>xi. Action plan to prevent nearby waterbodies from water pollution apprehended due to the proposed project.</li></ul>
	<b>xii.</b> Prediction of ground level concentration from the stack of DG sets
	xiii. Efforts shall be made to reduce capacity of DG set and remaining standby
	power shall be met from solar energy.
	xiv. Action plan to comply with the noise pollution norms with respect to various
	zones.
	xv. A management plan for excavation and dewatering to ensure compliance to the CGWA guidelines and regulation.
	xvi. Municipal solid waste management plan alongwith area earmarked for solid waste management scheme.
	xvii. Layout plan indicating greenbelt alongwith area earmarked to be provided.
	xviii. Give a conformity status to conditions stipulated in Annexure XIV of the amended EIA notification of 09-12-2016. Copy of Form1A also to be submitted.
	It was recommended that 'TORs' prescribed by the Expert Appraisal Committee (Infrastrucure- 2) should be considered for preparation of EIA / EMP report for the above mentioned project in addition to all the relevant information as per the 'Generic Structure of EIA' given in Appendix III and IIIA in the EIA Notification, 2006.
13.3.18.	Development of IT Building at Plot No. D-108/1,T.T.C. Industrial area,Nerul, Navi Mumbai, District Thane, Maharashtra by M/s Vishwagreen Realtors Pvt. Ltd Environmental Clearance – [F.No.21-97/2016-IA-III][IA/MH/MIS/60854/2016]
	M/s Vishwagreen Realtors Pvt. Ltd. has proposed for development IT building at Plot No. D- 108/1,T.T.C. Industrial area,Nerul, Navi Mumbai, District Thane, Maharashtra. The project is located at 19°02'42.2"N Latitude and 73°01'42.6"E longitude.The total plot area is 3300.00 sqm. The project will comprise of Commercial 1 Building + Basement + Ground +First Floor (Part Parking) + second floor Parking + third floor Parking + fourth floor Parking + 29 Floors (Total Basement+ Ground+ 32 Floors). FSI area is 9743.801 sqm. and total construction area of 27620.106 sqm. Total 234 IT Units shall be developed. Maximum height of the building is 118.800 m. Cost of the project is Rs. 89 crore.
	During construction phase, total water requirement is expected to be 12 KLD for workers and 10-20 KLD for construction, which will be met by MIDC and water tankers. During the construction phase, soak pits and septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided during peak labour force.During operational phase, total water requirement will be 69 KLD. Out of which fresh water requirement from MIDC water supply will be 29 m3/day and remaining water requirement ( 40 m3/day) will be met from recycled/treated effluent. Wastewater generation will be 59 KLD and treated in the STP based Microfiltration technology. 40 KLD of treated wastewater will be recycled (37 KLD for flushing, 3KLD for gardening). About 13 KLD will be disposed in to municipal drain.
	<b>Solid Waste Management:</b> About 355.50 TPD solid wastes will be generated in the project. The biodegradable waste (142.20 TPD) will be processed in OWC and the non-biodegradable waste generated (213.30 TPD) will be handed over to authorized local vendor. E waste generation will be 2.3 MTPA. Committee suggested them to provide atleast 80 m ² area for management of solid waste.
	<b>Power requirement</b> : The total power requirement during construction phase is 100 KVA and will be met from MSEDCL and total power requirement during cooperation phase is 1452.73 KVA and will be met from MSEDCL. <b>RWH:</b> Rooftop rainwater of buildings will be collected in 1

RWH tank of total 15.00 KLD capacities for harvesting after filtration. **Parking facility** for 215 four wheelers are proposed to be provided against the requirement of 195 (According to local norms).Proposed energy saving measures would save about 27 % of power. Area earmarked for greenbelt is 450 m². DG set ( 500 KVA) will be installed.

After detailed deliberations, the Committee recommended the project for environmental clearance and stipulated the following specific conditions along with other environmental conditions while considering for accord of environmental clearance:

# I. Construction Phase

- (i) The Projects Proponents shall obtain all necessary clearance / permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.
- (ii) Construction site should be adequately barricaded before the construction begins.
- (iii) The building envelope for all air conditioned buildings / spaces shall be complied with the ECBC. Roofs and opaque walls should comply with the maximum assembly U factor or the minimum insulation R-value as well as lighting systems and equipment shall comply with the provisions of Energy conservation building Code.
- (iv) Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
- (v) Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
- Sewage shall be treated in the STP (with tertiary treatment i.e. Ultra Filtration). The treated effluent from STP shall be recycled/re-used for flushing, horticulture & DG cooling.
- (vii) As proposed, Rooftop rainwater of buildings will be collected in 1 RWH tank of total 30.00 KLD capacities for harvesting after filtration as per CGWB guidelines.
- (viii) Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 80 m² of area for the proposed building shall be provided for solid waste management within the premises which will include area for segregation, composting. The inert waste from project will be sent to dumping site of Municipality. E-waste shall be disposed through authorised E-waste processor.re-cyclers.
- (ix) Solar based electric power shall be provided to each unit for atleast two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.
- (x) A First Aid Room will be provided in the project both during construction and operations of the project.
- (xi) All the top soil excavated during construction activities should be stored for use in horticulture/ landscape development within the project site.
- (xii) Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.

	(xiii)	The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environmental (Protection) prescribed for air and noise emission standards.
	(xiv)	Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
	(xv)	As proposed, no ground water shall be used during construction / operation phase of the project.
	(xvi)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
	(xvii)	Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
	(xviii)	Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.
	(xix)	Ambient noise levels should conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
	(xx)	Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27 th August, 2003. Ready mixed concrete must be used in building construction.
	(xxi)	As proposed, no ground water shall be used during construction / operation phase of the project.
	(xxii)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
II	Oper	ation Phase
(	he to	ne gaseous emissions from DG set shall be dispersed through adequate stack eight as per CPCB standards. Acoustic enclosure shall be provided to the DG sets mitigate the noise pollution. Low sulphur diesel shall be used. The location of e DG sets may be decided with in consultation with State Pollution Control Board.
(	ii) Fi	resh water requirement from MIDC Water Supply shall not exceed 29m ³ /day.
(	m pr	ne quantity of fresh water usage, water recycling and rainwater harvesting shall be easured and recorded to monitor the water balance as projected by the project roponent. The record shall be submitted to the Regional Office, MoEF&CC along ith six monthly Monitoring reports.
(	in be qu	ne installation of the Sewage Treatment Plant (STP) should be certified by an dependent expert and a report in this regard should be submitted to the Ministry efore the project is commissioned for operation. Periodical monitoring of water uality of treated sewage shall be conducted. Necessary measures should be made mitigate the odour problem from STP.
(	v) N	o sewage or untreated effluent water should be discharged into storm water drain.
(	vi) S	olid waste management shall be collected, treated disposed in accordance with

	the Municipal Solid Waste (Management & Handling) Rules, 2016.
	(vii) Rain water harvesting structure for roof run-off and surface run-off, as plan submitted should be implemented. Before recharging the surface run off, pre- treatment must be done to remove suspended mater, oil and grease. The borewell for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
	(viii) Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power.
	(ix) Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.
	(x) The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.
13.3.19.	'Sunberry" residential and commercial development at Plot No. 26, Sector-8, Ghansoli, Navi Mumbai, District – Thane, Maharashtra by M/s NeelkanthInfratech Co Environmental Clearance – [F.No.21-95/2016-IA-III][IA/MH/MIS/60828/2016]
	M/s NeelkanthInfratech Co. has proposed for development of residential and commercial development at Plot No. 26, Sector-8, Ghansoli, Navi Mumbai, District Thane, Maharashtra. The project is located at 19°07'05.0"NLatitude and 72°59'46.5"Elongitude.The total plot area is 4825.580 sqm. The project will comprise of Residential 1 Owner building + Ground + 3 podium parking) + 1 podium (garden) + 1 fire check floor + 24 floors + 141 Flats + 22 shops and in MHADA building + stilt + 9 floors + 33 flats. FSI area is 8685.978 sqm. and total construction area of 30170.176 sqm. Total 174 flats shall be developed. Maximum height of the building is 92.60 m.Cost of the project is Rs 98.70 in crore.
	t is reported that no eco-sensitive area is located within 15 km distance.
	During construction phase, total water requirement is expected to be 12 KLD for workers and 10-20 KLD for construction, which will be met by NMMC and water tankers. During the construction phase, soak pits and septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided during peak labour force. During operational phase, otal water requirement of the project is 166.80 KLD. Out of which, fresh water requirement rom NMMC water supply is 90 m ³ /day. Remaining water requirement (51.0 m3/day) will be net from recycled/treated effluent water. Waste water generation is 135.50 KLD and treated in Microfiltration technology based on KSQ flat sheet membrane STP of total 140.00 KLD capacity. 58.80 KLD of treated wastewater will be recycled (50.00 for flushing, 5.00 for gardening, 3.80 for car washing). About 63.15 KLD will be disposed in to municipal drain. Municipal solid waste: About 414.45 TPD solid wastes will be generated in the project. The biodegradable waste (290.11 TPD) will be processed in OWC and the non-biodegradable waste generated (124.33 TPD) will be handed over to authorized local vendor. Power equirement: The total power requirement during construction phase is 2878 KW and will be met from MSEDCL and total power requirement during cooperation phase is 2878 KW and will be met from MSEDCL.RWH:Rooftop rainwater of buildings will be collected in 1 RWH tank of otal 17.73 KLD capacities for harvesting after filtration. Parking facility for 255 four wheelers is proposed to be provided against the requirement of 255 (According to local norms).Proposed energy saving measures would save about 22.67 % of power.
	After detailed deliberation, the Committee sought following additional information:

	<ul> <li>(i) Landuse of the propose project site.</li> <li>(ii) Copy of approved Sanction plan. Approval of the project from High Rise Building Committee of Maharashtra.</li> <li>(iii) Give a conformity status to conditions stipulated in Annexure XIV of the amended EIA notification of 09-12-2016.</li> <li>(iv) Status project proposal in the SEIAA, Maharashtra.</li> <li>(v) Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.</li> <li>(vi) Layout of parking plan indicating entry and exit points of vehicular movement as well as traffic management plan. Highlight the fire tender pathway.</li> <li>(vii) Prediction of ground level concentration of emissions from stack due to DG sets.</li> <li>(viii) Efforts shall be made to reduce the capacity of DG sets.</li> <li>(ix) At least 2 solar powered lights and one fan shall be provided in each flat. Solar generation shall be connected to the grid.</li> <li>(x) Increase the area earmarked for solid waste management facilities.</li> <li>(xi) Details energy conservation measures to be taken. taken (all points mentioned in the proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported through drawings and details in the proposal</li> <li>(xii) Increase the area for greenbelt. Layout plan indicating Greenbelt alongwith area</li> </ul>
	earmarked to be provided.
	The proposal was deferred till the desired information is submitted. The above information shall be provided with the uploading of minutes on the website
13.3.20.	Residential and commercial development at Plot No2, Sector- 8, Ulwe,Navi Mumbai, District Raigad, Maharashtra by M/s Midtown Holding Leasing and Properties Pvt. Ltd Environmental Clearance - [IA/MH/MIS/60221/2016][F.No.21- 96/2016-IA-III]
	Proposal was considered by the EAC in its 11 th meeting held on 24-25 th November, 2016 and the Committee deferred the proposal for want of addl. information. Existing project file no. is F.No.21-41/2016-IA-III. Now, new file no. (F.No.21-96/2016-IA-III) has been created. Therefore, the Committee suggested to delist the duplicate file no. 21-41/2016-IA-III. PP has submitted the point wise reply on the website of MoEF&CC. The Committee also noted that earlier EC has been granted by SEIAA, Maharashtra vide letter no. SEAC-2013/CR-489/TC-1 dated 31 st May 2014. The Committee suggested them to submit the copy certified compliance report issued by the MoEF&CC's Regional Office, Nagpur.
	The proposal was deferred till the desired information is submitted. The above information shall be provided with the uploading of minutes on the website
13.3.21.	Construction of Proposed Residential Township Project "Casa Florenza" At Mauza - Patapur & Fakirpada, District Cuttack, Odisha by M/s Sai Kripa Real Estate Pvt Ltd – Environment Clearance reg. IA/OR/NCP/61434/2014 (21-12/2017-IA-III)
	The project authorities and their consultant (M/s Ind Tech House Consult) gave a detailed presentation on the salient features of the project and proposed environmental protection measures to be undertaken as per Draft Terms of References (TORs) awarded during the Meeting of the State level Expert Appraisal Committee, Odisha held during 23 rd February, 2015 for preparation of EIA-EMP report. Terms of Reference (ToR) was granted by SEIAA, Odisha vide letter No.127/SEAC-274 dated 23 rd February, 2015.Proposed project falls under item no. 8 (b) i.e. Township and area development projects of the schedule of the EIA Notification, 2006. As per amended notification dated 9.12.2016, covering an built up area more than 3,00,000

m², proposal is categorized as Category 'A' and appraised by EAC.

M/s Sai Kripa Real Estate Pvt Ltd has proposed for Construction of Proposed Residential Township Project "Casa Florenza" At Mauza - Patapur & Fakirpada, District Cuttack, Odisha. Net plot area of the proposed project is 96601.18 m² and proposed built-up area is 3,70,067 m². Cost of project is Rs. 558 Crores. Configuration of building is as given below:

S.N.	Description	Details
1	Number Building Blocks	27 ( 25 + 2)
2	Total no of Dwelling units	1258 ns.
3	No. of EWS Units	533 Nos.
4	Maximum Height of Building	50.46 m
5	Maximum No. of floors	B + ST + 16

It is reported that protected forests namely Jagannath Prasad PF (10.5 Km), Bharatpur PF (12.8 km), Nuapalli PF (14.2 Km), Dalua PF (11.6 km) and Krushna Nagar PF (4.36 km) and Reserved Forests namely Chandaka RF (4.5 km), Churhanga RH (3.7 Km), Suniamuhan RF (9.9 km), Subasi RF (11.13 km), Oringa RF (14.3 km), Khalakhala RF (11.6 km), Charbatia RD (14.39 km) and SankaRF (14.43 km). Nandan kanan zoological park is located at a distance of 5.5 km.

Water bodies namely Puri main canal (1.45 km), Daya Canal (4.7 km), Kakatapur canal (6.7 km) and Taladanda Canal (6.6 km), Kathajorh River (0.4 km), Mahanadi River (4.9 km) Kuakhai River (2.4 km), Serua River (7.25 Km and Sapua Nadi (9.8 km) are located withn 10 km distance.

Stack height of 64.2 m will be provided to DG set (5000 KVA). Total water requirement will be 1400 m³/day. Out of which fresh water requirement will be 878 m3/day and remaining water requirement (i.e. 522  $m^3$ /day) will be met from treated sewage. Wastewater generation will be 1138 m3/day and treated in the sewage treatment plant (STP) based on MBBR Technology followed by Ultra Filtration. Treated sewage will be recycled/reused for flushing, gardening and DG cooling. Greenbelt will be developed in 19647 m² of land. Total waste generation will be 4.02 TPD of which, organic waste generation will be 2.41 TPD; E-waste generation will be 25 KG/day and Sludge generation will be 409.76 Kg/day. Hazardous waste generation will be 1000 Lt/Annum. PP informed that space earmarked for solid waste management will be 200 m² and 50 m² for e-waste collection respectively. 26 nos of rain water recharge pits will be provided. Total parking area proposed is 95324 m². No R & R involved in the said project. The Group Housing project will be developed as per CDA master plan, which demarcates the project site as residential zone. PP confirmed that the project is outside the flood plain. The PP informed that no natural drains are passing through the project site and will not disturb the natural drains. Energy conservation measures will be adopted. PP will incorporate sola passive techniques in the building design to minimize load on conventional system. Energy efficient building envelops will be followed. Energy efficient LED lamps to be provided to reduce energy consumption. 250 KWP Solar PV plant will be installed. PP informed that two artificial ponds will be constructed (one of 600  $m^2$  and another of 400  $m^2$ )

After detailed deliberations, the Committee recommended the project for environmental clearance and stipulated the following specific conditions along with other environmental conditions while considering for accord of environmental clearance:

## I. Construction Phase

(i) The Projects proponent shall obtain all necessary clearance / permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building

	byelaws.
(ii)	Construction site should be adequately barricaded before the construction begins.
(iii)	The building envelope for all air conditioned buildings / spaces shall be complied with the ECBC. Roofs and opaque walls should comply with the maximum assembly U factor or the minimum insulation R-value as well as lighting systems and equipment shall comply with the provisions of Energy conservation building Code.
(iv)	Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
(v)	Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
(vi)	Sewage shall be treated in the STP (with tertiary treatment i.e. Ultra Filtration). The treated effluent from STP shall be recycled/re-used for flushing, horticulture & DG cooling.
(vii)	As proposed, 26 nos of rain water recharge pits as per CGWB guidelines.
(viii)	Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 250 m ² of area for the proposed building shall be provided for solid waste management within the premises which will include area for segregation, composting etc. The inert waste from project will be sent to dumping site of Municipality. E-waste shall be disposed through authorised E-waste processor.re-cyclers.
(ix)	Solar based electric power shall be provided to each unit for atleast two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.
(x)	A First Aid Room will be provided in the project both during construction and operations of the project.
(xi)	All the top soil excavated during construction activities should be stored for use in horticulture/ landscape development within the project site.
(xii)	Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
(xiii)	The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environmental (Protection) prescribed for air and noise emission standards.
(xiv)	Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
(xv)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
(xvi)	Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
(xvii)	Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak

		hours.
	(xviii)	Ambient noise levels should conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
	(xix)	Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27 th August, 2003. Ready mixed concrete must be used in building construction.
	(xx)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
11	Ор	peration Phase
	(i)	The gaseous emissions from DG set shall be dispersed through adequate stack height as per CPCB standards. Acoustic enclosure shall be provided to the DG sets to mitigate the noise pollution. Low sulphur diesel shall be used. The location of the DG sets may be decided with in consultation with State Pollution Control Board.
	(ii)	Fresh water requirement from CDA/Municipal Water Supply/Ground Watershall not exceed 878m ³ /day. Prior permission shall be obtained from CGWA/SGWA for ground water extraction.
	(iii)	The quantity of fresh water usage, water recycling and rainwater harvesting shall be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports.
	(iv)	The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the Ministry before the project is commissioned for operation. Periodical monitoring of water quality of treated sewage shall be conducted. Necessary measures should be made to mitigate the odour problem from STP.
	(v)	No sewage or untreated effluent should be discharged into storm water drain/river.
	(vi)	Solid waste management shall be collected, treated disposed in accordance with the Municipal Solid Waste (Management & Handling) Rules, 2016.
	(vii)	Rain water harvesting structure for roof run-off and surface run-off, as plan submitted should be implemented. Before recharging the surface run off, pre- treatment must be done to remove suspended mater, oil and grease. The borewell for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
	(viii)	Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power.
	(ix)	Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.
	(x)	The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.

	Jagatsingh	pur, Odisha	Harbour Paradip Port Trust, Paradip by M/s Paradip Port Trust – Reconsic IA-III; IA/OR/MIS/60156/2016]	
		ee sought follo	by EAC (Infra-2) in its meeting held on owing additional information:	
	i.		tement indicating details of (a) existing b) proposed additional facilities; (c) total l.	
	ii. iii.		Il environmental clearance obtained for th plementation of the existing EC.	ne existing project.
	iv.	As per form meeting it	1, it is mentioned that proposal involves was informed that expansion will be ca it clarification on the land use of the e	arried out on the reclaime
	V.	Details of la	nd use of the existing ports and propose	d project area
	vi. vii.		argo to be handled. Ty chart for the activities to be undertaken	in the first phase.
	Consent to periodically handling ber North Oil Jet CRZ issued import berth It was inform sought for 5 163.6 MTPA Township, In Total area fo existing land area is fores	Operate is be renewed.PP I ths; (ii) Copy tty ;Copy of E on 4.01.2011 and new clean ned that as o additional ber A. Total existing dustrial Zone, or proposed O and 220 ha o t land and bal	mmissioned in 1966. These berths are i eing issued by the State Pollution Cont has submitted the (i) copy of EC issu of EC issued on 24.12.1997 for grass C& CRZissued on 13.07.2012 for south for deep draught iron ore. So far, new n cargo berth to be implemented. n date installed handling capacity of por ths with capacity of 70 MTPA. Total cap ng plot area is (i) custom bound harbourd Storage Terminals, Railway Sidings etc puter Harbour for the Master plan is 300 of proposed reclaimed land. Out of the est ance 5 ha is non forest land utilized for the as given below:	rol Board, Odisha which ed on 10.04.1992 for co root petroleum refinery ar Oil Jetty; (iv) copy of EC Iron export berth; new co rt is 93.6 MTPA. Now EC acity after expansion will b our area (871.95 ha) + ( (1683.14 ha) = 2555.09 ha ha which includes 80 ha xisting 80 ha about 75 ha
		n Type	Cargo	
		Export	Thermal Coal	Export
		Export	Coking coal, Limestone, Gypsum	Import
		purpose	Break Bulk	Import/Export
		pulpooo	Broak Baik	Import/Export
	3 Multi Afte Terms of Re	r detailed deli ference as sp	berations on the proposal, the Committee ecified by the Ministry as Standard ToR is owing TOR in addition to Standard ToR	e recommended for grant o n April, 2015 for the said

- ii. A separate chapter on status of compliance of Environmental Conditions granted by State/Centre to be provided. As per circular dated 30th May, 2012 issued by MoEF, a certified report by RO, MoEF&CC on status of compliance of conditions on existing port to be provided in EIA-EMP report.
- iii. Submit a copy of layout superimposed on the HTL/LTL map demarcated by an authorized agency on 1:4000 scale.

	iv.	Recommendation of the SCZMA.		
	V.	Status of stage -1 forest clearance for the involvement of forest land of 75 ha.		
	vi.	Various Ports facilities with capacities for proposed project.		
	vii.	List of cargo to be handled along with mode of transportation.		
	viii.	Layout plan of existing and proposed Port.		
	ix.	A detailed analysis of the physico-chemical and biotic components in the highly turbid waters round the project site (as exhibited in the Google map shown during the presentation), compare it with the physico- chemical and biotic components in the adjacent clearer (blue) waters both in terms of baseline and impact assessment and draw up a management plan.		
	Х.	Study the impact of dredging on the shore line.		
	xi.	A detailed impact analysis of rock dredging.		
	xii.	Action plan for disposal of dredged soil and rocks.		
	xiii.	Dispersion modelling for the dumping of the dredge materials shall be carried out. The study report shall be incorporated.		
	xiv.	Details of air pollution control measures to be taken as well as cost to be incurred.		
	XV.	Total water consumption and its source. Wastewater management plan.		
	xvi.	Details of Environmental Monitoring Plan.		
	xvii.	The Marine biodiversity impact assessment report and management plan shall deal with all micro, micro and mega biotic components and ecology within the area of influence and should be drawn up through the National Institute of Oceanography or any other institution specializing in marine ecology.		
	xviii.	Disaster Management Plan for the above terminal.		
	xix.	Layout plan of existing and proposed Greenbelt.		
	XX.	Status of court case pending against the project.		
	xxi.	A tabular chart with index for point wise compliance of above TORs.		
	xxii.	Public hearing to be conducted and issues raised and commitments made by the project proponent on the same should be included in EIA/EMP Report in the form of tabular chart with financial budget for complying with the commitments made.		
It was recommended that 'TORs' along with Public Hearing prescribed by the Expert App Committee (Infrastrucure-2) should be considered for preparation of EIA / EMP report for above mentioned project in addition to all the relevant information as per the 'Generic Stru- of EIA' given in Appendix III and IIIA in the EIA Notification, 2006. The draft EIA/EMP r shall be submitted to the State Pollution Control Board for public hearing. The issues em- and response to the issues shall be incorporated in the EIA report.				
	1	Wednesday, 25 th January, 2017		
13.4.1	Ghatkopar, Hospitalitie	Hotel on plot A-5(PT) bearing C.T.S. No. 1/9 A -1 (PT)of village , Vikhroli Park site, Vikhroli (W), Mumbai, Maharashtra by M/s Kailas es- Environmental Clearance – [F.No.21-98/2016-IA- IIS/60882/2016]		

	The Committee deferred the project as the project proponent did not attend the meeting.
13.4.2	Proposed residential cum commercial project at S. No. 112A, 113/ 114, 117, 118, 119/ 122A,123A, 296/ 297, 318 P. No. 3,4,5,5A,10,11,11A,12,15,16 Pune Solapur Road, Hadapsar, Pune, Maharashtra by M/s Dosti Realty Limited- Environmental Clearance - [F.No.21-99/2016-IA-III][IA/MH/MIS/61054/2016]
	M/s Dosti Realty Limited has proposed for development of residential cum commercial project at S. No. 112A, 113/ 114, 117, 118, 119/ 122A,123A, 296/ 297, 318 P. No. 3,4,5,5A,10,11,11A,12,15,16 Pune Solapur Road, Hadapsar, Pune, Maharashtra. The project is located at 18°30'20.31"N Latitude and 73°55'08.46"E Longitude.The total plot area is 48,284.39 m ² . FSI area is 84,412.73 m ² and total built-up area is 1,46,972.99 m ² . The project comprises of 13 Residential Buildings, 1 Commercial building, and club house. Total 712 Flats and 870 m ² of commercial area shall be developed. Maximum height of the building is 68.10 m. <b>Cost</b> of the project is Rs. 488 Cr.
	It is reported that waterbodies namely Irrigation Department's water supply canal (Mutha canal section)- 120 m and Mula- Mutha River (3.5 km) are located within 10 km distance.
	During construction phase, total water requirement is expected to be 150 KLD which will be met by tanker water. During the construction phase, soak pits and septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided during peak labor force.During operational phase, total water requirement will be 419 m ³ /dayof which, fresh water requirement from PMC (Municipal Water Supply) will be 300 m ³ /day and remaining water requirement (96 m3/day) will be met from recycled water/treated sewage. Wastewater generation will be362 m ³ /day and treated in STP of 400 KLD capacity. 96 KLD of treated wastewater will be recycled for flushing. About 239 KLD will be discharged in Municipal sewer lines. About 2277 kg/d solid waste will be generated in the project. The biodegradable waste (1366 kg/d) will be processed in mechanical composting (Eco-biocompack) and the non-biodegradable waste generated (911 kg/d) will be handed over to authorized local vendor. Space of 100 m ² will be provided foe solid waste management. The total power requirement during operation phase is 3.3 MW and will be met from MSEDCL and Total power requirement during operation phase is 3.3 MW and will be met from MSEDCL.Rooftop rainwater of building will be recharged in ground through 5 nos. of recharge pits.Parking facility for 1631 Nos. four wheelers and 2525 Nos. two wheelers are proposed to be provided against the requirement of 986 and 1510 respectively (According to local norms).Proposed energy saving measures would save about 20.6 % of power.
	conditions while considering for accord of environmental clearance: I. Construction Phase
	<ul> <li>(i) The Projects proponent shall obtain all necessary clearance / permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.</li> </ul>
	(ii) Construction site should be adequately barricaded before the construction begins.
	(iii) The building envelope for all air conditioned buildings / spaces shall be complied with the ECBC. Roofs and opaque walls should comply with the maximum assembly U factor or the minimum insulation R-value as well as lighting systems

	and equipment shall comply with the provisions of Energy conservation building Code.
(iv)	Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
(v)	Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
(vi)	Sewage shall be treated in the STP (with tertiary treatment i.e. Ultra Filtration). The treated effluent from STP shall be recycled/re-used for flushing, horticulture & DG cooling.
(vii)	As proposed, 5 nos of rain water recharge pits as per CGWB guidelines.
(viii)	Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 100m ² of area for the proposed building shall be provided for solid waste management within the premises which will include area for segregation, composting etc. The inert waste from project will be sent to dumping site of Municipality. E-waste shall be disposed through authorised E-waste processor.re-cyclers.
(ix)	Solar based electric power shall be provided to each unit for atleast two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.
(x)	A First Aid Room will be provided in the project both during construction and operations of the project.
(xi)	All the top soil excavated during construction activities should be stored for use in horticulture/ landscape development within the project site.
(xii)	Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
(xiii)	The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environmental (Protection) prescribed for air and noise emission standards.
(xiv)	Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
(xv)	As proposed, no ground water shall be used during construction / operation phase of the project.
(xvi)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
(xvii)	Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
(xviii)	Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.
(xix)	Ambient noise levels should conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality should be

			closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
		(xx)	Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27 th August, 2003. Ready mixed concrete must be used in building construction.
		(xxi)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
	II	Ор	eration Phase
		(xi)	The gaseous emissions from DG set shall be dispersed through adequate stack height as per CPCB standards. Acoustic enclosure shall be provided to the DG sets to mitigate the noise pollution. Low sulphur diesel shall be used. The location of the DG sets may be decided with in consultation with State Pollution Control Board.
		(xii)	Fresh water requirement from Municipal Water Supplyshall not exceed 305m ³ /day.
		(xiii)	The quantity of fresh water usage, water recycling and rainwater harvesting shall be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports.
		(xiv)	The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the Ministry before the project is commissioned for operation. Periodical monitoring of water quality of treated sewage shall be conducted. Necessary measures should be made to mitigate the odour problem from STP.
		(xv)	No sewage or untreated effluent water should be discharged into storm water drain.
		(xvi)	Solid waste management shall be collected, treated disposed in accordance with the Municipal Solid Waste (Management & Handling) Rules, 2016.
		(xvii)	Rain water harvesting structure for roof run-off and surface run-off, as plan submitted should be implemented. Before recharging the surface run off, pre- treatment must be done to remove suspended mater, oil and grease. The borewell for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
		(xviii)	Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power.
		(xix)	Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.
		(xx)	The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.
13.4.3	47 Pr	, 48, 4 oviden	d Redevelopment of Residential cum Commercial Project at CTS. No. 15, 49, 59 & 63 at L.B.S. Marg, Damani Estate, Naupada, Thane by M/s ice Realty LLP- Environmental Clearance -[F.No.21-100/2016-IA- I/MIS/61192/2016]

M/s Providence Realty LLP has proposed for redevelopment of residential cum commercial Project at CTS. No. 15, 47, 48, 49, 59 & 63 at L.B.S. Marg, Damani Estate, Naupada, Thane, Maharashtra. The project is located at 19°11'25.58"N Latitude and 72°57'58.94"E Longitude.The plot area is 10,562.27 m². FSI area is 23,522.95 m² and total construction area is 47,642.69 m². The proposed redevelopment comprises of 2 residential buildings having 363 flats, Commercial shops and offices shall be developed. Maximum height of the building is 91.95 m.Cost of the project is Rs. 115 Crore.

It is reported that the project site is located within 10 km of Sanjay Gandhi National Park. However, it is outside the eco-sensitive area as per MoEF&CC Notification dated 5th December, 2016.

During construction phase, total water requirement is expected to be 60 KLD which will be met by tanker water / treated water from nearby STP. During the construction phase, soak pits and septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided.During operational phase, total water demand of the project is expected to be 201 KLD and same will be met by fresh water from TMC (Thane Municipal Corporation) and recycled water. Wastewater generated (176 KLD) uses will be treated in STP of 200 KLD capacity. 50 KLD of treated water will be recycled for flushing and about 10 KLD for gardening. About 114 KLD will be discharged in Municipal sewer line. About 1114 kg/d solid waste will be generated in the project. The biodegradable waste (669 kg/d) will be processed in mechanical composting (Eco-biocompack) and the non-biodegradable waste 446 kg/d will be handed over to recyclers. The total power requirement during construction phase is 250 kVA and will be met from MSEDCL and total power requirement during operation phase is 1.8 MW (demand Load) and will be met from MSEDCL.Rooftop rainwater of building will be collected in 2 RWH tanks of total 50 m³ holding capacity for harvesting after filtration. **Parking facility**: Parking facility for 435 Nos. of four wheelers and 370 Nos. of two wheelers are proposed to be provided against the requirement of 434 Nos. four wheelers and 363 Nos. two wheelers respectively (as per local norms). Proposed energy saving measures would save about 21.19 % of power.

After detailed deliberation, the Committee sought following additional information:

- (i) Status of project proposal in SEIAA, Maharashtra.
- (ii) Give a conformity status to conditions stipulated in Annexure XIV of the amended EIA notification of 09-12-2016.
- (iii) Copy of approved Sanction plan.
- (iv) Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.
- (v) Layout of parking plan indicating entry and exit points of vehicular movement as well as traffic management plan. Highlight the fire tender pathway.
- (vi) Details of source of water supply alongwith permission to be submitted.
- (vii) Excess treated sewage disposal plan/scheme to be submitted.
- (viii) Prediction of ground level concentration of emissions from stack due to DG sets.
- (ix) Efforts shall be made to reduce capacity of DG set and remaining standby power shall be met from solar energy.
- (x) At least 2 solar powered lights and one fan shall be provided in each flat. Solar generation shall be connected to the grid.
- (xi) Solid waste management plan alongwith area earmarked for solid waste management scheme.
- (xii) Action plan for management of construction and demolition waste.
- (xiii) Management of excavated soil. Pollution control measures to be taken to control fugitive emission during construction phase including marble /stone cutting.
- (xiv) Details energy conservation measures to be taken (all points mentioned in the

	<ul> <li>proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported through drawings and details in the proposal</li> <li>(xv) Layout plan indicating Greenbelt alongwith area earmarked to be provided.</li> </ul> The proposal was deferred till the desired information is submitted. The above information shall be provided with the uploading of minutes on the website.		
13.4.4	Redevelopment of Residential cum Commercial Project at Byculla, Mumbai, Maharashtra by M/s Dosti Realty Ltd - Environmental Clearance - [F.No.21- 101/2016-IA-III] [IA/MH/MIS/61280/2016]		
	M/s Dosti Realty Ltd has proposed for redevelopment of property bearing C. S. No. 2050 of byculla div. situated at N.M Joshi Marg, Byculla, Mumbai, Maharashtra. The project is located at 18°59'2.07"N Latitude and 72°49'56.28"E Longitude.The plot area is 5,221.61 m ² . FSI area is 21,099.74 m ² and total construction area is 41,541.53 m ² . Total 71 Sale Flats, 252 Rehab Flats, 15 Commercial shops, parking building shall be developed. The maximum height of the building is 150.3 m. <b>Cost</b> of the project is Rs. 244 Cr.		
	It is reported that Jijamata Udyan Zoo( Approx 0.6 km) is located within 10 km distance. Water bodies namely Jijamata Udyan Zoo(0.6 km) within 10 km distance.		
	During construction phase, total water requirement is expected to be 60 KLD which will be me by tanker water / treated water from nearby STP. During the construction phase, soak pits an septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided during peak labor force. During operational phase, total water demand of the project expected to be 146 KLD and same will be met by fresh water from MCGM (Municip. Corporation of Greater Mumbai) and recycled water. Wastewater generated (130 KLD) use will be treated in STP of 140 KLD capacity. 35 KLD of treated water will be recycled for flushing and about 2 KLD for gardening. About 91 KLD will be discharged in Municipal sews line. About 817 kg/d solid waste will be generated in the project. The biodegradable waste (49 kg/d) will be processed in mechanical composting (Eco-biocompack) and the non biodegradable waste 327 kg/d will be handed over to recyclers. The total power requirement during construction phase is 250 kVA and will be met from BEST and Total power requirement during operation phase is 3.5 MW (demand Load) and will be met from BEST.Rooftor rainwater of building will be collected in 2 RWH tanks of total 115 m ³ capacity for harvestin after filtration. <b>Parking facility</b> for 181 Nos. four wheelers and 10 Nos. two wheelers and proposed to be provided against the requirement of 180 Nos. four wheelers (as per loc norms).Proposed energy saving measures would save about <b>20.3</b> % of power.		
	After detailed deliberation, the Committee sought following additional information:		
	<ul> <li>(i) Status of project proposal in SEIAA, Maharashtra.</li> <li>(ii) Give a conformity status to conditions stipulated in Annexure XIV of the amended EIA notification of 09-12-2016.</li> <li>(iii) Copy of approved Sanction plan.</li> </ul>		
	(iv) Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.		
	<ul> <li>(v) Layout of parking plan indicating entry and exit points of vehicular movement as well as traffic management plan. Highlight the fire tender pathway.</li> <li>(vi) Details of source of water supply alongwith permission to be submitted.</li> </ul>		

	<ul> <li>(vii) Excess treated sewage disposal plan/scheme to be submitted.</li> <li>(viii) Prediction of ground level concentration of emissions from stack due to DG sets.</li> <li>(ix) Efforts shall be made to reduce capacity of DG set and remaining standby power shall be met from solar energy.</li> <li>(x) At least 2 solar powered lights and one fan shall be provided in each flat. Solar generation shall be connected to the grid.</li> <li>(xi) Solid waste management plan alongwith area earmarked for solid waste management scheme.</li> <li>(xii) Action plan for management of construction and demolition waste.</li> <li>(xiii) Management of excavated soil. Pollution control measures to be taken to control fugitive emission during construction phase including marble /stone cutting.</li> <li>(xiv) Details energy conservation measures to be taken (all points mentioned in the proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1, use of ECBC compliant envelope measures to be supported through drawings and details in the proposal</li> <li>(xv) Layout plan indicating Greenbelt alongwith area earmarked to be provided.</li> </ul>
13.4.5	Proposed Redevelopment of Residential Building No. 38 & 39 of Vartaknagar Layout at Plot bearing Sy. No. 212 (Pt) at village Majiwade, Tal and Dist: Thane, Maharashtra by M/s Ekdanta Construction & Developers Pvt. Ltd- Environmental Clearance – [F.No.21-102/2016-IA-III][IA/MH/MIS/61293/2016] M/s Ekdanta Construction & Developers Pvt. Ltd. has proposed for redevelopment of residential building No. 38 & 39 of Vartaknagar Layout at Plot bearing Sy. No. 212 (Pt) at Village Majiwade, Taluka and District Thane, Maharashtra. The project is located at
	19°12'42.34"N Latitude and 72°57'39.77"E Longitude. The total plot area is 3,810.77 m ² . FSI area is 16,334.24 m ² and total construction area is 31,275.50 m ² . The project comprise of 1 Residential Building having 305 flats & Commercial area of 2260 m ² (44 shops). Maximum height of the building is 91.50 m.It is reported that Sanjay Gandhi National Park (approx. 1.3 km)and Tungareshwar Wild life Sanctuary (12 km) are located at a distance of 15 km. During construction phase, total water requirement is expected to be 60 KLD which will be met by tanker water/ treated water from nearby STP. During the construction phase, soak pits and septic tanks will be provided for disposal of waste water. Temporary sanitary toilets will be provided during peak labor force. During operational phase, total water demand of the project is expected to be 167 KLD and same will be met by fresh water from TMC (Thane Municipal corporation) and recycled water. Wastewater generated (Sullage Generation- 95 KLD) will be treated in Sullage Treatment Plant of 100 KLD capacity. 44 KLD of treated wastewater will be recycled for flushing. Sewage and Excess Treated Sullage of 93 KLD will be discharged to Municipal sewer lines. About 960 kg/d solid waste will be generated in the project. The biodegradable waste (576 kg/d) will be processed in mechanical composting (Ecobiocompack) and the non-biodegradable waste generated (384 kg/d) will be handed over to authorized local vendor.
	The total power requirement during construction phase is 250 kVA and will be met from MSEDCL and Total power requirement during operation phase is 1.4 MW (Demand Load) and will be met from MSEDCL.Rooftop rainwater of building will be collected in one RWH tank of total holding capacity 49 m ³ for harvesting after filtration.
	<b>Parking facility</b> for 280 Nos. four wheelers and 305 Nos. two wheelers are proposed to be provided against the requirement of 223 four wheelers and 305 two wheelers respectively (as per local norms). Proposed energy saving measures would save about 20.5 % of (Total demand) power.

	After detailed deliberation, the Committee sought following additional information:		
	(i) Status of project proposal in SEIAA, Maharashtra.		
	(ii) Give a conformity status to conditions stipulated in Annexure XIV of the amended		
	EIA notification of 09-12-2016.		
	(iii) Copy of approved Sanction plan.		
	(iv) Layout plan indicating road, greenbelt, drainage, sewer line, STP, solid waste handling area, rain water harvesting structure, etc. in different colour to be furnished.		
	(v) Layout of parking plan indicating entry and exit points of vehicular movement as		
	<ul><li>well as traffic management plan. Highlight the fire tender pathway.</li><li>(vi) Details of source of water supply alongwith permission to be submitted.</li></ul>		
	(vii) Excess treated sewage disposal plan/scheme to be submitted.		
	(viii) Prediction of ground level concentration of emissions from stack due to DG sets.		
	<ul> <li>(ix) Efforts shall be made to reduce capacity of DG set and remaining standby power shall be met from solar energy.</li> </ul>		
	(x) At least 2 solar powered lights and one fan shall be provided in each flat. Solar generation shall be connected to the grid.		
	(xi) Solid waste management plan alongwith area earmarked for solid waste management scheme.		
	(xii) Action plan for management of construction and demolition waste.		
	(xiii) Management of excavated soil. Pollution control measures to be taken to control fugitive emission during construction phase including marble /stone cutting.		
	(xiv) Details energy conservation measures to be taken (all points mentioned in the		
	proposal such as orientation to support reduced heat gain, use of ASHRAE 90.1,		
	use of ECBC compliant envelope measures to be supported through drawings and		
	details in the proposal (xv) Layout plan indicating Greenbelt alongwith area earmarked to be provided.		
	(XV) Layout plan indicating Greenbeit alongwith area earmarked to be provided.		
	The proposal was deferred till the desired information is submitted. The above information shall be provided with the uploading of minutes on the website.		
13.4.6	Proposed Residential cum Commercial Project- "Wadhwa Rhodesia" at S. No. 158/9, bhiwandi Railway Station, Pritesh Compound, Bhiwandi, Thane Maharashtraby M/s Wadhwa Rhodesia- Environmental Clearance [IA/MH/MIS/61424/2016][F.No.21-103/2016-IA-III]		
	The Committee deferred the project as the project proponent did not attend the meeting.		
13.4.7	Mixed used development "Trivedi Tower" CTS No 551/13 at junction of Madan Mohan Malviya Road, & 18.30 wide D P Road of village NahurMulund (w), Mumbai, Maharashtra by M/s ChhaganlalKhimji& Co Ltd- Environmental Clearance – [IA/MH/MIS/56371/2016][F.No.21-90/2014- IA III]		
	Project proposal was considered by the EAC (Infra-2) in its meeting held on 23 rd February, 2016 and the Committee desired the following addl. Information :		
	<ul> <li>a) Fresh form1, IA and conceptual plan.</li> <li>b) A report on mandatory compliance measures taken for proposed buildings as recommended in the Energy conservation building code (ECBC) 2007 of the Bureau of</li> </ul>		

c) S d) [ e) S f) [	e) Solid waste management.					
74/2006 The Co	PP has submitted the addl. Information. Environment Clearance was granted vide letter No.21 74/2006-IA-III dated 17 th October 2006. Total Constructed FSI on site till date is 19485.97 sqm The Committee noted that project file of existing EC is closed as validity of existing EC is expired. Proposed project will be considered as fresh EC proposal.					
Madan	The project involves mixed used development "Trivedi Tower" CTS No 551/13 at junction of Madan Mohan Malviya Road, & 18.30 wide D P Road of village NahurMulund (w), Mumbai, Maharashtra promoted by M/s ChhaganlalKhimji & Co Ltd.					
16898.2 Club Ho Total 46 temple s	The project is located at 19°56'12.43"N Latitude and 72°56'36.17"E Longitude. The plot area is 16898.20 sqm. The project will comprise of 10 wings with one building of Marathon House, Club House and Temple. FSI area is 56539.56 sqm and total built-up area of 145223.18 sqm. Total 465 flats, 24 shops, offices, Amenity (Retail market), Marathon House, club house & temple shall be developed. Maximum height of the building upto terrace level is 149.00 m. <b>Cost</b> of the project isRs. 118.95 Crores. The details of the building is as under:-					
		Project Proposal				
	Residential	Wing A:				
	neolaennia	B2 + B1 + Lower Ground + Ground+1 st to 4 th parking floors + 5 th service floor + 6 th floor podium level + 7 th to 43 rd floors <b>Wing B:</b> B2 + B1 +Lower Ground + Ground + 33 upper floors <b>Wing J:</b> B3 + B2 + B1 + Lower ground + Ground+ 25 th (part) upper floors Flats :465 Nos.	Extended parking floors of Ground + 3 upper floors over basement connecting all wings.			
	Commercial	Wing D,E,F,G,H & I: B2 + B1 +Lower ground + Ground+ 3upper floors Shops: 24 Nos. Offices				
	Amenity	Wing C :	·			
	(Retail Market)	Ground + 1upper floor + Service flo	oor			
	Marathon House	Ground+ 6 th (part) upper floors :Off				
	Club House	Ground + 7 upper floors				
	Temple	Ground				
Waterbo	It is reported that Sanjay Gandhi National Park is located at the distance of 1.0 km Waterbodies namely Vihar Lake, Tulsi Lake, Powai Lake, Arabian Sea and Thane Creek an located within 10 km distance.					

During construction phase, total water requirement is expected to be 33 KLD for workers and 30-40 KLD for construction activity which will be met by M.C.G.M. and tanker respectively. During construction phase the waste water will be disposed to existing municipal sewer line. Temporary sanitary toilets will be provided during peak labor force. During operational phase,

total water requirement for the project is will be 369 m³/day. Out of which fresh water requirement from MCGM will be 229 m³/day and remaining water requirement i.e. 131 m3/day will be met from recycled/treated effluent. Besides, 4 KLD for swimming pool will be required from tanker water of potable quality. Waste water generation will be 314 KLD and treated in 3 STPs of total 630 KL capacity. 136 KLD of treated wastewater will be recycled (131 KLD for flushing, 5 KLD for gardening). About 147 KLD from the whole project will be disposed in to municipal drain. About 1.2 TPD solid wastes will be generated in the project. The biodegradable waste (0.8 TPD) will be processed in OWC and the non-biodegradable waste generated (0.40 TPD) will be handed over to M.C.G.M. The total power requirement during construction phase is 100 kVA and will be met from Local Authority and total power requirement during cooperation phase is 13494 KW and will be met from MSEDCL. Rooftop rainwater of buildings will be collected in 3 RWH tanks of total 154 KL capacity for harvesting after filtration. Parking facility for 1283 four wheelers and 160 two wheelers is proposed to be provided against the requirement of 1282 and Nil respectively (according to local norms).

After detailed deliberations, the Committee recommended the project for environmental clearance and stipulated the following specific conditions along with other environmental conditions while considering for accord of environmental clearance:

### I. Construction Phase

- (i) The Projects proponent shall obtain all necessary clearance / permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.
- (ii) Construction site should be adequately barricaded before the construction begins.
- (iii) The building envelope for all air conditioned buildings / spaces shall be complied with the ECBC. Roofs and opaque walls should comply with the maximum assembly U factor or the minimum insulation R-value as well as lighting systems and equipment shall comply with the provisions of Energy conservation building Code.
- (iv) Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
- (v) Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
- Sewage shall be treated in the STP (with tertiary treatment i.e. Ultra Filtration). The treated effluent from STP shall be recycled/re-used for flushing, horticulture & DG cooling.
- (vii) As proposed, Rooftop rainwater of buildings shall be collected in 3 RWH tanks of total 154 KL capacity for harvesting after filtration as per CGWB guidelines.
- (viii) Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 120 m² of area shall be provided for solid waste management within the premises which will include area for segregation, composting etc. The inert waste from project will be sent to dumping site of Municipality. E-waste shall be disposed through authorised E-waste processor.re-cyclers.
- (ix) Solar based electric power shall be provided to each unit for atleast two bulbs/light and one fan. As proposed, central lighting and street lighting shall

	also be based on solar power.
(x)	A First Aid Room will be provided in the project both during construction and operations of the project.
(xi)	All the top soil excavated during construction activities should be stored for use in horticulture/ landscape development within the project site.
(xii)	Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
(xiii)	The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environmental (Protection) prescribed for air and noise emission standards.
(xiv)	Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
(xv)	As proposed, no ground water shall be used during construction / operation phase of the project.
(xvi)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
(xvii)	Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
(xviii)	Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.
(xix)	Ambient noise levels should conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
(xx)	Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27 th August, 2003. Ready mixed concrete must be used in building construction.
(xxi)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
Оре	ration Phase
r t	The gaseous emissions from DG set shall be dispersed through adequate stack neight as per CPCB standards. Acoustic enclosure shall be provided to the DG sets o mitigate the noise pollution. Low sulphur diesel shall be used. The location of he DG sets may be decided with in consultation with State Pollution Control Board.
(ii) F	Fresh water requirement from Municipal Water Supplyshall not exceed 229 m ³ /day.
r F	The quantity of fresh water usage, water recycling and rainwater harvesting shall be neasured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports.
	(xi) (xii) (xiii) (xiv) (xv) (xvi) (xvii) (xviii) (xix) (xix) (xix) (xix) (xix) (xix) (xix)

	(iv)	The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the Ministry before the project is commissioned for operation. Periodical monitoring of water quality of treated sewage shall be conducted. Necessary measures should be made to mitigate the odour problem from STP.		
	(v)	No sewage or untreated effluent water should be discharged into storm water drain.		
	(vi)	Solid waste management shall be collected, treated disposed in accordance with the Municipal Solid Waste (Management & Handling) Rules, 2016.		
	(vii)	Rain water harvesting structure for roof run-off and surface run-off, as plan submitted should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended mater, oil and grease.		
	(viii)	Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power.		
	(ix)	Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.		
	(x)	The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.		
13.4.8	Proposed Residential cum Commercial project "Wadhwa Rhodesia" at survey no. 159, Bhiwandi, Railway station, Pritesh compound, Kamatghar, Bhiwandi(East) by M/s. Wadhwa Rhodesia- Environmental Clearance -[F.No.21- 1/2017-IA-III][IA/MH/MIS/61428/2016] The Committee deferred the project as the project proponent did not attend the meeting.			
13.4.9	Proposed commercial project - XENON on Plot Bearing C.T.S No. 1406- A/25 – B/ 20 F, Village Malad, Off Link road, Malad West, Maharashtra by M/s. Raheja Universal (Pvt) Ltd- Environmental Clearance –[F.No.21-2/2017-IA-III] [IA/MH/MIS/61429/2016]			
	M/s. Raheja Universal (Pvt) Ltd has proposed for development of commercial project 'XENON' at Plot Bearing C.T.S No. 1406- A/25 – B/ 20 F, Village Malad, Off Link road, Malad West, Maharashtra. The Latitude is $19^{\circ}10'28.83$ "N, $19^{\circ}10'28.52$ "N and Longitude is $72^{\circ}50'8.05$ "E, $72^{\circ}50'6.30$ "E. Total plot area is $7257.00$ sqm, FSI area will be $13421.09$ sqm and the total built-up area will be $25545.42$ sqm. The project consists one building having $127$ nos. of shops. (LB + UB + Gr + 3 floors). The maximum height of the buildings will be $17.70$ m. <b>Cost of the project is</b> Rs. 98.98 Crores.			
	notificatio	rted that Sanjay Gandhi National Park is situated at a distance of 2.51 km. As per the on of MOEFCC Sr. No. 3645 (E) dated 5.12.2016, the Eco-sensitive Zone (ESZ) is ted. <i>The project is outside the Eco- sensitive zone boundary.</i>		
	The water requirement during construction phase will be 15 KLD which will be outsourced through Tanker Water. Soak pits and septic tanks will be provided for disposal of waste water. Modular STP will be provided during construction. Temporary sanitary toilets will be provided during peak labor force. During operation phase, the total water requirement will be 24 m ³ /day.			

Out of which, fresh water requirement will be 7 m3/day and remaining water requirement (17 m³/day) will be met from treated/recycled sewage. Waste water generation will be 17 m³/day and treated in the STP. **Solid Waste Management:** Biodegradable waste will be 42 Kg/day which will be processed in OWC. Area earmarked for solid waste management is 53 m². Non-biodegradable waste will be 99 Kg/day which will be handed over to authorized local vendor. **Power Requirement:** 100 KW which will be sourced through Tata Power/Reliance Energy. **Rain Water Harvesting:** Quantity of Rain Water is 11 cum and the capacity of RWH Tanks for harvesting after filtration will be 33 cum (3 days capacity). **Parking Details: For** 4 wheelers requirement according to local norms is 98 nos and will be provided for 266 Nos of 4 wheelers and 45 nos. for 2 wheelers. 26% energy will be conserved by using energy efficient LED, CFL lamps & solar panel, providing energy efficient devices for equipment's and machinery etc.

After detailed deliberations, the Committee recommended the project for environmental clearance and stipulated the following specific conditions along with other environmental conditions while considering for accord of environmental clearance:

# I. Construction Phase

- (i) The Projects proponent shall obtain all necessary clearance / permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.
- (ii) Construction site should be adequately barricaded before the construction begins.
- (iii) The building envelope for all air conditioned buildings / spaces shall be complied with the ECBC. Roofs and opaque walls should comply with the maximum assembly U factor or the minimum insulation R-value as well as lighting systems and equipment shall comply with the provisions of Energy conservation building Code.
- (iv) Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
- (v) Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
- Sewage shall be treated in the STP (with tertiary treatment i.e. Ultra Filtration). The treated effluent from STP shall be recycled/re-used for flushing, horticulture & DG cooling.
- (vii) As proposed, Rooftop rainwater of buildings shall be collected in 1 RWH tanks of total 33 KL capacity for harvesting after filtration as per CGWB guidelines.
- (viii) Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter. As proposed, 53 m² of area shall be provided for solid waste management within the premises which will include area for segregation, composting etc. The inert waste from project will be sent to dumping site of Municipality. E-waste shall be disposed through authorised E-waste processor.re-cyclers.
- (ix) Solar based electric power shall be provided to each unit for atleast two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.
- (x) A First Aid Room will be provided in the project both during construction and operations of the project.

(xi)	All the top soil excavated during construction activities should be stored for use in horticulture/ landscape development within the project site.
(xii)	Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
(xiii)	The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environmental (Protection) prescribed for air and noise emission standards.
(xiv)	Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
(xv)	As proposed, no ground water shall be used during construction / operation phase of the project.
(xvi)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
(xvii)	Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
(xviii)	Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.
(xix)	Ambient noise levels should conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
(xx)	Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27 th August, 2003. Ready mixed concrete must be used in building construction.
(xxi)	The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of fire fighting equipment etc as per National Building Code including protection measures from lightening etc.
Оре	ration Phase
ł t	The gaseous emissions from DG set shall be dispersed through adequate stack neight as per CPCB standards. Acoustic enclosure shall be provided to the DG sets o mitigate the noise pollution. Low sulphur diesel shall be used. The location of he DG sets may be decided with in consultation with State Pollution Control Board.
(ii) F	Fresh water requirement from Municipal Water Supplyshall not exceed 7 m ³ /day.
r F	The quantity of fresh water usage, water recycling and rainwater harvesting shall be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports.
i	The installation of the Sewage Treatment Plant (STP) should be certified by an ndependent expert and a report in this regard should be submitted to the Ministry before the project is commissioned for operation. Periodical monitoring of water quality of treated sewage shall be conducted. Necessary measures should be made
	(xii) (xiii) (xiv) (xv) (xvi) (xvii) (xviii) (xviii) (xix) (xix) (xxi) (xxi) (xxi) (xxi) (xxi) (xxi)

	to mitigate the odour problem from STP.
(v)	No sewage or untreated effluent water should be discharged into storm water drain.
(vi)	Solid waste management shall be collected, treated disposed in accordance with the Municipal Solid Waste (Management & Handling) Rules, 2016.
(vii)	Rain water harvesting structure for roof run-off and surface run-off, as plan submitted should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended mater, oil and grease.
(viii)	Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power.
(ix)	Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.
(x)	The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.
M/s. Lak bearing Mumbai, (i) T (ii) T p	MIS/61322/2014] [F.No.21-194/2014-IA.III] eview Developers has proposed for development of slum rehabilitation scheme on plot C.T.S No. 1 (pt) of village Ghatkopar, Hanuman Nagar, Tal. Kurla, Ghatkopar (W), Maharashtra he project is located at Latitude : 19° 06'36.11" N and Longitude :72° 54'59.30"E he total area of the slum plot is 64,219.67sq.mt. The total construction area of the roject is 510205.02 sqm. The proposed FSI area is 190900.08 sqm and non FSI area is 319304.94 sqm. The proposed project comprises of 6 rehab buildings and 2 sale
(iii) T n (/ B (iv) T	uildings. he total 6 nos. of rehab buildings comprises of Building With G + 23 Floors, Building o. 1 with 2LG+ G+ 18 Floors, Building no. 2,3 with 3LG+ G+ 23 Floors ,Building no. 4 A,B,C) with 3LG+ G+23Floors, Building no. 4 (D, E, F) with 3LG+ G+ 22 Floors and uilding no. 5 with 2 LG+ Gr +14 (pt)Floors. he sale building no.1 comprises of Wing A & B with P4 to P7 + St+ 25 Floors, Wing
a V b	to F with P6 to P7 + St+ 25 Floors, Wing H,J,L with Gr + P1 to P7 + St + 25 Floors nd Wing K,M with Gr + P1 to P7 + St + 24 Floors. The sale building no.2 consists of Ving P to S with B+ Gr + P1 to P3 + St + 25 Floors. The maximum height of the rehab uilding is 69.75 mt and for sale building is 106.35 mt. he rehabilitation components of scheme will consists of 1431 nos. of residential
te o s (vi) T	enements, 13 nos. of residential /commercial tenements, 37 nos. of shops, 1224 nos. f PAP, 07 nos. existing amenities and 28 nos. of Balwadis. The sale components of cheme will consists of 2675 nos. of residential units & 36 nos of commercial (shops). he proposed RG area is 4254.42 sqm. Total parking provided will be 442 nos. for
	whab and 1469 nos. for sale. he proposed infrastructure works includes water supply from Municipal Corporation of

- (viii) The total water requirement during operation phase of the project will be 3645 kld out of which fresh water requirement is 2409 kld and recycled water requirement is 1236 kld. The fresh water supply for domestic purpose will depend on the local municipal supplies i.e. Municipal Corporation of Greater Mumbai water supply whereas treated water from sewage treatment plant will be use for flushing and gardening purpose. The arrangement of rainwater harvesting system will be provided which will reduce the demand of fresh water requirement.
- (ix) The total wastewater generated from the project is estimated 3113 KLD. The waste generated will be treated in sewage treatment plant based on MBBR Technology. 6 no. of STP's will be installed. Total 3 STP's for Rehab of capacity (1 x 580 KLD, 1 x 980 KLD and 1 x 85 KLD) and Total 3 STP's for sale of capacity (1 x 700 KLD , 1 x 610 KLD and 1 x 245 KLD ). The treated water from sewage treatment plant will be reclaimed and used for flushing and gardening purpose that will result in minimum consumption of fresh water. The balance water will be discharge to municipal drain.
- (x) Power requirement: The power requirement during operation period will be about 25959.61 KW for connected load and 18443.99 KW for maximum demand load. The power supply will be from Reliance Energy. There will be also provision for DG set in case of emergency. Total 2 no. of DG sets 750 KVA and 1 DG set of capacity 125 for Rehab and 2 DG set of 600 KVA and 1 Dg set of 750 KVA and 2 DG sets of 1010 KVA for Sale will be provided.
- (xi) Solid Waste Management: The total solid waste generated during operation phase will be 13411 kg/day. The biodegradable waste will be 8030 kg/day whereas nonbiodegradable waste will be 5381 kg/day. The biodegradable waste will be composted whereas other will be handed over to authorized vendors / recyclers for the final disposal.
- (xii) Energy efficient fluorescent tube lights & CFL lamps which give approx. 30% more light output for the same watts consumed and therefore require less no of fixtures and corresponding lower point wiring costs
- (xiii) Investment/Cost: The estimated project cost of the project is Rs. 1050 Crores.
- (xiv) RWH: 15 nos. of RWH tank of capacity totaling to 575 cum will be provided for Rehab and 14 nos. of RWH tank of capacity totaling to 700 cum will be provide for Sale.
- (xv) The project is not located in CRZ area.
- (xvi) National Park/ Wild Life Sanctuary in 10 km radius area: Sanjay Gandhi National Park is at distance of 4 km.
- (xvii) Parking facility: Parking facility proposed to be provided as under:-

Area of Flat	Total Flats	Parking Required	Parking
Below 35 sq.mt.	2705	1 For 8 nos.	338.12
			nos.
	338.12		
	nos.		
Add 25% visito	84.53 nos.		
Parking Required	423 nos.		
Pa	442 nos.		

#### Parking Statement -Rehab Building

#### Parking Statement -Sale Building

Sale Bldg - 1& 2 Parking Area Statement					
Area of Flat	Total Flats (Nos)	Parking Required	Parking (Nos)		
Below 35 sq.mt	787	1 For 8 Nos.	98.38		
35 to 45 sq.mt	0.00	1 For 4 Nos.	0.00		

	·				
	45 to 70 sq.mt	1749	1 For 2 Nos.	874.50	
	Above 70 sq.mt	139	1 For 1 Nos.	139.00	
	Total	2675	0() 070	1111.88	
		ors (1111.88 x 25		278	
	Residential Parking		,	1390 nos.	
		• •			
	Total Parking Prop	osed for Sale Blo	lg (1+2) (A+B)	1469 nos.	
letter N PP informed th 25 th January, 2 1,97682.67 m ² 5,10,205.02 sq After detailed d (i) As build beformed (ii) Sta (iii) Efformed (iv) Lay har furr (v) Lay wel (vi) Det (vii) Exo (viii) Pre (ix) Efformed (x) At lager (xi) Sol mathebase (xi) Act	Commerce Total Parking Requ Total Parking Prop etails: The project lo.21-194/2014-IA hat Slum Rehabilitat 2012 has approved . However, PP sul m. The Committee leliberation, the Com per Slum Rehabilitat it-up area is mentio ore EAC the built u uirement of EC for s tus of project propo orts shall be made to yout plan indicating ndling area, rain w hished. yout of parking plan tails of source of wa cess treated sewage diction of ground ley orts shall be made for all be met from solar least 2 solar power heration shall be cor id waste manage nagement scheme. ion plan for manage	ial Parking Requir uired for Sale Bld bosed for Sale Bld bosed for Sale Bld dosed for Mld dosed for Mld dosed for Sale Bld dosed for Sale Bld dosed for Mld dosed for Sale Bld dosed for Sale Bld dosed for Mld dosed for Mld dosed for Mld dosed for Mld dosed for Mld dosed for Sale Bld dosed for Mld dosed for Mld dos	ed -B g (1+2) (A+B) lg (1+2) (A+B) lg (1+2) (A+B) Ferms of Refe larch 2015. e letter no SRA/ herein total buil- bosal in the Mo- is huge difference llowing addition ter dated 25 th Ja 67 m ² . However sed project is 51 -up area. harashtra. r parking for reh- t, drainage, sev- structure, etc. and exit points ght the fire tender vith permission the cheme to be sub- of emissions fro- ty of DG set and the fan shall be d. ngwith area ea- structure, etc.	64 nos. 1454 nos. 1469 nos. 1469 nos. rence by Ma (ENG/843/N/I t-up area is EFCC for built al information al informat	MHL/LOI dated mentioned as uilt up area of up area. approved total sentation made n. PI clarify the P, solid waste colour to be movement as ed. to DG sets. standby power each flat. Solar r solid waste
<b>(xiii)</b> Mai fugi	nagement of excav	ated soil. Pollution g construction ph	on control meas ase including m	sures to be ta arble /stone o	cutting.
pro use det	tails energy conser posal such as orier of ECBC complian ails in the proposal rout plan indicating (	ntation to suppor It envelope meas	t reduced heat ures to be supp	gain, use of orted through	ASHRAE 90.1, n drawings and
The proposal	was deferred till the	e desired inform	ation is submit	·	

*******

# LIST OF PARTICIPANTS OF EAC (INFRASTRUCTURE-2) IN 13th MEETING OF EAC (INFRASTRUCURE-2) HELD ON 23-25 JANUARY, 2017

Sr. No.	Name & Address	Position	Attendance
1.	Prof. T. Haque	Chairman	Р
2.	Shri K. Gowarappan	Member	Р
3	Dr. Yashpal Singh	Member	А
7	Dr. S.K. Bhargava	Member	Р
5	Dr.Chandrahas Deshpande	Member	А
6	Dr.AyiVaman N. Acharya	Member	P (1 st & 2 nd Day)
7	Shri A.P. Singh	Member	P (1 st & 3 rd Day)
8	Ms. MiliMajumdar	Member	A
9	Prof.Dr. Sanjay Gupta	Member	P (1 st Day)
MOEF&0			
10	Sh. A N Singh	Joint Director and Member Secretary	Р